

Technical Information Sheet

Image Coming Soon

QuickSeam™ II Professional Kit

Item Description	Item Number
Seaming Kit	W56RAC180L

Description

This professional grade seaming kit contains all the items necessary to complete 7.01 m (25.0') of seams for approved Elevate membranes. Included with the kit are step by step instructions on how to complete the seaming process.

Storage

- Store in original unopened containers at temperatures between 15.6 - 26.7 °C (60 – 80 °F) until ready for use.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep the material out of direct sunlight until ready for application.

Shelf Life

- Shelf life of one (1) year can be expected if stored in original unopened container at temperatures between 15.6 - 26.7 °C (60 – 80 °F).
- Shelf life will be shortened if exposed to elevated temperatures.
- Rotate stock to insure stored material will not go beyond the shelf life of one (1) year.

Packaging

The carton contains all items listed in the Product Data section.

Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
- Red caution labels are required when shipping.

- Use only in well ventilated areas.
- Avoid contact with skin. Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
- Use only in conjunction with QuickScrubber™ pad and handle. Do not apply with rollers, brushes, or rags.
- Mix thoroughly before and during use.
- Thinning is not allowed.
- Keep out of reach of children.
- Dispose as a hazardous waste in accordance with local, state, and federal regulations.
- Recommended cleaner is rubbing alcohol followed by soap and water.
- Do not contaminate with foreign materials.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Item	Quantity
QuickSeam Cover Strip	7.01 m of 152.4 mm (25.0' of 6.0") QuickSeam Cover Strip (See QuickSeam Cover Strip for more info)
Single-Ply LVOC Primer™	1 can (0.47 l, 1 pint) (See Single-Ply LVOC Primer for more info)
QuickScrubber Handle	1 each
QuickScrubber Pad	1 each
Seam Roller	1 each
Special Crayon	1 each
Instructions	1 each

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.