

Technical Information Sheet



QuickSeam™ R.M.A. Strip

| Item Description | Item Number |
|------------------|-------------|
| 100' Roll | W56RAC16330 |

Description

Elevate QuickSeam R.M.A. Strip is a 10" (254 mm) wide RubberGard™ MAX EPDM membrane with two 3" (76 mm) wide strips of QuickSeam tape factory laminated to it along its length. It is used for roof membrane attachment beneath RubberGard membrane as additional membrane securement as specified in Elevate specifications and details. QuickSeam R.M.A. is also used for membrane securement in Elevate's RubberGard R.M.A. (Reinforced Mechanically Attached) Roofing System.

Method of Application

1. Unroll the QuickSeam R.M.A. Strip with the release paper facing up.
2. Anchor the QuickSeam R.M.A. Strip using Elevate 2" Metal Seam Plates, V-Plates or batten strips and Elevate fasteners 12" (305 mm) o.c. maximum per current Elevate specifications and details.
3. Position EPDM membrane over QuickSeam R.M.A. Strip with release paper in place and allow membrane to relax.
4. Fold back EPDM membrane to expose the R.M.A. Strip.
5. Prime the EPDM to be spliced to the tape using QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime Primer or Single-Ply LVOC Primer, applied with QuickScrubber™ or QuickScrubber Plus pad and handle.
6. Use touch-push test to determine when primer is flashed-off and ready to be mated to the tape.
7. Remove the release paper from the tape.
8. Roll the primed EPDM membrane onto the tape.
9. Mate the membrane by pressing down using a clean QuickScrubber Plus Pad and Handle, then roll the EPDM membrane over the QuickSeam R.M.A. with a 1½" (38 mm) wide silicone hand roller to ensure proper adhesion.
10. Refer to application instructions at: www.HolcimElevate.com.

Packaging

1 roll, 100' (30.5 m) roll, 1 roll per carton, 36 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Storage

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life

Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Prescott, AR • Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



| Typical Properties | | | |
|--------------------|-------------------------------------|---|----------------------------|
| QuickSeam Tape | | Membrane | |
| Property | Value | Property | Value |
| Base | Rubber Polymers | Base | EPDM |
| Color | Black | Color | Black |
| Solvents | None | Solvents | None |
| Solids | 100% | Thickness | 0.060" (1.52 mm) ± 20% |
| Specific Gravity | 98 ± 0.02 (H2O =1) | Width | 10" + 0, - 0.125" (254 mm) |
| Cured State | Cured | NOTE: Refer to Technical Information Sheet for RubberGard EPDM MAX for additional information. | |
| Thickness | 0.025" (0.63 mm) ± 0.007" (0.18 mm) | | |
| Width | 3" (76 mm) -0, + 0.125" mm | | |

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.