

## 1. Identification

<b>Product identifier</b>	<b>Elevate SA Primer</b>
<b>Other means of identification</b>	
<b>Product code</b>	W70RACSAP5
<b>Recommended use</b>	Construction. Adhesive.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Distributed by</b>	Holcim Solutions and Products US, LLC
<b>Address</b>	26 Century Boulevard, Suite 205 Nashville, TN 37214 Elevate™ is a Holcim Solutions and Products US, LLC brand.
<b>Website</b>	holcimelevate.com
<b>Telephone Number</b>	1-800-428-4442
<b>Emergency Telephone Number</b>	For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:  CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system)
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (central nervous system) through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it before reuse. In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. Collect spillage.

### Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	CAS number	%
Heptane	142-82-5	0 - 50*
Naphtha (petroleum), hydrotreated light	64742-49-0	0 - 50*
Toluene	108-88-3	40 - 50
Polymethylene polyphenylene isocyanate	9016-87-9	0.1 - <1
Methylene Diphenyl Diisocyanate	101-68-8	0.1 - <1
Nonylphenol	84852-15-3	0.1 - <1

### Composition comments

\*Product contains CAS 142-82-5 or CAS 64742-49-0.

All concentrations are in percent by weight unless otherwise indicated.  
Components not listed are either non-hazardous or are below reportable limits.  
Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
<b>5. Fire-fighting measures</b>	
<b>Suitable extinguishing media</b>	Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ). Water fog. Larger fires: Water spray.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides (CO <sub>x</sub> ). Hydrogen Bromide (HBr). Hydrocarbons. Nitrogen Oxides (NO <sub>x</sub> ).
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. A vapor-suppressing foam may be used to reduce vapors. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Heptane (CAS 142-82-5)	PEL	2000 mg/m <sup>3</sup>
		500 ppm
Methylene Diphenyl Diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m <sup>3</sup>
		0.02 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m <sup>3</sup>
		100 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Methylene Diphenyl Diisocyanate (CAS 101-68-8)	TWA	0.005 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m <sup>3</sup>
		440 ppm
	TWA	350 mg/m <sup>3</sup>
Methylene Diphenyl Diisocyanate (CAS 101-68-8)	Ceiling	85 ppm
		0.2 mg/m <sup>3</sup>
	TWA	0.02 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	0.05 mg/m <sup>3</sup>
		0.005 ppm
	TWA	400 mg/m <sup>3</sup>
Toluene (CAS 108-88-3)	STEL	100 ppm
		560 mg/m <sup>3</sup>
	TWA	150 ppm
		375 mg/m <sup>3</sup>
		100 ppm

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

## Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear safety glasses with side shields (or goggles). Face shield is recommended.

### Skin protection

#### Hand protection

Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Fluoroelastomer (FKM). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol (PVA). Suitable gloves can be recommended by the glove supplier.

### Skin protection

#### Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge and full facepiece. Appropriate respirator selection should be made by a qualified professional.

### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

## General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

### Appearance

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Black.

### Odor

Characteristic.

### Odor threshold

Not available.

### pH

Not determined; product is not soluble in water.

### Melting point/freezing point

Not determined.

### Initial boiling point and boiling range

208.4 °F (98 °C)

### Flash point

24.8 °F (-4 °C) Closed Cup

### Evaporation rate

Not available.

### Flammability (solid, gas)

Not applicable.

### Upper/lower flammability or explosive limits

Explosive limit - lower (%) 1.1

Explosive limit - upper (%) 7

### Vapor pressure

48 hPa (68 °F (20 °C))

	36 mmHg (68 °F (20 °C))
<b>Vapor density</b>	Not determined.
<b>Relative density</b>	0.791 (68 °F (20 °C))
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble.
<b>Partition coefficient (n-octanol/water)</b>	Not applicable, product is a mixture.
<b>Auto-ignition temperature</b>	Not self-igniting.
<b>Decomposition temperature</b>	Not applicable as the product is not unstable.
<b>Viscosity</b>	Not available.
<b>Other information</b>	Ignition temperature: 215 °C (419 °F) Organic solvents: 83% Solids content: 17%
<b>Density</b>	6.58 lbs/gal
<b>Explosive properties</b>	Not explosive.
<b>Kinematic viscosity</b>	Not determined.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC</b>	> 650 - < 660 g/l > 5.42 - < 5.51 lb/gal

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
---	--

### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
Heptane (CAS 142-82-5)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 29.29 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	15000 mg/kg

Components	Species	Test Results
Methylene Diphenyl Diisocyanate (CAS 101-68-8)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 2.24 mg/l, 1 Hours
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 2920 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 23300 mg/m <sup>3</sup>
<b>Oral</b>		
LD50	Rat	> 5840 mg/kg
Nonylphenol (CAS 84852-15-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	2031 mg/kg
<b>Oral</b>		
LD50	Rat	1200 mg/kg
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 10000 mg/kg
<b>Inhalation</b>		
<i>Mist</i>		
LC50	Rat	> 490 mg/m <sup>3</sup> , 4 Hours
<b>Oral</b>		
LD50	Rat	> 10000 mg/kg
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12200 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	28.1 mg/l, 4 Hours
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Suspected of causing cancer.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Methylene Diphenyl Diisocyanate (CAS 101-68-8)	3 Not classifiable as to carcinogenicity to humans.	
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)	3 Not classifiable as to carcinogenicity to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
<b>NTP Report on Carcinogens</b>		
Not listed.		
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>		
Not listed.		

<b>Reproductive toxicity</b>	Possible reproductive hazard. Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs (central nervous system) through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Nonylphenol (CAS 84852-15-3)			
<b>Aquatic</b>			
<i>Acute</i>			
Algae	EC50	Scenedesmus subspicatus	1.3 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna	0.085 mg/l, 48 Hours
Fish	LC50	Pimephales promelas	0.128 mg/l, 96 Hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	24 µg/l, 21 days
Fish	NOEC	Pimephales promelas	0.0074 mg/l, 33 days
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days

**Persistence and degradability** There are no data on the degradability of this product.

**Bioaccumulative potential** No data available for this product.

### Partition coefficient n-octanol / water (log Kow)

Heptane (CAS 142-82-5)	4.66
Methylene Diphenyl Diisocyanate (CAS 101-68-8)	5.22
Nonylphenol (CAS 84852-15-3)	5.71
Toluene (CAS 108-88-3)	2.73

**Mobility in soil** No data available.

**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



## 14. Transport information

### DOT

UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

### IATA

UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

### IMDG

UN number	UN1133
UN proper shipping name	ADHESIVES
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Nonylphenol (CAS 84852-15-3) 1.0 % One-Time Export Notification only.

### TSCA Chemical Action Plans, Chemicals of Concern

Methylene Diphenyl Diisocyanate (CAS 101-68-8)	Methylene Diphenyl Diisocyanate (MDI) And Related Compounds Action Plan [RIN 2070-ZA15]
Nonylphenol (CAS 84852-15-3)	Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action Plan
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)	Methylene Diphenyl Diisocyanate (MDI) And Related Compounds Action Plan [RIN 2070-ZA15]

### CERCLA Hazardous Substance List (40 CFR 302.4)

Heptane (CAS 142-82-5)	Listed.
Methylene Diphenyl Diisocyanate (CAS 101-68-8)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Toluene (CAS 108-88-3)	Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**Toxic Substances Control Act (TSCA)**

All components of the mixture on the TSCA 8(b) inventory are designated "active".

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitization  
 Carcinogenicity  
 Reproductive toxicity  
 Specific target organ toxicity (single or repeated exposure)  
 Aspiration hazard

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Toluene	108-88-3	40 - 50

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Methylene Diphenyl Diisocyanate (CAS 101-68-8)

Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

**US state regulations****US. Massachusetts RTK - Substance List**

Heptane (CAS 142-82-5)

Methylene Diphenyl Diisocyanate (CAS 101-68-8)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Toluene (CAS 108-88-3)

**US. New Jersey Worker and Community Right-to-Know Act**

Heptane (CAS 142-82-5)

Methylene Diphenyl Diisocyanate (CAS 101-68-8)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Nonylphenol (CAS 84852-15-3)

Polymethylene polyphenylene isocyanate (CAS 9016-87-9)

Toluene (CAS 108-88-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Heptane (CAS 142-82-5)

Methylene Diphenyl Diisocyanate (CAS 101-68-8)

Toluene (CAS 108-88-3)

**US. Rhode Island RTK**

Heptane (CAS 142-82-5)

Methylene Diphenyl Diisocyanate (CAS 101-68-8)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Toluene (CAS 108-88-3)

## California Proposition 65



**WARNING:** This product can expose you to Carbon black, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black (CAS 1333-86-4)	Listed: February 21, 2003
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988

### California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)	Listed: January 1, 1991
------------------------	-------------------------

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Heptane (CAS 142-82-5)  
Methylene Diphenyl Diisocyanate (CAS 101-68-8)  
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
Nonylphenol (CAS 84852-15-3)  
Polymethylene polyphenylene isocyanate (CAS 9016-87-9)  
Toluene (CAS 108-88-3)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 20-March-2023  
**Revision date** -  
**Version #** 01  
**HMIS® ratings** Health: 3\*  
Flammability: 3  
Physical hazard: 0

**Disclaimer** Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.