

# Technical Information Sheet



## SkyScape™ Slope Drainage

Item Description
Slope Drainage: 39" x 185' (1 m x 56.4 m)

### Description

SkyScape Slope Drainage is a thin drainage composite consisting of a post-industrial recycled white polypropylene drainage core and a very strong but lightweight white filter fabric thermally bonded to one side. The SkyScape Slope Drainage allows proper air flow throughout the system.

### Method of Application

Starting from one corner of the highest point of the roof, unroll SkyScape Slope Drainage. Sides and ends may be abutted together.

### Storage

- Deliver and store products in original packaging with manufacturer's labels and materials list intact and signed off.
- Store products in designated weather protected areas, elevated from ground, and protected from environmental damage.

### Shelf Life

Indefinite

### Coverage Rate

600 ft<sup>2</sup> (55.7 m<sup>2</sup>) per roll

### Clean-Up

- Gather and dispose all debris upon completion of work.
- Clean all surfaces and inspect final assembly for approval.

## LEED® Information

Post-Consumer Recycled Content:	40%
Post Industrial Recycled Content:	0%
Manufacturing Location:	Murfreesboro, TN

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Property	Value
Dimension	39" x 185' (1 m x 56.4 m)
Fabric Weight	2.95 oz/yd <sup>2</sup> (643 g/m <sup>2</sup> )
Thickness	0.30" (7.6 mm)
Total Weight	18.95 oz/yd <sup>2</sup> (643 g/m <sup>2</sup> )
Grab Strength MD/CD	125 lb (57/kg)
Flow Rate at 1000 psf	9.71 gal/min/ft (121 L/min/m)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.