

Technical Information Sheet



UltraPly™ QuickSeam™ Reinforced Perimeter Fastening (RPF) Strip

Item Description	Item Number
White	W56TPO30T1

Description

UltraPly QuickSeam Reinforced Perimeter Fastening Strip is a 6" (152 mm) wide UltraPly TPO membrane with 3" (76 mm) wide tape factory laminated along one edge. It is used for non-penetrating flashings as specified in Elevate Specifications and Details.

Method of Application

1. Unroll the UltraPly QuickSeam Reinforced Perimeter Fastening Strip P (UPQSRPF Strip) with the release paper up and the tape portion farthest away from the wall or penetration.
2. Anchor UPQSRPF Strip P using Heavy Duty or Heavy Duty Plus seam plates and fasteners 12" (305 mm) o.c. maximum per current base tie-in details.
3. Position UltraPly TPO membrane over UPQSRPF Strip P with release paper in place and allow membrane to relax.
4. Fold back UltraPly TPO membrane to expose the tape.
5. Prime the UltraPly TPO to be spliced to the tape using Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer and QuickScrubber™ or QuickScrubber Plus pad and handle per current procedures.
6. Use touch-push test to determine when the primer is completely dry and ready to be mated to the tape.
7. Remove the release paper.
8. Roll the primed UltraPly TPO membrane into the tape.
9. Bond the portion of the UPQSRPF without tape to the membrane using an approved Elevate Bonding Adhesive.
10. Roll the UltraPly TPO membrane over the UPQSRPF Strip with a 1½" (38 mm) wide silicone hand roller to ensure proper adhesion.
11. Refer to current Elevate installation instructions and details for additional information.

Storage

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions

- Do not use UltraPly QuickSeam Reinforced Perimeter Strip P with UltraPly TPO XR membranes.
- The use of metal or polymer batten bar is not acceptable.
- Refer to Safety Data Sheets (SDS) for additional safety information.

LEED® Information

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Properties	Value
QuickSeam Tape	
Base	Rubber Polymers
Color	White
Solvents	None
Solids	100%
Specific Gravity	98 ± 0.02 (H2O = 1)
Cured State	Cured
Thickness	0.030" (0.77 mm) ± 0.007" (0.18 mm)
Width	3" (76 mm) + 0, - 0.125"
UltraPly TPO	
Base	TPO
Color	White
Solvents	None
Thickness	0.050" (1.26 mm) ± 20%
Width	6" + 0, -0.125"
NOTE: Refer to Technical Information Sheet for UltraPly TPO for additional information.	

Packaging	
Roll	100' (30.5 m) roll length, 2 rolls per carton, 21 cartons per pallet
NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.	

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.