

1. Identification

Product identifier	Elevate UltraPly TPO General Purpose Sealant
Other means of identification	
Product code	W56TPO3002
Recommended use	Construction. Sealant.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Distributed by	Holcim Solutions and Products US, LLC
Address	26 Century Boulevard, Suite 205 Nashville, TN 37214 Elevate™ is a Holcim Solutions and Products US, LLC brand.
Website	holcimelevate.com
Telephone Number	1-800-428-4442
Emergency Telephone Number	For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident: CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards	Flammable solids	Category 1
Health hazards	Skin corrosion/irritation	Category 2
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	

Label elements

Signal word	Danger
Hazard statement	Flammable solid. Causes skin irritation. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/eye protection/face protection.
Response	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use carbon dioxide, dry powder, water fog to extinguish.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	7 - 13
Solvent naphtha (petroleum), medium aliph.	64742-88-7	1 - 5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	< 2.5
Titanium Dioxide	13463-67-7	< 2.5
Quartz (SiO ₂)	14808-60-7	< 0.5

Composition comments

All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed such as: Carbon oxides (CO_x).

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Flammable solid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation.

Conditions for safe storage, including any incompatibilities

Keep away from heat, spark, open flames and other sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Components	Type	Value
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.05 mg/m ³

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³	
		500 ppm	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	PEL	400 mg/m ³	
		100 ppm	
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	PEL	400 mg/m ³	
		100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	IDLH	2500 mg/m3
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	IDLH	1 %
		1000 ppm
Quartz (SiO2) (CAS 14808-60-7)	IDLH	50 mg/m3
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	IDLH	1 %
		1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	TWA	400 mg/m3	
		100 ppm	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Nitrile. Nitrile butyl rubber (NBR). Chloroprene rubber. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other

Wear appropriate chemical resistant clothing.

Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Appropriate respirator selection should be made by a qualified professional.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Paste.
Color	White.
Odor	Petroleum-like.
Odor threshold	Not available.
pH	Not determined.
Melting point/freezing point	Not determined.
Initial boiling point and boiling range	267.8 °F (131 °C)
Flash point	< 77 °F (< 25 °C)
Evaporation rate	9.2 (68 °F (20 °C))
Flammability (solid, gas)	Flammable solid.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit - upper (%)	Not applicable, material is a solid.

Vapor pressure	Not determined.
Vapor density	3.8
Relative density	1.35 (68 °F (20 °C))

Solubility(ies)

Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.

Auto-ignition temperature	509 °F (265 °C)
Decomposition temperature	Not applicable as the product is not unstable.

Viscosity	Not available.
------------------	----------------

Other information	Solids: 83.6% Organic solvents: 16.4%
--------------------------	--

Density	11.8499 lb/gal 1.42 g/cm ³
----------------	--

Explosive properties	Not explosive.
-----------------------------	----------------

Kinematic viscosity	> 20.5 cSt
----------------------------	------------

Oxidizing properties	Not oxidizing.
-----------------------------	----------------

VOC	< 250 g/l
------------	-----------

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

Chemical stability	Material is stable under normal conditions.
---------------------------	---

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
---	---

Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
----------------------------	---

Incompatible materials	Acids. Strong oxidizing agents. Fluorine.
-------------------------------	---

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Aerosol</i>		
LC50	Rat	> 5.53 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rat	> 2920 mg/kg
Inhalation		
LC50	Rat	> 23300 mg/m ³
Oral		
LD50	Rat	> 5840 mg/kg
Quartz (SiO ₂) (CAS 14808-60-7)		
Chronic		
Inhalation		
LOEC	Human	0.0563 mg/m ³
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 5.28 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Titanium Dioxide (CAS 13463-67-7)		
Acute		
Inhalation		
LC50	Rat	> 6.82 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust. Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	3 Not classifiable as to carcinogenicity to humans.
Quartz (SiO ₂) (CAS 14808-60-7)	1 Carcinogenic to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Quartz (SiO ₂) (CAS 14808-60-7)	Known To Be Human Carcinogen.
---	-------------------------------

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO ₂) (CAS 14808-60-7)	Cancer
---	--------

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	The product is soluble in water.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1325
UN proper shipping name	Flammable solids, organic, n.o.s. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RQ = 885 LBS; Solvent Naphtha (petroleum), Medium Aliph. RQ = 2273 LBS)
Transport hazard class(es)	
Class	4.1
Subsidiary risk	-

Label(s)	4.1
Packing group	II
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	A1, IB8, IP2, IP4, T3, TP33
Packaging exceptions	151
Packaging non bulk	212
Packaging bulk	240

IATA

UN number	UN1325
UN proper shipping name	Flammable solid, organic, n.o.s. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Solvent Naphtha (petroleum), Medium Aliph.)
Transport hazard class(es)	
Class	4.1
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1325
UN proper shipping name	FLAMMABLE SOLID, ORGANIC, N.O.S. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Solvent Naphtha (petroleum), Medium Aliph.)
Transport hazard class(es)	
Class	4.1
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-A, S-G
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	Listed.
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO ₂) (CAS 14808-60-7)	Cancer lung effects immune system effects kidney effects
---	---

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes
Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Quartz (SiO₂) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Quartz (SiO₂) (CAS 14808-60-7)

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Quartz (SiO₂) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Quartz (SiO₂) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 28-February-2023

Revision date 02-August-2023

Version # 02

HMIS® ratings Health: 2
Flammability: 1
Physical hazard: 0
Personal protection: D

Disclaimer Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.