SAFETY DATA SHEET



1. Identification

ELEVATE Water Based Bonding Adhesive P Product identifier

Other means of identification

Product code W563587038

Recommended use Construction. Sealant.

Recommended restrictions Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Holcim Solutions and Products US, LLC Distributed by

Address 26 Century Boulevard, Suite 205

Nashville, TN 37214

Elevate™ is a Holcim Solutions and Products US, LLC brand.

Website holcimelevate.com **Telephone Number** 1-800-428-4442

Emergency Telephone

Number

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Not classified. **Physical hazards**

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1 Carcinogenicity Category 2

Hazardous to the aquatic environment, acute **Environmental hazards** Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. **Hazard statement**

Suspected of causing cancer. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Category 3

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist/vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear

protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before

reuse.

Store locked up. Storage

ELEVATE Water Based Bonding Adhesive P

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Vinyl acetate	108-05-4	0.1 - 1
2-methylisothiazol-3(2H)-one	2682-20-4	0.1 - 1

Composition comments

All concentrations are in percent by weight.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides (COx).

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Absorb spillage with suitable absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

ELEVATE Water Based Bonding Adhesive P

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.

Conditions for safe storage. including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Туре	Value	
Vinyl acetate (CAS 108-05-4)	STEL	15 ppm	
	TWA	10 ppm	
US. NIOSH: Pocket Guide to C	Chemical Hazards		
Components	Туре	Value	
Vinyl acetate (CAS 108-05-4)	Ceiling	15 mg/m3	
		4 ppm	

Biological limit values

Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

shower

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include:

Nitrile. Nitrile butyl rubber (NBR). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl

chloride (PVC). Suitable gloves can be recommended by the glove supplier.

Skin protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

Liquid. Physical state Liquid. **Form** Color Pink Odor Mild.

Odor threshold Not available.

7 - 9

32 °F (0 °C) Melting point/freezing point

3/7 968086 Version #: 02 Revision date: 11-April-2024 Issue date: 11-April-2024

Initial boiling point and boiling 212 °F (100 °C)

range

Flash point Not applicable.

Evaporation rate 0.4 (Butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 18 mbar (68 °F (20 °C))

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Dispersible.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Partition coefficient Not applicable.

(oil/water)

VOC < 1 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Mineral acids.

Hazardous decomposition

products

Carbon oxides. Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause gastrointestinal discomfort and irritation.

Symptoms related to the physical, chemical and

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

toxicological characteristics Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

Components Species Test Results

Vinyl acetate (CAS 108-05-4)

Acute Inhalation Vapor

Rat 14.1 mg/l, 4 Hours

ELEVATE Water Based Bonding Adhesive P

968086 Version #: 02 Revision date: 11-April-2024 Issue date: 11-April-2024

Species Test Results Components

Oral

LD50 Rat 2500 mg/kg

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Vinyl acetate (CAS 108-05-4) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Toxic to aquatic life. Harmful to aquatic life with long lasting effects. **Ecotoxicity**

Components **Test Results Species**

Vinyl acetate (CAS 108-05-4)

Aquatic

Algae EC50 Pseudokirchnerella subcapitata 12.7 mg/l, 72 Hours LC50 Crustacea Daphnia magna 12.6 mg/l, 48 Hours Fish NOEC Pimephales promelas 0.55 mg/l, 34 days

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Vinyl acetate (CAS 108-05-4) 0.73

Mobility in soil No data available. No data available. Other adverse effects

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-methylisothiazol-3(2H)-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Vinvl acetate (CAS 108-05-4) Listed.

SARA 304 Emergency release notification

Acetic acid ethenyl ester; Vinyl acetate; Vinyl acetate 5000 LBS

monomer (CAS 108-05-4)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
--------------------------	------------------------------------	--	--	--

Vinyl acetate 108-05-4 5000 1000 Yes

SARA 311/312 Hazardous

chemical

Skin corrosion or irritation

Classified hazard categories

Serious eve damage or eve irritation

Respiratory or skin sensitization

Carcinogenicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Vinyl acetate	108-05-4	01-1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Vinyl acetate (CAS 108-05-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Vinyl acetate (CAS 108-05-4)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Vinyl acetate (CAS 108-05-4)

US. New Jersey Worker and Community Right-to-Know Act

Vinyl acetate (CAS 108-05-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Vinyl acetate (CAS 108-05-4)

US. Rhode Island RTK

Vinyl acetate (CAS 108-05-4)

ELEVATE Water Based Bonding Adhesive P 968086 Version #: 02 Revision date: 11-April-2024 Issue date: 11-April-2024 6/7

SDS US

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Taiwan

country(s).

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date11-April-2024Revision date11-April-2024

Version # 02

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0

Disclaimer Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this

Taiwan Chemical Substance Inventory (TCSI)

information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper

use. The information in the sheet was written based on the best knowledge and experience

currently available.

ELEVATE Water Based Bonding Adhesive P

968086 Version #: 02 Revision date: 11-April-2024 Issue date: 11-April-2024 7 / 7

Yes