



# BlueRibbon®

Rated Sheathing

buildgpc.com



**BlueRibbon® Rated Sheathing** is an excellent oriented strand board (OSB) choice for floor, wall and roof sheathing in residential and light commercial construction applications. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays. BlueRibbon Rated Sheathing is edge coated to limit absorption and pick-up of moisture.

### Available Sizes\*

#### Square Edge

- 3'-11<sup>7</sup>/<sub>8</sub>" (1.216 m) x 7'-11<sup>7</sup>/<sub>8</sub>" (2.435 m) – sized for 4' x 8'
- 3'-11<sup>7</sup>/<sub>8</sub>" (1.216 m) x 8'-11<sup>7</sup>/<sub>8</sub>" (2.740 m) – sized for 4' x 9'
- 3'-11<sup>7</sup>/<sub>8</sub>" (1.216 m) x 9'-11<sup>7</sup>/<sub>8</sub>" (3.044 m) – sized for 4' x 10'

\*Custom panels up to 26' are also available.

#### Tongue & Groove

- 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 7'-11<sup>7</sup>/<sub>8</sub>" (2.435 m) – sized for 4' x 8'
- 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 8'-11<sup>7</sup>/<sub>8</sub>" (2.740 m) – sized for 4' x 9'
- 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 9'-11<sup>7</sup>/<sub>8</sub>" (3.044 m) – sized for 4' x 10'

### Building Code Performance Categories, Panel Thickness

- 7/16 CAT – 0.418" (10.61 mm)
- 15/32 CAT – 0.451" (11.45 mm)
- 1/2 CAT – 0.483" (12.26mm)
- 19/32 CAT – 0.578" (14.68 mm)
- 23/32 CAT – 0.703" (17.85 mm)
- 1-1/8 CAT – 1.091" (27.71 mm)

### Specifications

<b>Length/Width Tolerance</b>	±1 <sup>1</sup> / <sub>6</sub> " (±1.6 mm)
<b>Straightness Tolerance</b>	±1 <sup>1</sup> / <sub>6</sub> " (±1.6 mm)
<b>Squareness Tolerance</b>	±1 <sup>1</sup> / <sub>8</sub> " (±3.2 mm)
<b>Testing Agency</b>	APA® – The Engineered Wood Association
<b>Classification</b>	<b>Exposure 1</b> – Rated sheathing suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.
<b>Code Fire Classification</b>	Class III or C
<b>Flame Spread Rating</b>	76-200, smoke-developed index <450
<b>Building Code Compliance</b>	PS 2-10

### Other Information

<b>Forestry Certification</b>	BlueRibbon Rated Sheathing is made from wood sourced through a system that is third-party certified to the Sustainable Forestry Initiative® procurement standard.
<b>Green Building Programs</b>	See our BlueRibbon Rated Sheathing Sustainability Fact Sheet available at <a href="http://www.builditbetter.com">www.builditbetter.com</a> for more information on potential point contributions towards specific green building programs.
<b>NGBS Green Certified</b>	BlueRibbon Rated Sheathing is Home Innovation NGBS Green Certified for Resource Efficiency and Indoor Environmental Quality. Please visit <a href="http://HomeInnovation.com/Green">HomeInnovation.com/Green</a> for more information.



# SPECIFICATIONS



# BlueRibbon®

Rated Sheathing

[buildgp.com](http://buildgp.com)

- Product Warranty** BlueRibbon® Rated Sheathing is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at [www.builditbetter.com](http://www.builditbetter.com).
- International Shipping** To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. **Pallets made with engineered wood, including BlueRibbon Rated Sheathing, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing," [www.PerformancePanels.com](http://www.PerformancePanels.com))
- Formaldehyde Emissions** BlueRibbon Rated Sheathing contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the Manufactured Home Construction and Safety Standards.

**Manufacturing Locations**

Location	APA Mill Number	Zip Code	Harvest Radius
Brookneal, VA	451	24528	100 miles
Clarendon, SC	532	29001	80 mile
Englehart, ONT, CA	530	P0J 1H0	50 miles
Fordyce, AR	475	71742	100 miles
Hosford, FL	500	32334	75 miles

For installation instructions, specifications and warranty, please visit [buildgp.com/warranties](http://buildgp.com/warranties) | 800-284-5347



Blue Ribbon, Georgia-Pacific and the BlueRibbon and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA is a registered trademark of APA-The Engineered Wood Association. Sustainable Forestry Initiative, SFI, and SFI logo are trademarks of Sustainable Forestry Initiative, Inc. The Home Innovation NGBS Green Certified logo is a trademark of Home Innovation Research Labs. ©2022 Georgia-Pacific Wood Products LLC. All rights reserved. Rev. 10/22 GP-TM Lit. Item #512105.