

SAFETY DATA SHEET

1. Identification

Product identifier	Glass Mat Faced Gypsum Panels
Product list	Product List A DensArmor Plus® Interior Panel DensArmor Plus® Fireguard® Abuse-Resistant Panels DensArmor Plus® Fireguard® Impact-Resistant Panels DensArmor Plus® Fireguard® Interior Panels DensDeck® Prime Roof Board DensDeck® Roof Board DensDeck® Prime Fireguard® Roof Board DensDeck® Fireguard® Roof Board DensDeck® StormX™ Prime Roof Board DensElement® Sheathing DensGlass® Fireguard® Sheathing DensGlass® Shaftliner DensGlass® Sheathing DensShield® Fireguard® Tile Backer DensShield® Tile Backer Product List B DensArmor Plus® Fireguard C® Interior Panels
Other means of identification	
Product code	GP-71C
Recommended use	Products accommodate a wide range of wall, floor, ceiling and roof applications.
Recommended restrictions	None known.

Manufacturer/Importer/Supplier/Distributor information

Company name	Georgia-Pacific Gypsum LLC	
Address	133 Peachtree Street, NE Atlanta, GA 30303	
Telephone	Technical Information	800.225.6119
	(M)SDS Request	404.652.5119
E-mail	Not available.	
Emergency phone number	Chemtrec - Emergency	800.424.9300

2. Hazard(s) identification

Emergency overview	Cutting, sanding, or otherwise working with this product may generate large amounts of dust. Dust may be irritating to eyes, skin and respiratory system.
Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling. Get medical advice/attention if you feel unwell.
Storage	Store away from incompatible materials (see Section 10 of the SDS).
Disposal	Dispose of contents/container in accordance with applicable regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM SULFATE DIHYDRATE		10101-41-4	80 - 100
VERMICULITE**		1318-00-9	0 - 10
CONTINUOUS FILAMENT GLASS FIBER		65997-17-3	1 - 5
CRYSTALLINE SILICA (QUARTZ)*		14808-60-7	0.1 - 1

Composition comments ** Found in products in List B, Section 1 of this SDS.

Gypsum (calcium sulfate, dihydrate) and vermiculite contain naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

*The weight percent for crystalline silica represents total crystalline silica and not the respirable fraction. Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

4. First-aid measures

Inhalation	If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.
Skin contact	For skin contact, wash immediately with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub the eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. May result in obstruction and irritation if ingested. Get medical attention.
Most important symptoms/effects, acute and delayed	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Firefighters should wear full protective clothing including self contained breathing apparatus.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Use personal protection recommended in Section 8. Keep unnecessary personnel away.
--	---

Methods and materials for containment and cleaning up

Avoid the generation of dusts during clean-up. Collect dust using a vacuum cleaner equipped with HEPA filter. This product is miscible in water. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Minimize dust generation. Sweep up or gather material and place in an appropriate container for disposal. Utilize wet methods, if appropriate, to minimize dust. For waste disposal, see section 13 of the SDS.

Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

7. Handling and storage**Precautions for safe handling**

Practice good housekeeping. Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Do not get this material in contact with eyes. Do not taste or swallow. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate NIOSH/MSHA approved dust mask or filtering facepiece if dust is generated. Do not eat or drink while using the product. Wash hands before eating, drinking, or smoking.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store level and keep dry. Dewpoint or other conditions causing the presence of moisture can damage the product during storage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	PEL	0.05 mg/m ³	Respirable dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
VERMICULITE** (CAS 1318-00-9)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

ACGIH

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	3 mg/m ³	Respirable Particles.
CONTINUOUS FILAMENT GLASS FIBER (CAS 65997-17-3)	TWA	5 mg/m ³	Inhalable fraction.
VERMICULITE** (CAS 1318-00-9)	TWA	3 mg/m ³	Respirable particles.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	10 mg/m ³	Inhalable fraction.
CONTINUOUS FILAMENT GLASS FIBER (CAS 65997-17-3)	TWA	1 fibers/cm ³	Fiber.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
VERMICULITE** (CAS 1318-00-9)	TWA	10 mg/m ³	Inhalable particles.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	IDLH	50 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

Appropriate engineering controls

Score and snap method recommended. When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Safety glasses or goggles are recommended when using this product. Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Eye wash fountain is recommended.

Skin protection**Hand protection**

For prolonged or repeated skin contact use suitable protective gloves.

Other

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)). Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Safety shower/eye wash fountain is recommended in the workplace area.

Respiratory protection

A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Keep away from food and drink.

9. Physical and chemical properties

Appearance	Gypsum boards
Physical state	Solid.
Form	Solid
Color	Facing color varies
Odor	Low odor
Odor threshold	Not available.
pH	> 6 - < 8
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	0.2 % @ 22°C
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Other information	
Flash point class	Not flammable
Specific gravity	> 2.2 - < 2.4

10. Stability and reactivity

Reactivity	Contact with strong acids produces carbon dioxide.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Incompatible materials	Strong acids.
Hazardous decomposition products	May include and are not limited to: calcium oxide and sulfur dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of dusts may cause respiratory irritation.
Skin contact	Dust or powder may irritate the skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Dust generated during processing may cause eye irritation.
Ingestion	Not applicable under normal conditions of use. May cause gastrointestinal irritation if ingested.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Glass Mat Faced Gypsum Panels		
Acute		
Oral		
LD50	Rat	1728 mg/kg

Components	Species	Test Results
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)		
Acute		
Oral		
LD50	Rat	> 1581 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation Dust generated during processing may cause eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not likely to cause respiratory sensitization.
Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity Not classified.

Carcinogenicity Not expected to be hazardous by OSHA/WHMIS criteria.

Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not classified.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not classified.

Chronic effects Not hazardous under normal conditions of use.

Further information *Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

12. Ecological information

Ecotoxicity Not considered to be harmful to aquatic life.

Components	Species	Test Results
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours > 1970 mg/l, 96 hours
CONTINUOUS FILAMENT GLASS FIBER (CAS 65997-17-3)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fish > 1000 mg/l, 96 hours

Components	Species	Test Results
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Zebra danio (Danio rerio)	> 10000 mg/l, 96 Hours OECD SIDS
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Not available.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
Toxic Substances Control Act (TSCA)	All components of the mixture are designated as "active" on or exempt from the TSCA 8(b) inventory.	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.	
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.	
SARA 304 Emergency release notification	Not regulated.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) Cancer lung effects immune system effects kidney effects	
Superfund Amendments and Reauthorization Act of 1986 (SARA)		
SARA 302 Extremely hazardous substance	Not listed.	
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting)	Not regulated.	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	March-13-2015
Revision date	December-15-2022
Version #	08
HMIS® ratings	Health: 0 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 0 Flammability: 0 Instability: 0

Disclaimer

This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.