


Upholstery, Plastic, Molding, and Wood-to-Wood






















Description

Construction staples for quick fastening of construction materials.

Specifications

Size | Gauge: 23 to 18 Length: 1/2 in. to 2 1/2 in. Crown Size: 3/16 in. to 1 in. Point Type: Chiseled Finish: Electrogalvanized, Mechanically Galvanized

Quality Assurance: Grabber® fasteners are manufactured in ISO 9001 and ISO 14001 certified and approved factories.

LEED Reporting: The post-consumer recycled steel content is 25%.

Compliance: The fasteners comply with ASTM F1667 performance requirements.

Applications

Narrow Crown

- Molding
- Cabinets
- Trim
- Paneling
- **Drawer Construction**
- Upholstery
- Gift Boxes

Medium Crown

- Furniture
- Pallet/Crate Construction
- Sheathing
- Subflooring
- Roof Material

Wide Crown

- Roof Material
- Packaging

Upholstery, Plastic, Molding, and Wood-to-Wood



Installation

- Ensure that the crown size and the gauge match the specifications for the stapler being used.
- Always load the stapler with the chiseled point facing away from the handle of the stapler.
- It is best to drive the staple at a 90° angle to the work surface.
- When choosing the staple length, multiply the length of the material being fastened by three, or the closest shorter leg length.
- For thin material such as fabric or cloth, add 3/16 in. for the staple length, or the closest shorter leg length.
- For hard materials, it is recommended to double the thickness of the material, or the closest shorter leg length.

Features

- Narrow crown staples for low visibility finishing on cabinetry and furniture building.
- Medium crown staples for a larger area, often used in home construction.
- Wide crown staples are used when visibility is not an issue, and they are mainly used in construction and packaging.
- Electrogalvanized staples have a thin layer of zinc for added protection against corrosion.
- The chiseled point penetrates the wood quickly.



Product Dimensions

Gauge	Wire Diameter
23	0.031 in.
22	0.022 in.
20	0.019 in.
18	0.044 in.
16	0.055 in.

Ordering Information and Product Options

Item No.	Leg	Coating	Amount	Weight	Special Features
23 Gauge					
3/8 in. Crown					
A1914	1/4 in.	Electrogalvanized	5,000	1 lb.	
22 Gauge					
3/8 in. Crown					
716	1/4 in.	Electrogalvanized	10,000	1 lb.	
718	5/16 in.	Electrogalvanized	10,000	1.5 lb.	
710	3/8 in.	Electrogalvanized	10,000	2 lb.	
7112	1/2 in.	Electrogalvanized	10,000	2 lb.	
7114	9/16 in.	Electrogalvanized	10,000	2 lb.	

Upholstery, Plastic, Molding, and Wood-to-Wood



Ordering Information and Product Options (continued)

Item No.	Leg	Coating	Amount	Weight	Special Features
20 Gauge					
3/8 in. Crown					
A1138	3/8 in.	Electrogalvanized	5,000	1.5 lb.	
A1112	1/2 in.	Electrogalvanized	5,000	2 lb.	
18 Gauge					
3/16 in. Crown					
GSN1812	1/2 in	Electrogalvanized	5,000	3 lb.	
GSN1858	5/8 in.	Electrogalvanized	5,000	3.5 lb.	
GSN1834	3/4 in.	Electrogalvanized	5,000	4 lb.	
GSN1878	7/8 in.	Electrogalvanized	5,000	4.5 lb.	
GSN181	1 in.	Electrogalvanized	5,000	5 lb.	
GSN18118	1 1/8 in.	Electrogalvanized	5,000	6 lb.	
GSN18114	1 1/4 in.	Electrogalvanized	5,000	6.5 lb.	
GSN18112	1 1/2 in.	Electrogalvanized	5,000	7.5 lb.	
7/32 in. Crown		•	·		
SX503512	1/2 in	Electrogalvanized	5,000	3 lb.	
SX503558	5/8 in.	Electrogalvanized	5,000	3 lb.	
SX503534	3/4 in.	Electrogalvanized	5,000	4 lb.	
SX503578	7/8 in.	Electrogalvanized	5,000	4 lb.	
SX50351	1 in.	Electrogalvanized	5,000	5 lb.	
SX5035118	1 1/8 in.	Electrogalvanized	5,000	5 lb.	
SX5035114	1 1/4 in.	Electrogalvanized	5,000	6 lb.	
SX5035112	1 1/2 in.	Electrogalvanized	5,000	7 lb.	
1/4 in. Crown					
L08	1/2 in	Electrogalvanized	5,000	3 lb.	
L10	5/8 in.	Electrogalvanized	5,000	3 lb.	
L11	3/4 in.	Electrogalvanized	5,000	4 lb.	
L12	7/8 in.	Electrogalvanized	5,000	4.5 lb.	
L13	1 in.	Electrogalvanized	5,000	5 lb.	
L14	1 1/8 in.	Electrogalvanized	5,000	6 lb.	
L15	1 1/4 in.	Electrogalvanized	5,000	6 lb.	
L17	1 1/2 in.	Electrogalvanized	5,000	7 lb.	
16 Gauge					
7/16 in. Crown					
N11	3/4 in.	Electrogalvanized	10,000	15 lb.	
N13	1 in.	Electrogalvanized	10,000	18 lb.	
N14	1 1/8 in.	Electrogalvanized	10,000	20 lb.	
N15	1 1/4 in.	Electrogalvanized	10,000	21 lb.	
N17	1 1/2 in.	Electrogalvanized	10,000	26 lb.	
N19	1 3/4 in.	Electrogalvanized	10,000	30 lb.	
N21	2 in.	Electrogalvanized	10,000	33 lb.	

Upholstery, Plastic, Molding, and Wood-to-Wood



Ordering Information and Product Options (continued)

Item No.	Leg	Coating	Amount	Weight	Special Features
16 Gauge (cont	inued)				
1/2 in. Crown					
16S420G	3/4 in.	Mechanically Galvanized	10,000	16 lb.	
16S422G	7/8 in.	Mechanically Galvanized	10,000	17 lb.	
16S425G	1 in.	Mechanically Galvanized	10,000	19 lb.	
16S428G	1 1/8 in.	Mechanically Galvanized	10,000	20 lb.	
16S432G	1 1/4 in.	Mechanically Galvanized	10,000	23 lb.	
16S434G	1 3/8 in.	Mechanically Galvanized	10,000	24 lb.	
16S438G	1 1/2 in.	Mechanically Galvanized	10,000	26 lb.	
16S444G	1 3/4 in.	Mechanically Galvanized	10,000	30 lb.	
16S450G	2 in.	Mechanically Galvanized	10,000	33 lb.	
15/16 in. Crov	wn				
GSW1634	3/4 in.	Electrogalvanized	10,000	18 lb.	
GSW1678	7/8 in.	Electrogalvanized	10,000	20 lb.	
GSW161	1 in.	Electrogalvanized	10,000	21 lb.	
GSW16114	1 1/4 in.	Electrogalvanized	10,000	25 lb.	
GSW16112	1 1/2 in.	Electrogalvanized	10,000	30 lb.	
GSW16134	1 3/4 in.	Electrogalvanized	10,000	33 lb.	
GSW162	2 in.	Electrogalvanized	10,000	36 lb.	
1 in. Crown					
BCS1096	5/8 in.	Electrogalvanized	10,000	17 lb.	
P10	5/8 in.	Electrogalvanized	10,000	18 lb.	
BCS1097	3/4 in.	Electrogalvanized	10,000	19 lb.	
P11	3/4 in.	Electrogalvanized	10,000	19 lb.	
BCS1098	7/8 in.	Electrogalvanized	10,000	21 lb.	
P12	7/8 in.	Electrogalvanized	10,000	21 lb.	
BCS1099	1 in.	Electrogalvanized	10,000	22 lb.	
P13	1 in.	Electrogalvanized	10,000	23 lb.	
BCS1101	1 1/4 in.	Electrogalvanized	10,000	26 lb.	
P15	1 1/4 in.	Electrogalvanized	10,000	27 lb.	
BCS1102	1 1/2 in.	Electrogalvanized	10,000	30 lb.	
P17	1 1/2 in.	Electrogalvanized	5,000	15 lb.	
BCS1116	1 3/4 in.	Electrogalvanized	5,000	17 lb.	
BCS1117	2 in.	Electrogalvanized	5,000	19 lb.	
P21	2 in.	Electrogalvanized	5,000	18 lb.	

Note: Product availability is subject to change without prior notice, and the availability of products may differ from what is printed in literature and displayed on our website.

Staples PS1072 USA-ENG/Rev. 02-25

GRABBER CONSTRUCTION PRODUCTS, INC. 5255 W 11000 N., STE 100 HIGHLAND, UT 84003

(800) 477-8876 | GrabberPro.com

SAFETY FIRST: Wear appropriate personal protective equipment. Read applicable SDS and literature before

TECHNICAL INFORMATION: Technical information contained herein is furnished without charge or obligation and is given and accepted at the recipient's sole risk. Because conditions of use may vary and are beyond our control, Grabber Construction Products makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with uses of any product described herein. Grabber $Construction \, Products \, reserves \, the \, right \, to \, modify \, this \, document \, without \, prior \, notice.$







