

## #352 Rubber Expansion Joint

### SECTION 04 00 00 MASONRY Section 04 05 23 Masonry Accessories Section 04 05 23.13 Masonry Control and Expansion Joints Section 04 21 13.13 Brick Veneer Masonry

#### **PART 1: GENERAL**

##### 1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

##### 1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

#### **PART 2: MANUFACTURER**

##### 2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

##### 2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

B. ASTM D2000–18 Standard Classification System for Rubber Products in Automotive Applications

C. ASTM D2240-15e1 Standard Test Method for Rubber Property Durometer Hardness

##### 2.3 MATERIALS

**No. 352 RUBBER CONTROL JOINT**

Standard: Thickness: 1/4" Depth: 02-5/8" [6-7/8'] [11-1/8"]

Tee: Thickness: 1/4" Depth 2-5/8"

Materials: Extruded Rubber

**PART 3: EXECUTION**

- A. Install as specified in applicable masonry section(s).
- B. Install vertically at expansion joints and seal interior and exterior joint with backer rod and sealant.