



# Henry® Pro-Grade® Product Catalog

Made especially for the contractor



Roof Coatings | Sealants | Primers | Mastics & Roof Cements | Repair & Reinforcement Fabrics

## Silicone Roof Coatings

### Pro-Grade® 988 Silicone White Roof Coating

- Mold and mildew resistant
- Rain safe in 15 minutes
- Permanent ponding water resistance
- High solids content, one coat application
- NSF P151 approved for rainwater catchment
- Superior UV resistance and reflectivity, helps lower roof and interior temperatures providing energy savings
- Low odor and VOC compliant in all jurisdictions
- Proven waterproofing performance per ASTM D7281
- Helps extend the existing roof membrane life cycle
- Restoration System installation qualifies for up to 20-year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 1.5 gallons/square

**Sizes available:** 5 gallon pail and 55 gallon drum

**Colors:** White, gray and tan



### Pro-Grade® 988 Premium & Custom Color Silicone Roof Coating

- Permanent ponding water resistance
- Low odor and VOC compliant in all jurisdictions
- High solids content, one coat application
- Excellent adhesion to many substrates
- Restoration System installation qualifies for up to 20-year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 1.5 gallons/square

**Sizes available:** 5 gallon pail and 55 gallon drum

**Colors:** Almond, brick red, brown, charcoal, light gray, terra cotta, safety yellow and custom



## Acrylic Roof Coatings

### Pro-Grade® 280 Elastomeric White Roof Coating

- Premium water-based 100% acrylic latex coating
- Highly resistant to disbonding, chalking, mildew, fungi, discoloration
- Helps extend the existing roof membrane life cycle
- Meets or exceeds ASTM D6083 - Standard Specification for Liquid Applied Acrylic Coating Used in Roofing
- Restoration System installation qualifies for up to 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 3.0 gallons/square to be applied in two coats at 1.5 gallons/square

**Sizes available:** 5 gallon pail, 55 gallon drum and 275 gallon tote

**Color:** White



### Pro-Grade® 276 Elastomeric White Roof Coating

- Reflects 80% of sun's heat and UV rays after 3 years
- Dirt Pick-Up resistant (DPR) technology maintains a highly reflective white roof surface
- Helps preserve existing roof membrane against elements and extends the roof life cycle
- 100% acrylic polymer technology with excellent hiding ability

**Coverage:** 3.0 gallons/square to be applied in two coats at 1.5 gallons/square

**Sizes available:** 5 gallon pail, 55 gallon drum and 275 gallon tote

**Color:** White



### Pro-Grade® 285 Fast Set Acrylic Elastomeric Coatings

- Helps protect and extend SPF roof performance
- Meets or exceeds ASTM D6083 - Standard Specification for Liquid Applied Acrylic Coating Used in Roofing
- Restoration System installation qualifies for up to 20-Year Material, Labor and Workmanship Henry Gold Seal Warranty

**Coverage:** 3.0 gallons/square to be applied in two coats at 1.5 gallons/square

**Sizes available:** 5 gallon pail, 55 gallon drum and 275 gallon tote

**Colors:** White, light gray, dark gray and tan




## Aluminum Roof Coatings

### Pro-Grade® 599 Rubberized Aluminum Roof Coating

- One-coat application – no primer required
- Excellent flexibility
- Helps extend the existing roof membrane life cycle
- Helps lower interior temperatures as well as energy costs
- Restoration System installation qualifies for up to 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 1.5 - 2.5 gallons/square

**Sizes available:** 5 gallon pail and 50 gallon drum



### Pro-Grade® 586 Fibered Aluminum Roof Coating

- Resists moisture intrusion and levels irregularities in asphaltic roof surfaces
- Helps extend the existing roof membrane life cycle
- Low odor and VOC compliant in all jurisdictions
- Restoration System installation qualifies for up to a 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 1.5 - 2.5 gallons/square

**Sizes available:** 5 gallon pail and 50 gallon drum



### Pro-Grade® 588 Aluminum WB Roof Coating

- Resists moisture intrusion and levels irregularities in asphaltic roof surfaces
- Helps extend the existing roof membrane life cycle
- Low odor and VOC compliant in all jurisdictions
- Restoration System installation qualifies for up to a 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 1.5 gallons/square

**Sizes available:** 5 gallon pail, 50 gallon drum and 250 gallon tote



## Asphalt Roof Coatings

### Pro-Grade® 197 Asphalt Emulsion

- Resists moisture intrusion and levels irregularities in asphaltic roof surfaces
- Helps extend the existing roof membrane life cycle
- Low odor and VOC compliant in all jurisdictions
- Restoration System installation qualifies for up to a 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

**Coverage:** 3.0 gallons/square

**Sizes available:** 5 gallon pail, 55 gallon drum and 275 gallon tote



### Henry® 307 Fibered Asphalt Emulsion

- Polymer fibers allow greater application rate per coat
- ASTM D1227 Type II, Class I, Fed. Spec. SS-R-1781 Type I

**Coverage:** 3.0 - 4.0 gallons/square

**Sizes available:** 5 gallon pail



## Silicone Sealants

### Pro-Grade® 957 Silicone Fibered Roof Sealer

- Reinforced with fibers
- Excellent repair material for many roofing substrates
- Seals flashings, fasteners, seams and drains
- Easily applied by trowel up to 1/2" thick on vertical or horizontal applications

Application Rate	Coverage per Gallon
1/16" thickness	24 sq. ft./gal.
1/8" wide	12 sq. ft./gal.
1/4" wide	6 sq. ft./gal.

**Sizes available:** 2 gallon pail  
**Color:** White



### Pro-Grade® 920 Silicone Roof Sealant

- Seals roof membrane seams, concrete cracks, flashing, drains and damaged areas on most roof substrates
- No hardening, chalking, crazing, cracking or reverting
- Wide temperature performance range: -40 °F to 200 °F
- 100% silicone moisture-cure technology

**Sizes available:** 10.1 oz cartridge  
**Color:** White



### Pro-Grade® 928 Pitch Pocket & Self-Leveling Roof Sealer

- Encapsulates and seals fasteners on metal roofs
- Forms a watertight, non-shrinking seal for penetrations in metal pitch pocket flashings

**Coverage:** 150 - 200 fasteners/cartridge at 1/2" diameter  
**Sizes available:** 10.1 oz cartridge  
**Color:** Black



### Pro-Grade® 923 Butter Grade Silicone Roof Sealer

- Excellent repair material for many roofing substrates
- Seals flashings, fasteners, seams and drains
- Easily applied by brush or trowel up to 1/4" thick on vertical or horizontal applications

Application Rate	Coverage per Gallon
1/16" thickness	24 sq. ft./gal.
1/8" wide	12 sq. ft./gal.
1/4" wide	6 sq. ft./gal.

**Sizes available:** 2 gallon pail  
**Color:** White



## Acrylic Sealants

### Henry® 295 Metal Seam Sealer

- Rubber-based, mastic-grade, elastomeric sealant designed to seal critical fasteners and lap seams on metal roofing
- Can be applied with a bulk cartridge applicator
- May be coated with either an acrylic or solvent-based elastomeric reflective coating, or an asphalt-aluminum reflective coating
- Not for use in VOC regulated areas

Application Rate	Coverage per Gallon
1/2" bead	75 linear ft./gal.
1/4" thickness	4" wide - 20 linear ft./gal.
6" wide	13 linear ft./gal.
12" wide	6.5 linear ft./gal.

**Sizes available:** 5 gallon pail  
**Color:** White



### Henry® 289 White Roof Sealant

- Elastomeric acrylic patching compound
- Applies to dry or damp (not wet) surfaces
- Doesn't "bleed through" reflective coatings
- Skins over quickly – no delays

**Coverage:** 12 1/2 sq. ft. per gallon applied 1/8" thick.  
**Sizes available:** 10.1 oz. cartridge, 1 gallon, 3.5 gallon  
**Color:** White



### Pro-Grade® 294 Base Coat and Sealer

- Stain-blocking sealer for use on asphaltic surfaces prior to silicone roof coating systems
- Gray base coat for use in water-based white roof coating systems
- Highly resistant to disbonding

**Coverage:** 1.5 gallons/square when used as a base coat prior to application of Pro-Grade® 280  
1.0 gallons/square when used as a stain blocker prior to application of Pro-Grade® 988

**Sizes available:** 5 gallon pail, 55 gallon drum and 275 gallon tote  
**Color:** Gray



### Pro-Grade® 941 Adhesion Promoter

- One coat adhesion promoter designed to enhance the bond strength of silicone coatings to roof surfaces
- Quick drying

**Coverage:** 500 sq. ft./gallon  
**Sizes available:** 1 gallon can



## Pro-Grade® 167 Extreme Rubberized Flashing Cement

- Contains UV inhibitors and SEBS rubber for durability
- Suitable for extreme weather conditions
- Superior elasticity and flexibility; ideal for control joints and seams or anywhere else movement is expected
- Installation temperature range (ambient): -20 °F to 140 °F
- 100% underwater adhesion per ASTM D3409
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

**Coverage:** 12 sq. ft. per gallon applied 1/8" thick  
6 sq. ft. per gallon for 3-course application

**Sizes available:** 1 gallon can and 3 gallon pail

**Color:** Black



## Pro-Grade® 155 Flashing Cement

- Contains SBS rubber for flexibility and elasticity
- Will not sag/slip even at high roof temperatures
- Low temperature and summer grades
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

**Coverage:** 12 sq. ft. per gallon applied 1/8" thick  
30 sq. ft. per 5 gallon pail for 3-course application

**Sizes available:** 5 gallon pail

**Color:** Black



## Pro-Grade® 151 Plastic Cement

- Smooth, easy-to-use, trowel application
- Contains 100% recycled fibers for added strength and durability
- Excellent adhesion to many common roof surfaces
- Low temperature and summer grades
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

**Coverage:** 12 sq. ft. per gallon applied 1/8" thick  
30 sq. ft. per 5 gallon pail for 3-course application

**Sizes available:** 5 gallon pail

**Color:** Black



## Pro-Grade® 163 Emergency Leak Repair Sealant

- Modified with SBS rubber for improved flexibility and durability
- Tenacious adhesion even when applied underwater
- Spreads easily, even in cold weather
- Installation temperature range (ambient): 0 °F to 120 °F
- 100% underwater adhesion per ASTM D3409
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

**Coverage:** 12 sq. ft. per gallon applied 1/8" thick  
6 sq. ft. per gallon for 3-course application

**Sizes available:** 10.1 oz cartridge, 1 gallon can and 3 gallon pail

**Color:** Black



## Pro-Grade® 161 All Weather Flashing Cement

- Appropriate for setting and repairing SBS Modified Bitumen flashings
- Modified with SBS rubber for improved flexibility and durability
- Will not curl or chase the trowel when applied underwater
- Low-temperature and summer-grade formulations allow for an installation temperature range (ambient) of 20 °F to 120 °F
- 100% underwater adhesion per ASTM D3409
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

**Coverage:** 12 sq. ft. per gallon applied 1/8" thick  
30 sq. ft. per 5 gallon pail for 3-course application

**Sizes available:** 5 gallon pail

**Color:** Black



## Henry® 181 Black Asphalt Saturated Glass Fabric

- Woven, open-mesh fiberglass
- 20 x 10 thread count
- ASTM D1668

**Sizes available:** 4 in. x 150 ft., 6 in. x 150 ft., 36 in. x 150 ft.



## Henry® 183 Yellow Resin Coated Glass Fabric

- Yellow resin coating minimizes distortion and aids in quality workmanship
- Compatible with asphalt cements and coatings, emulsions, solvent-based and hot-melt products
- Woven, open-mesh fiberglass
- 20 x 10 thread count
- ASTM D1668

**Sizes available:** 4 in. x 150 ft., 6 in. x 150 ft., 36 in. x 150 ft.



## Henry® 296 ElastoTape™ Repair Fabric

- 100% spunbonded, non-woven polyester mat
- High tensile strength
- Puncture resistant
- Excellent reinforcement fabric for roofing and waterproofing applications

**Sizes available:** 4 in. x 150 ft.



## Henry® 195 Polyester Fabric

- Contains soft-finish polyester
- Provides an ideal reinforcing component in cold process roofing and repair
- Conforms readily to irregular surfaces

**Sizes available:** 6 in. x 300 ft., 12 in. x 300 ft., 40 in. x 324 ft., 6 ft. x 324 ft.



**Henry**<sup>®</sup>

**Building Envelope Systems**<sup>®</sup>  
Roofing | Air Barrier | Waterproofing

Ask us today about other Henry<sup>®</sup> solutions that help manage the flow of water, air, vapor and energy.

Henry and ProGrade are registered trademarks of the Henry Company

1-800-486-1278  
[www.henry.com](http://www.henry.com)

© 2020 Henry Company. All rights reserved.  
Printed in U.S.A. 142.3US.E005 (01/20)