


Aluminum Brick Vents Cast Aluminum Brick Vent - Style "CA"





Model Number

CA 168

DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Style "CA" Brick Vent Description:

- One piece molded cast aluminum
- Minimum .125" thick, 4" deep
- Rear water stop
- Load bearing
- Overlapping blades
- Continuous bottom weepage

Note: Can be equipped with operable damper and ducts

Free Area Chart

Vent Size	Free Area
16 ½" W x 2 ¾" H	26%
16 ½" W x 3 ¾" H	34.5%
16 ½" W x 4 ¾" H	38%
16 ½" W x 5 ¾" H	30%
16 ½" W x 7 ¾" H	38%
16 ½" W x 9 ¾" H	38%
16 ½" W x 11 ¾" H	38%
16 ½" W x 15 ¾" H	38%

NOTE:

- Less than 16" wide reduces free area by 1%
- Greater than 16" wide increases free area by 1%.

H&B manufactures aluminum brick vents from a minimum of 41% pre-consumer and 23% post-consumer recycled material.

CA 825 8 1/8" x 2 1/4" CA 847 8 1/4" x 4 15/16" CA 808 8" x 7 1/8" CA 123 12" x 2 3/4" CA 124 12" x 3 1/2" CA 125 12" x 5"

W x H (Nominal)

CA 128 12" x 7 ¾"

CA 162 16 ½" x 2 ¾"

CA 1604 16" x 4"

CA 164 16" x 4 15/16"

CA 166 16" x 6"

NOTE: Cast aluminum vents are standard in mill finish and do not include mortar ribs (also available in baked enamel at an extra charge)

16" x 7 3/4"

HOHMANN & BARNARD, Inc.

30 Rasons Court | Hauppauge, NY 11788 CORPORATE HEADQUARTERS T: 800.645.0616 F: 631.234.0683

www.h-b.com

Branch/Subsidiary Locations: ALABAMA - ILLINOIS - MARYLAND NEW YORK - PENNSYLVANIA - TEXAS CANADA © HOHMANN & BARNARD, INC. - 2012