





**ENTRANCE MAT - Activ-Mat™ EM800 Series with EFRA8 Frame** - Aluminum Mat with Recessed Aluminum Angle Frame




**SPECIFICATIONS:**

**Aluminium Roll-Up Entrance Mat with Aluminum Hinges**  
 Material: 6063-T6 extruded aluminum alloy tread rails and frames.  
 Depth: 3/8" (9.5 mm).  
 Standard Finish: Mill.  
 Tread Spacing: 2" (50.8 mm) on center with 6 treads per foot in the direction of travel.  
 Spacing Between Rails: Heelproof spacing of 3/16"  
 Rolling Wheel Load Rating: 350 lbs

**NOTE:**

Verify traffic direction - traffic to run perpendicular to rails.  
 Maximum single section size not to exceed 12'-0" (3.66m) in width (dim "x") or 100 sq. ft.  
 If multiple sections, verify sectioning does not occur in traffic path.  
 Vinyl filler to be trimmed in field for tight fit.  
 Mat dimensions allow for clearance between mat section(s) and frame(s) in width (dim "x").  
 Additional product information including installation instructions may be found on our website.

QTY	LOCATION	DIMENSION "X" <small>Width</small>	DIMENSION "Y" <small>Length</small>	FINISH	TREAD OPTIONS	TREAD COLOR	NOTES

 <p><b>JL INDUSTRIES</b>                  9702 Newton Ave S. Bloomington, MN 55431   Many Locations Nationwide</p>	800-554-6077 sales@activarcpg.com www.activarcpg.com	Distributor: Contractor: Date: Scale: N/A	Project: Approved By: Architect: Item #:
	Pages: 1 of 1	Item #:	