SUBMITTAL: EXTERIOR ACCESS PANEL XTA™ and XTS™

Select this exterior access panel design with energy efficiency in mind. 2 inches of polyisocyanurate provides an R-value of 13, and dual layered gasketing provides the weather-resistance you need. Door opens to 170°.

STEP 1: SELECT MODEL

Model XTA (Galvanneal and Aluminum)

Frame: 16 ga. Galvanneal steel frame with 1" exposed flange

Door: 2" Thick Polyisocyanurate Insulation, .040 Aluminum door panel with continuous stainless

steel. Hinge and R-value 13.0

Gaskets: Adhesive backed EPDM foamed silicone rubber seal on frame and door.

Finish: White powder coat paint.

Handle: (F4) Lockable Compression Paddle Latch, Black

Model XTS (Stainless Steel)

Frame: 16 ga. 304 Stainless Steel Frame with #4 finish

Door: 2" Thick Polyisocyanurate insulation, 20 ga. Stainless steel door with continuous hinge and R-

RK (Black)

value of 13.0

Gaskets: Adhesive backed EPDM foamed silicone rubber seal on frame and door.

Finish: 304 Stainless - No. 4 Finish

Handle: (F4) Lockable Compression Paddle Latch, Black

STEP 2: SELECT SIZE FROM TABLE BELOW OR ENTER OTHER SIZE


Sizes: ORDER SIZE IS DOOR SIZE. Minimum 8" x 8". Maximum 48" x 48".

STEP 3: SELECT OPTIONAL FEATURES AT ADDITIONAL COST

____ (F6) Chrome lockable compression paddle Latch

____ Optional color code - See colors below





VV (VVIIILE)	D (Broffize)	It (keu)	J (Sariu)	AD (Alvis Beige)	3D (3C Beige)	G (Gray)	31 (Sliver)		2
QTY	Size (A)	Wall Opening (C)	Handles	Approx Ship Weight in lbs.	QTY	Size (A)	Wall Opening (C)	Handles	Approx Ship Weight in lbs.
	12" x 12"	12-3/8" x 12-3/8"	1	11		24" x 30"	24-3/8" x 30-3/8"	2	40
	14" x 14"	14-3/8" x 14-3/8"	1	15		24" x 36"	24-3/8" x 36-3/8"	2	42
	18" x 18"	18-3/8" x 18-3/8"	1	19		24" x 48"	24-3/8" x 48-3/8"	2	57
	20" x 24"	20-3/8" x 24-3/8"	2	30		30" x 30"	30-3/8" x 30-3/8"	2	44
	20" x 30"	20-3/8" x 30-3/8"	2	32		30" x 36"	30-3/8" x 36-3/8"	2	56
	22" x 30"	22-3/8" x 30-3/8"	2	34		36" x 36"	36-3/8" x 36-3/8"	2	61
	22" x 36"	22-3/8" x 36-3/8"	2	40		36" x 48"	36-3/8" x 48-3/8"	2	75
	24" x 24"	24-3/8" x 24-3/8"	2	27		48" x 48"	48-3/8" x 48-3/8"	2	108
		Custom Size							

AR (AMS Raiga)

	800-554-6077	Distributor:		Project:				
JL INDUSTRIES	sales@activarcpg.com	Contractor:		Approved By:				
	www.activarcpg.com	Date:		Architect:				
9702 Newton Ave S. Bloomington, MN 55431	on Ave S. Bloomington, MN 55431 Many Locations Nationwide		Pages: 1 of 1	Item #:				
© 2024 Activar Construction Products Group, Inc. THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC.								