



# GoBoard® Wedge



*Compatible with all GoBoard products*

GoBoard Wedge is a tile backer board that allows for custom-sized shower pan installation, accommodating all types of shower areas and offset drain locations. The pre-sloped panels can be quickly cut right where it's installed. And best of all, waterproofing is built-in.

## High Density Closed Cell Polyiso

### GoBoard® Wedge

48-in x 48-in panel, 1/4-in per ft slope  
Tapers from 1 1/8-in down to 1/8-in



## USES

For use in shower pan areas as a component of the GoBoard Shower Pan system.

## APPROVED MATERIALS

**Substrate** - Level wood subfloor, or level concrete slab

**Bonding** - Polymer modified thin-set mortar compliant with ANSI A118.4 and dry-set mortar compliant with ANSI A118.1.

**Joint Sealing** - GoBoard® Pro Sealant, GoBoard® Sealant, or approved alternative. Overlap GoBoard Membrane a minimum of 2 inches or butt membrane joints and cover with GoBoard Banding. Use GoBoard Corner for both inside and outside corners and GoBoard Curb Cover for GoBoard Curb.

**Tools Needed** - Utility knife, pencil or pen, straight edge, speed square, level, measuring tape, 90° putty knife, 1/4-in x 1/4-in square-notch, 3/16-in x 5/32-in v-notch trowel, margin trowel, caulk gun, corded or cordless drill, thin-set mixing paddle and bucket.

## SAFETY

Please wear gloves, safety glasses, long sleeve shirts, and long pants when installing GoBoard products. Temporary mechanical abrasion (itching) of skin, eyes and respiratory track may occur upon exposures to fibers or dust during handling of GoBoard.

## FEATURES

- Developed to offer easy on-site customization of the shower pan, so there's no need to move the plumbing.
- Accommodates most shower pan areas using only four wedges.
- GoBoard composite backer boards provide equivalent performance to ANSI A118.9, and as a waterproof membrane in wet areas, provides equivalent performance to ANSI A118.10 when installed in accordance with Section 4.2.4 of the ICC-ES evaluation report.
- Same level of performance as GoBoard Tile Backer.

## TECHNICAL DATA

Property	Method	GoBoard® Wedge (1/8" - 1 1/8")
Dimensions (feet)	ASTM C473	4'x4'
Thickness (inches)	ASTM C473	0.58
Board Weight (lbs/ft²)		
R-Value (°F · ft² · h/BTU)	ASTM C518	2.9
Compressive Strength (avg. psi)	ASTM D2394	200
Moisture Movement (%)	ASTM D1037	<0.07
Surface Burning Characteristics <sup>1</sup>	ASTM E84	Pass
Waterproof	ASTM D4068	Pass <sup>2</sup>
WVT Permeance (perms)	ASTM E96	<1
Resistance to Fungi / Bacteria	ASTM G21/G22	No Growth
Freeze Thaw	ASTM C666	>25
Robinson Floor Test	ASTM C627	Residential

<sup>1</sup> Per International Building Code Requirements  
<sup>2</sup> ANSI 118.10 certified, <sup>3</sup> pending



FOLLOW US!



Download the complete installation instructions:  
[www.JM.com/GoBoard](http://www.JM.com/GoBoard)