



# LP LEGACY® PREMIUM SUB-FLOORING

## For The Toughest Sub-Floor Jobs On The Planet

LP Legacy® Premium Sub-Flooring is a super durable, premium, strand-based composite wood panel designed for demanding sub-floor applications. It's not only proven tough but is also APA-verified to have exceptional stiffness and strength. LP Legacy sub-flooring represents more than 40 years of innovation from Louisiana-Pacific, a company known and trusted for manufacturing excellence.

## What Makes LP Legacy Premium Sub-Flooring The Toughest Out There?

### GORILLA TOUGH®

LP Legacy Premium Sub-Flooring has an exclusive relationship with Gorilla Glue, a name your customers know and trust for superior strength and sticking properties. Each wood strand is coated with a water-resistant adhesive that uses Gorilla Glue Technology® for exceptional stiffness and moisture resistance. Plus, the edges on each board have a clear high-performance edge seal for further protection.

### INDUSTRY-LEADING WARRANTY

Only LP Legacy Premium Sub-Flooring offers our Covered Until It's Covered® no-sand warranty—plus a Lifetime Limited Warranty that lasts as long as the home.

### EXCEPTIONAL FASTENER HOLDING

High panel density and superior stiffness provide optimum fastener holding strength for a quieter sub-floor.



MADE WITH  
GORILLA GLUE  
TECHNOLOGY

See complete warranty details at [LPCorp.com/literature](http://LPCorp.com/literature) or call 888.820.0325

## ONE OF THE STIFFEST IN CLASS

LP Legacy® Premium Sub-Flooring is APA-verified with the industry-leading bending stiffness and as one of the strongest sub-floor panels on the market. What's more, it was tested to significantly higher design values than required by industry standards.

## BEYOND STANDARD COMPLIANCE

- LP Legacy panels are trademarked by the APA and manufactured in conformance with U.S. Voluntary Product Standard PS2
- LP Legacy panel bending capacities exceed PS2 standards; for proprietary design capacities refer to APA Product Report® PR-N127
- Structural I panel grade, meaning enhanced cross-panel bending properties

## HANDLING/STORAGE INFORMATION

- Store panels in clean, dry areas; if possible, store indoors
- If stored outside, cover panels with plastic sheets or tarps; keep cover open and away from the sides and bottom of the panels to allow for air circulation
- Protect edges to avoid damage to the tongue-and-groove profile
- Space units at least 4" on all four sides

## BENDING STIFFNESS, EI (LBF-IN.<sup>2</sup>/FT)\*

AXIS	LP LEGACY RATED 24 OC	5-PLY PLYWOOD RATED 24 OC	OSB RATED 24 OC
Primary Strength Axis	395,120	330,000	300,000
Secondary Strength Axis	160,980	80,500	80,500

\*Bending stiffness is Apparent EI. Reference APA Product Report PR-N127.

## BENDING STRENGTH, F<sub>s</sub> (LBF-IN./FT)

AXIS	LP LEGACY RATED 24 OC	5-PLY PLYWOOD RATED 24 OC	OSB RATED 24 OC
Primary Strength Axis	1,300	770	770
Secondary Strength Axis	750	385	385

## NUTS & BOLTS

- Clear high-performance edge seal keeps panels moisture resistant (and let you see how much wood is packed into each panel)
- RainChannel® notches on one 4-foot end of the panel help ensure better drainage
- Unique tongue-and-groove profile along panel length makes installation easier

## WORK MORE EFFICIENTLY

- LP Legacy panels are fastened with conventional nailing and gluing techniques; code-approved screws may also be used
- Higher density may require additional air pressure on pneumatic tools to fully drive fasteners
- See LP Legacy installation instructions for complete details

## PRODUCT SPECS

- Exceptional strength and proven stiffness across panel length and width
- Fully sanded face for a uniform thickness
- Clear edge sealant on all panel edges
- Fastener marks for common joist spacings

## ENVIRONMENTAL IMPACT

- Made of engineered wood substrate, a renewable resource with a reduced environmental impact
- LP uses SFI® certified forest management and procurement systems, which help ensure wood comes from well-managed forests
- Raw material procurement targets small, fast-growing trees
- In LP's manufacturing process, no part of the log goes to waste
- Only low-emitting, safe adhesives are used as a binder



See complete warranty details at [LPCorp.com](http://LPCorp.com) or call 888.820.0325