




WSC SLIDE CLIPS




WSC1200
(10 slots)




WSC1000
(8 slots)



WSC800
(6 slots)



WSC600
(4 slots)



WSC362
(2 slots)

Allowable Anchorage Load Table			WSC362	WSC600, 800, 1000 & 1200
Anchor Type	Stud Thickness	# of Anchors to Structure	Allowable Load (lbs)	Allowable Load (lbs)
0.157" dia Hilti X-U P.A.F. to 3/16" steel	33 mil (33 ksi)	2	376	535
		3	376	564
		4	376	564
	43 mil (33 ksi)	2	535	535
		3	560	802
		4	560	840
	54 mil (50 ksi)	2	535	535
		3	652	802
		4	652	978
	68 mil (50 ksi)	2	535	535
		3	652	802
		4	652	978
97 mil (50 ksi)	2	535	535	
	3	652	802	
	4	652	978	
#12 Hilti Kwik-Flex screws to 3/16" steel	33 mil (33 ksi)	2	376	564
		3	376	564
		4	376	564
	43 mil (33 ksi)	2	560	665
		3	560	840
		4	560	840
	54 mil (50 ksi)	2	652	665
		3	652	978
		4	652	978
	68 mil (50 ksi)	2	652	665
		3	652	978
		4	652	978
97 mil (50 ksi)	2	652	665	
	3	652	978	
	4	652	978	

Notes:

1. All anchors must be attached in a straight line down the center of the clip
2. All anchor data is from Hilti-Volume 1 - Direct Fastening Technical Guide - Edition 18
3. All anchors must be attached to the structure per manufacturer's instructions.
4. Anchor edge distance to the edge of the clip to be 1/2" min.
5. Values for WSC362 require 2 #14 shouldered screws, WSC600-1200 require minimum 3 #14 shouldered screws
6. Values are based on concentric loading (screws in the middle of the slots)

For more information, please contact MarinoWARE® Technical Services at 866.545.1545
This technical information reflects the most current information available and supersedes any and all previous publications effective May 22, 2023 | MW_ClipSourceCatalog | © WARE Industries, Inc. 2023