

Marino\WARE® Product Submittal Data


PRODUCT NAME: Paper Faced Metal Bead

DELUXE SUPER WIDE OUTSIDE CORNER - TAPE ON




USE: Provides the same extra coverage as P1 Super Wide outside corners and is manufactured with ease and speed of installation in mind.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500




EXTRA WIDE OUTSIDE CORNER - TAPE ON




USE: Designed for open angle wall intersections on inside open angle corners.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500



L 1/2" PAPER TRIM



USE: L-shaped 1/2" and 5/8" trim is designed for a clean, professional finish. Best for areas where 1/2" and 5/8" drywall runs adjacent to masonry walls, cinder blocks, drop ceilings, beams, unfinished doorways, or door jams.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500



L 5/8" PAPER TRIM



USE: L-shaped 1/2" and 5/8" trim is designed for a clean, professional finish. Best for areas where 1/2" and 5/8" drywall runs adjacent to masonry walls, cinder blocks, drop ceilings, beams, unfinished doorways, or door jams.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500



Marino\WARE® Product Submittal Data


PRODUCT NAME: Paper Faced Metal Bead

SLOK EXTRA WIDE BULLNOSE - NAIL ON:




USE: This bullnose has a wider 7/8" flange which allows for easier installation and added corner coverage when nails, screws, or staples are being used.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500




OPEN ANGLE / SPLAY OUTSIDE CORNER OS SPLAY - TAPE ON:




USE: Designed for wider offset outside corners providing easier installation and more consistent mudding.

Length	Pcs/Ctn	Ft/Ctn
8'	50	400
9'	50	450
10'	50	500



SLOK BULLNOSE SLOK - TAPE ON:




USE: This bullnose outside corner provides an elegant, smooth finish.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500



SLOK OPEN ANGLE / SPLAY BULLNOSE SLOK NOS - NAIL ON:




USE: Provides a clean and smooth bullnose finish on offset outside corners where nails, screws, or staples are required.

Length	Pcs/Ctn	Ft/Ctn
8'	50	400
9'	50	450
10'	50	500



SOUTHWESTERN STANDARD BULLNOSE SLOK - TAPE ON:



USE: A less expensive substitute for the 3/4" bullnose outside corner and offers the same smooth rounded finish.

Length	Pcs/Ctn	Ft/Ctn
7'	50	350
8'	50	400
9'	50	450
10'	50	500

