



The QuickFrame® Rough Opening System streamlines installation by reducing the number of components required to frame windows and doors.

The QuickFrame system comes in extra wide flanges and extra-long returns and can be used for exterior or interior framing around any non-load bearing opening.

Simply attach the header and jamb with our easy-to-use QuickFrame Clip for quick installation.

A single QuickFrame member can replace built-up headers and jambs, reducing jobsite labor assembly time by up to 50%.

BENEFITS + FEATURES

NOMENCLATURE + GAUGE CARD

- Increased performance
- Less material weight and pieces
- Pre-cut lengths
- Eliminates built-up jambs and headers
- Simple 1-piece clip with pre-drilled holes
- Up to 50% reduction in assembly time

Marino\WARE DesignGroup

866.545.1545 | technicalservices@marinoware.com

**600** **S** **162** - **54**

MEMBER DEPTH	TYPE	FLANGE WIDTH	MILS TO GAUGE
162 = 1-5/8"	S = Stud	125 = 1-1/4"	15 = Viper25 ga. EQ
250 = 2-1/2"	T = Track	137 = 1-3/8"	18 = Viper20 ga. EQ
362 = 3-5/8"	VS = ViperStud	162 = 1-5/8"	30 = 20 ga. (DW)
400 = 4"	VT = ViperTrack	200 = 2"	33 = 20 ga. (STR)
600 = 6"	QFH = QuickFrame Header	250 = 2-1/2"	43 = 18 ga.
800 = 8"	QFJ = QuickFrame Jamb	300 = 3"	54 = 16 ga.
1000 = 10"	SR = StudRite	350 = 3-1/2"	68 = 14 ga.
1200 = 12"	JR = JoistRite		97 = 12 ga.
1600 = 16"	SLT = Slotted Track		118 = 10 ga.
	SG = SoundGuard		

**MARINO WARE**

**STEEL THICKNESS TABLE**

MILS	DESIGN (IN.)	MINIMUM (IN.)	GAUGE	COLOR CODE
15	0.0155	0.0147	VIPER 25 EQ	NONE
18	0.0190	0.0181	VIPER 20 EQ	BROWN
27	0.0283	0.0269	22	BLACK
30	0.0312	0.0296	20DW	PINK
33	0.0346	0.0329	20STR	WHITE
43	0.0451	0.0428	18	YELLOW
54	0.0566	0.0538	16	GREEN
68	0.0713	0.0677	14	ORANGE
97	0.1017	0.0966	12	RED
118	0.1242	0.1180	10	BLUE

**MARINO WARE**

Technical Services | technicalservices@marinoware.com