
SLOK EXTRA WIDE BULLNOSE - NAIL ON:



USE: This bullnose has a wider 7/8" flange which allows for easier installation and added corner coverage when nails, screws, or staples are being used.

Length	Pcs/Ctn	Ft/Ct
7'	50	350
8′	50	400
9′	50	450
10'	50	500



OPEN ANGLE / SPLAY OUTSIDE CORNER OS SPLAY -TAPE ON:



USE: Designed for wider offset outside corners providing easier installation and more consistent mudding.

Length	Pcs/Ctn	Ft/Ctn
8′	50	400
9'	50	450
10'	50	500



SLOK BULLNOSE SLOK - TAPE ON:



USE: This bullnose outside corner provides an elegant, smooth finish.

n

SLOK OPEN ANGLE / SPLAY BULLNOSE SLOK NOS - NAIL ON:



USE: Provides a clean and smooth bullnose finish on offset outside corners where nails, screws, or staples are required.

ength	Pcs/Ctn	Ft/Ctn
3′ ¯	50	400
9′	50	450
0'	50	500



SOUTHWESTERN STANDARD BULLNOSE SLOK - TAPE ON:



USE: A less expensive substitute for the 3/4" bullnose outside corner and offers the same smooth rounded finish.

Length	Pcs/Ctn	Ft/C	
7'	50	350	
8′	50	400	
9'	50	450	
10'	EU.	FUL	

