## DIAMOND MESH LATH

USE: Manufactured by slitting and stretching galvanized steel to form small openings to allow the keying of plaster so it will bond to the lath. Diamond Mesh Lath can be bent easily to create curved surfaces.

SIZE:
27" x 97" (686 mm x 2440 mm)
MATERIAL:
G-60

Approx. Lath Weight		Finish	Bundle				
			No.	Weight		Area	
lbs/yd²	(kg/m²)	Galv.	Pcs.	lbs.	(kg)	yd²	(m²)
1.75	(0.9)	✓	10	35	(15.9)	20	(16.7)
2.50	(1.4)	✓	10	50	(22.7)	20	(16.7)
3.40	(1.8)	✓	10	68	(30.8)	20	(16.7)

SELF-FURRING DIAMOND MESH LATH

USE: Uses the same mesh configuration as Diamond Mesh Lath but made with 1/4" dimple indentations spaced 1-1/2" o.c. each way. Used as exterior stucco base, column fireproofing and re-plastering over old surfaces. Available in galvanized only.

SIZE:
27" x 97" (686 mm x 2440 mm)
MATERIAL:
G-60

Approx. Lath Weight		Finish	Bundle				
			No.	Weight		Area	
lbs/yd²	(kg/m²)	Galv.	Pcs.	lbs.	(kg)	yd²	(m²)
1.75	(0.9)	✓	10	35	(15.9)	20	(16.7)
2.50	(1.4)	✓	10	50	(22.7)	20	(16.7)
3.40	(1.8)	✓	10	68	(30.8)	20	(16.7)

3/8" HIGH RIB LATH

USE: Superior spanning characteristics over common expanded metal laths, suited for horizontal applications such as ceilings and soffits. Its 3/8" deep ribbed configuration is a self-furring feature. Designed for application on 24" on center.

SIZE:
27" x 97" (686 mm x 2440 mm)
MATERIAL:
G-60

Approx. Lath Weight		Finish	Bundle Quantity				
			No.	Weight		Area	
lbs/yd²	(kg/m²)	Galv.	Pcs.	lbs.	(kg)	yd²	(m²)
3.40	(1.8)	✓	10	68	(30.8)	20	(16.7)

V-GROOVE MESH LATH

USE: For exterior stucco work over sheathing and as a plaster base over masonry walls. Self-furring embossed "V" groove holds the lath away from the surface to aid in the keying of stucco to the lath.

SIZE:
27" x 97" (686 mm x 2440 mm)
MATERIAL:
G-60

Approx. Lath Weight		Finish	Bundle Quantity				
			No.	Weight		Area	
lbs/yd²	(kg/m²)	Galv.	Pcs.	lbs.	(kg)	yd²	(m²)
1.75	(0.9)	✓	10	35	(15.9)	20	(16.7)
2.50	(1.4)	✓	10	50	(22.7)	20	(16.7)
3.40	(1.8)	✓	10	68	(30.8)	20	(16.7)