PRODUCT NAME: 250SLT300-30

PROPERTIES:

A. Web (in)	2-1/2	Yield Strength Fy (KSI)	40
B. Flange (in)	3	Design Thickness (in)	0.0312
Mils	30	Minimum Thickness (in)	0.0296
Available Finish	G40, G60	Gauge	20
Slot (in)	2		

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Cross Sectional Area: A (in ²)	0.2651
Weight of Member: (lb/ft)	0.9022
Section Modulus: Sx (in ³)	0.2718
Moment of Inertia: Ix (in ⁴)	0.3588
Radius of Gyration: Rx (in)	1.1633
Gross Moment of Inertia: Iy (in ⁴)	0.2615
Gross Radius of Gyration: Ry (in)	1.1633

TORSIONAL SECTION PROPERTIES

St. Venant Torsional Constant: Jx1000 (in ⁴)	0.0860
Torsional Warping Constant: Cw (in ⁶)	0.3250
Shear Center to Centroid on Principal X-axis: Xo (in)	-2.351
Shear Center to Mid-Plane of the Web: m (in)	1.302
Radius of Gyration on the Centroid Principal axis: Ro (in)	2.805
Torsional Flexural Constant: β [1-(xo/Ro) ²]	0.297

CODES & STANDARDS

- AISI North American Specification 2007
- Framing meets ASTM A 1003, A 653, & C 645
- Galvanized steel sheet meets ASTM A 924

GREEN INFO LEED® v3

Available LEED® points in the following categories:

- MR Credit 2 Construction Waste Management (1-2 points)
- •MR Credit 4 Recycled Content (1-2 points)
- •MR Credit 5 Regional Materials (1-2 points)
- Total Recycled Content: 34.9%Post Consumer Content: 24.3%
- Pre Consumer (Post Industrial) Content: 9.4%

FIRE RATINGS

•Approved for these UL Head Of Wall Assemblies

```
HW-D-0003, HW-D-0020, HW-D-0021, HW-D-0024, HW-D-0025, HW-D-0029, HW-D-0031, HW-D-0032, HW-D-0034, HW-D-0034, HW-D-0036, HW-D-0042, HW-D-0043, HW-D-0044, HW-D-0045, HW-D-0046, HW-D-0049, HW-D-0058, HW-D-0059, HW-D-0062, HW-D-0063, HW-D-0071, HW-D-0072, HW-D-0073, HW-D-0076, HW-D-0079, HW-D-0079, HW-D-0083, HW-D-0083, HW-D-0083, HW-D-0083, HW-D-0083, HW-D-0089, HW-D-0099, HW-D-0101, HW-D-0102, HW-D-0103, HW-D-0104, HW-D-0105, HW-D-0106, HW-D-0107, HW-D-0111, HW-D-0112, HW-D-0128, HW-D-0129, HW-D-0130, HW-D-0134, HW-D-0134, HW-D-0134, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0173, HW-D-0173, HW-D-0179, HW-D-0180, HW-D-0184, HW-D-0185, HW-D-0191, HW-D-0194, HW-D-0209, HW-D-0209, HW-D-0210, HW-D-0217, HW-D-0211, HW-D-0221, HW-D-0222, HW-D-0227, HW-D-0227, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0241, HW-D-0243, HW-D-0243, HW-D-0244, HW-D-0244, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0310, HW-D-0314, HW-D-0316, HW-D-0316, HW-D-0316, HW-D-0310, HW-D-0314, HW-D-0314, HW-D-0316, HW-D-0316, HW-D-0316, HW-D-0329, HW-D-0324, HW-D-0324, HW-D-0344, HW-D-0365, HW-D-0371, HW-D-0377, HW-D-0380, HW-D-0381, HW-D-0388, HW-D-0388, HW-D-0399, HW-D-0354, HW-D-0354, HW-D-0364, HW-D-0364, HW-D-0364, HW-D-0366, HW-D-0365, HW-D-0371, HW-D-0371, HW-D-0354, HW-D-0542, HW-D-0542, HW-D-0542, HW-D-0542, HW-D-0554, HW-D-05570, HW-D-05572
```

0.22" 0.22" 2-1/2", 3" or 3-1/2"

09.22.16 Non Structural Framing

