


093 CONTROL JOINT



USE: To relieve the stresses from expansion and contraction across the joint in large ceiling and wall areas in drywall and veneer finish systems. It is used from floor to ceiling in long partition runs and from door header to ceiling. It is also recommended for repair of existing plastered masonry. Made of roll-formed zinc to resist corrosion, it has 3/32" grounds. Plastic tape protects 1/4" wide x 7/16" deep opening, and is to be removed after installation.


USE: Relieves the stresses from expansion and contraction across the joint in large ceiling and wall areas

STOCK LENGTHS:
10 Ft.

PACKAGING:
25 pieces per carton, weight is 27.5 lbs per box.

LIMITATION:
Where sound transmission and/or fire ratings are prime considerations, an adequate seal must be provided behind the control joint.

DOUBLE V EXPANSION JOINT



USE: To relieve the stresses of expansion and contraction in plaster or stucco. It is available in zinc or galvanized steel. Zinc should be used for exterior applications.

STOCK LENGTHS:
10 Ft.

PACKAGING:
24 pieces per carton
Galvanized or
Zinc available in:
3/8", 1/2", 5/8", 3/4", 7/8"

Product	Flange Width		Length		Carton Quantity				
					No. Pcs.	Weight		Length	
	in.	(mm)	ft.	(m)		lbs.	(kg)	ft.	(m)
Double V Expansion Joint, Galvanized	3/8	(9.5)	10	(3.05)	24	48	(21.8)	240	(73.2)
	1/2	(12.7)	10	(3.05)	24	66	(30.0)	240	(73.2)
	3/4	(19.1)	10	(3.05)	24	74	(33.6)	240	(73.2)
	7/8	(22.2)	10	(3.05)	24	83	(37.7)	240	(73.2)
Double V Expansion Joint, Zinc	3/8	(9.5)	10	(3.05)	24	44	(20.2)	240	(73.2)
	1/2	(12.7)	10	(3.05)	24	61	(27.9)	240	(73.2)
	3/4	(19.1)	10	(3.05)	24	69	(31.2)	240	(73.2)
	7/8	(22.2)	10	(3.05)	24	77	(35.0)	240	(73.2)

Zinc available in all sizes as galv.

ACCESSORIES

TIE WIRE



USE: Tie wire is used to support suspended cold rolled channel gridwork for stucco, plaster, acoustical or drywall ceilings. Available in several gauges.

