

Marino\WARE® Product Submittal Data

PRODUCT NAME: Viper20 (600VT300-18)

MARINO\WARE PART # 600VT318

PROPERTIES:

A. Web (in)	6	Yield Strength Fy (KSI)	70
B. Leg (in)	3	Design Thickness (in)	0.0190
Mils	18	Minimum Thickness (in)	0.0181
Finish*	G40EQ	Gauge EQ	20 DW

*Or other ASTM A1003 Table 1 Coating

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Weight of Member: (lb/ft)	0.7694
Cross Sectional Area: A (in²)	0.2263
Moment of Inertia: Ix (in⁴)	1.3005
Section Modulus about the X-axis: Sx (in³)	0.4358
Radius of Gyration: Rx (in)	2.3973
Gross Moment of Inertia: Iy (in⁴)	0.2051
Section Modulus about the Y-axis: Sy (in³)	0.0923
Gross Radius of Gyration: Ry (in)	0.9521

EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: Ixd (in⁴)	0.4514
Section Modulus: Sxe (in³)	0.0964
Allowable Moment: Ma (in-k)	3.3750

TORSIONAL PROPERTIES

Shear Center to Centroid on Principal X-axis: Xo (in)	-1.8309
St. Venant Torsional Constant: Jx10³ (in⁴)	0.0272
Torsional Warping Constant: Cw (in⁶)	1.3248
Radius of Gyration on the Centroid Principal axis: ro (in)	3.1632
Torsional Flexural Constant: β=1-(xo/ro)²	0.6650

CODES & STANDARDS

- Meets IBC 2015, 2018 & FBC 2017
- Meets or tested to: ASTM C 645, C 754, E 90, E 119 & AISI S220
- Steel sheet meets ASTM A 1003 & A 653
- Third Party Code Evaluation Report: CCRR-0154
- Multiple Fire Rated Assemblies

GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information



09.22.16 Non-Structural Metal Stud

