

Marino\WARE® Product Submittal Data

PRODUCT NAME: Viper20 (600VT200-18)

MARINO\WARE PART # 600VT218

PROPERTIES:

A. Web (in)	6	Yield Strength Fy (KSI)	70
B. Leg (in)	2	Design Thickness (in)	0.0190
Mils	18	Minimum Thickness (in)	0.0181
Finish*	G40EQ	Gauge EQ	20 DW

*Or other ASTM A1003 Table 1 Coating

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Weight of Member: (lb/ft)	0.6402
Cross Sectional Area: A (in²)	0.1883
Moment of Inertia: Ix (in⁴)	0.9831
Section Modulus about the X-axis: Sx (in³)	0.3294
Radius of Gyration: Rx (in)	2.2851
Gross Moment of Inertia: Iy (in⁴)	0.0667
Section Modulus about the Y-axis: Sy (in³)	0.0425
Gross Radius of Gyration: Ry (in)	0.5950

EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: Ixd (in⁴)	0.4206
Section Modulus: Sxe (in³)	0.0954
Allowable Moment: Ma (in-k)	3.3380

TORSIONAL PROPERTIES

Shear Center to Centroid on Principal X-axis: Xo (in)	-1.0225
St. Venant Torsional Constant: Jx10³ (in⁴)	0.0227
Torsional Warping Constant: Cw (in⁶)	0.4392
Radius of Gyration on the Centroid Principal axis: ro (in)	2.5731
Torsional Flexural Constant: β=1-(xo/ro)²	0.8421

CODES & STANDARDS

- Meets IBC 2015, 2018 & FBC 2017
- Meets or tested to: ASTM C 645, C 754, E 90, E 119 & AISI S220
- Steel sheet meets ASTM A 1003 & A 653
- Third Party Code Evaluation Report: CRR-0154
- Multiple Fire Rated Assemblies

GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information



09.22.16 Non-Structural Metal Stud

