

Marino\WARE® Product Submittal Data

PRODUCT NAME: Viper20 (600VT125-18)

MARINO\WARE PART # 600VT18

PROPERTIES:

A. Web (in)	6	Yield Strength Fy (KSI)	50
B. Leg (in)	1-1/4	Design Thickness (in)	0.0190
Mils	18	Minimum Thickness (in)	0.0181
Finish	CP60	Gauge EQ	20 DW

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Weight of Member: (lb/ft)	0.5433
Cross Sectional Area: A (in²)	0.1598
Moment of Inertia: Ix (in⁴)	0.7400
Section Modulus about the X-axis: Sx (in³)	0.2480
Radius of Gyration: Rx (in)	2.1521
Gross Moment of Inertia: Iy (in⁴)	0.0174
Section Modulus about the Y-axis: Sy (in³)	0.0107
Gross Radius of Gyration: Ry (in)	0.3303

EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: Ixd (in⁴)	0.4203
Section Modulus: Sxe (in³)	0.1052
Allowable Moment: Ma (in-k)	2.6309

TORSIONAL PROPERTIES

Shear Center to Centroid on Principal X-axis: Xo (in)	-0.4903
St. Venant Torsional Constant: Jx10³ (in⁴)	0.0192
Torsional Warping Constant: Cw (in⁶)	0.1218
Radius of Gyration on the Centroid Principal axis: ro (in)	2.2318
Torsional Flexural Constant: β=1-(xo/ro)²	0.9517

CODES & STANDARDS


- Meets IBC 2015, 2018 & FBC 2017
- Meets or tested to: ASTM C 645, C 754, E 90, E 119 & AISI S220
- Steel sheet meets ASTM A 1003 & A 653
- Third Party Code Evaluation Report: CCRR-0154
- Multiple Fire Rated Assemblies

GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information



09.22.16 Non-Structural Metal Stud



www.marinoware.com

For more information, please contact Marino\WARE Technical Services at 866-545-1545

This technical information reflects the most current information available and supersedes any and all publications, effective 11/30/19.

©Copyright 2019 by Ware Industries, Inc. All rights reserved