

Marino\WARE® Product Submittal Data

PRODUCT NAME: 362VT125-15

MARINO\WARE PART # 358VT25

PROPERTIES:

A. Web (in)	3-5/8	Yield Strength Fy (KSI)	50
B. Leg (in)	1-1/4	Design Thickness (in)	0.0155
Mils	15	Minimum Thickness (in)	0.0147
Finish	CP60	Gauge EQ	25

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Weight of Member: (lb/ft)	0.320
Cross Sectional Area: A (in²)	0.095
Moment of Inertia: Ix (in⁴)	0.197
Section Modulus about the X-axis: Sx (in³)	0.105
Radius of Gyration: Rx (in)	1.440
Gross Moment of Inertia: Iy (in⁴)	0.014
Section Modulus about the Y-axis: Sy (in³)	0.0139
Gross Radius of Gyration: Ry (in)	0.381

EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: Ixd (in⁴)	0.115
Section Modulus: Sxe (in³)	0.039
Allowable Moment: Ma (in-k)	1.150

TORSIONAL PROPERTIES

Shear Center to Centroid on Principal X-axis: Xo (in)	-0.665
St. Venant Torsional Constant: Jx10³ (in⁴)	0.0076
Torsional Warping Constant: Cw (in⁶)	0.035
Radius of Gyration on the Centroid Principal axis: Ro (in)	1.630
Torsional Flexural Constant: β=1-(xo/Ro)²	0.833

CODES & STANDARDS


- Meets IBC 2015, 2018 & FBC 2017
- Meets or tested to: ASTM C 645, C 754, E 90, E 119 & AISI S220
- Steel sheet meets ASTM A 1003 & A 653
- Third Party Code Evaluation Report: CCRR-0154
- Multiple Fire Rated Assemblies

GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information.



09.22.16 Non-Structural Metal Stud



For more information, please contact Marino\WARE Technical Services at 866-545-1545

This technical information reflects the most current information available and supersedes any and all publications, effective 11/3/19.
©Copyright 2019 by Ware Industries, Inc. All rights reserved