Marino\WARE® Product Submittal Data

162VS125-30

158VS30

PRODUCT NAME:

MARINO\WARE PART #

PROPERTIES:

A. Web (in)	1-5/8	Yield Strength Fy (KSI)	33
B. Flange (in)	1-1/4	Design Thickness (in)	0.0312
C. Lip (in)	1/4"	Minimum Thickness (in)	0.0296
Mils	30	Gauge	20 DW
Finish	CP60		

SECTION PROPERTIES

GROSS SECTION PROPERTIES	
Weight of Member: (lb/ft)	0.460
Cross Sectional Area: A (in ²)	0.135
Moment of Inertia: Ix (in ⁴)	0.062
Radius of Gyration: Rx (in)	0.680
Gross Moment of Inertia: Iy (in ⁴)	0.028
Gross Radius of Gyration: Ry (in)	0.455
EFFECTIVE SECTION PROPERTIES	
Moment of Inertia-Deflection: Ix (in ⁴)	0.062
	0.062 0.067
Moment of Inertia-Deflection: Ix (in ⁴)	
Moment of Inertia-Deflection: Ix (in ⁴) Section Modulus: Sx (in ³)	

LIMITING HEIGHTS - COMPOSITE (ft-in)

Distortional Buckling Moment: Mnd (in-k)

	5 psf		7.5 psf		10 psf				
Spacing (in)	L/120	L/240	L/360	L/120	L/240	L/360	L/120	L/240	L/360
12	14-7	11-6	10-0	12-9	10-0	8-6	11-7	8-11	-
16	13-3	10-5	8-11	11-7	8-11	-	10-6	7-10	-
24	11-7	8-11	-	10-1	-	-	8-10	-	-

1. Gypsum must be vertically oriented, applied full height to both sides, and fastened to each stud and track flange

2.380

2. Acceptable wallboards are 5/8" type X from: USG, National, GP, Pabco, American, Continental & CertainTeed.

3. No screws are required between stud and track, except as required by ASTM C754.

4. See CCRR-0154 for additional information. Review fire related assemblies for any additional requirements

CODES & STANDARDS

- Meets IBC 2015, 2018 & FBC 2020
- ASTM C 645, C 754, E 90, E 119, & AISI S220
- Steel sheet meets ASTM A 1003 or A 653
- Third Party Code Evaluation Report: CCRR-1054
- Multiple Fire Rated Assemblies

GREEN INFO

- LEED v4 credits available
- Contact Technical Services for more information



For more information, please contact Marino\WARE Technical Services at 866-545-1545

This technical information reflects the most current information available and supersedes any and all publications, effective 4/2/22. ©Copyright 2022 by Ware Industries, Inc. All rights reserved



09.22.16 Non-Structural Metal Stud



