

# Marino\WARE® Product Submittal Data

**PRODUCT NAME:** 250VT300-30

**MARINO\WARE PART #** 212VT330

## PROPERTIES:

<b>A. Web (in)</b>	2-1/2	<b>Yield Strength Fy (KSI)</b>	33
<b>B. Leg (in)</b>	3	<b>Design Thickness (in)</b>	0.0312
<b>Mils</b>	30	<b>Minimum Thickness (in)</b>	0.0296
<b>Finish</b>	CP60	<b>Gauge</b>	20 DW

## SECTION PROPERTIES

### GROSS SECTION PROPERTIES

Weight of Member: <b>(lb/ft)</b>	0.900
Cross Sectional Area: <b>A (in<sup>2</sup>)</b>	0.266
Moment of Inertia: <b>Ix (in<sup>4</sup>)</b>	0.363
Section Modulus about the X-axis: <b>Sx (in<sup>3</sup>)</b>	0.274
Radius of Gyration: <b>Rx (in)</b>	1.170
Gross Moment of Inertia: <b>Iy (in<sup>4</sup>)</b>	0.262
Section Modulus about the Y-axis: <b>Sy (in<sup>3</sup>)</b>	0.135
Gross Radius of Gyration: <b>Ry (in)</b>	0.993

### EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: <b>Ixd (in<sup>4</sup>)</b>	0.204
Section Modulus: <b>Sxe (in<sup>3</sup>)</b>	0.104
Allowable Moment: <b>Ma (in-k)</b>	2.060

### TORSIONAL PROPERTIES

Shear Center to Centroid on Principal X-axis: <b>Xo (in)</b>	-2.350
St. Venant Torsional Constant: <b>Jx10<sup>3</sup> (in<sup>4</sup>)</b>	0.0862
Torsional Warping Constant: <b>Cw (in<sup>6</sup>)</b>	0.329
Radius of Gyration on the Centroid Principal axis: <b>Ro (in)</b>	2.800
Torsional Flexural Constant: <b>β = 1-(xo/Ro)<sup>2</sup></b>	0.299

## CODES & STANDARDS

- Meets IBC 2015, 2018 & FBC 2017
- Meets or tested to: ASTM C 645, C 754, E 90, E 119 & AISI S220
- Steel sheet meets ASTM A 1003 & A 653
- Third Party Code Evaluation Report: CCRR-0154
- Multiple Fire Rated Assemblies

## GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information.



09.22.16 Non-Structural Metal Stud

