



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

#### **SECTION 1. IDENTIFICATION**

Product name : SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Product code : 00000000051668469

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

#### **SECTION 2. HAZARDS IDENTIFICATION**

## GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : 2

Serious eye damage/eye

irritation

: Category 2A

Skin sensitization : Category 1

Germ cell mutagenicity : 2

Short-term (acute) aquatic

hazard

2

Long-term (chronic) aquatic

hazard

2

**GHS** label elements

Hazard pictograms :







Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

H341 Suspected of causing genetic defects.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements**

#### Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P202 Do not handle until all safety precautions have been read and understood.

P272 Contaminated work clothing should not be allowed out of the workplace.

P264 Wash face, hands and any exposed skin thoroughly after handling.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

#### Storage:

P405 Store locked up.

## Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
bisphenol A-epichlorohydrin resin	25068-38-6	>= 25 - < 75
Reaction product: bisphenol-A-	25068-38-6	>= 25 - < 75



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)		
talc	14807-96-6	>= 15 - < 25
2,3-epoxypropyl o-tolyl ether	2210-79-9	>= 10 - < 15
Titanium dioxide	13463-67-7	>= 5 - < 7

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Suspected of causing genetic defects.

Notes to physician : Treat symptomatically.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry powder Foam

Unsuitable extinguishing

media

High volume water jet



## SikaEmaco ADH 326 Part A Formerly MEmaco **ADH 326 PTA**

Version SDS Number: Date of last issue: -Revision Date:

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : Use personal protective equipment.

tive equipment and emer-

gency procedures

Prevent product from entering drains. **Environmental precautions** 

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Product is not explosive.

Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

the technological safety standards.

Further information on stor-

age conditions

: Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
				(Table Z-1)
		TWA value	10 mg/m3	29 CFR
		(Total dust)		1910.1000
				(Table Z-1-A)
		TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA	10 mg/m3	ACGIH
			(Titanium dioxide)	
talc	14807-96-6	TWA value	2 mg/m3	ACGIHTLV
		(Respirable		
		fraction)		
		TWA (Dust)	20 Million parti-	OSHA Z-3
		, ,	cles per cubic foot	
		TWA (respir-	2 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	2 mg/m3	NIOSH REL
		pirable)		
		TWA	0.1 fibres per	ACGIH
			cubic centimeter	
		TWA (Res-	2 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		

**Engineering measures** : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

tional exposure limits they must use appropriate certified

respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : white

pH : not applicable

Boiling point : approx. 248 °F / 120 °C

Flash point : 480 °F / 249 °C

Method: Flash-Point by Pensky-Martens Closed Cup Tester.

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : approx. 1.35 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : emulsifiable (68 °F / 20 °C)

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Remarks : May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks : May cause irreversible eye damage.

#### Respiratory or skin sensitization

## Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.

## Germ cell mutagenicity

Suspected of causing genetic defects.

#### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

# SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

**Further information** 

**Product:** 

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

**Product:** 

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

**Product:** 

Biodegradability : Remarks: Taking into consideration the properties of several

ingredients, the product is estimated not to be readily biode-

gradable according to OECD classification.

Stability in water : Remarks: The product is slightly soluble in water. It can be

eliminated from water by abiotic processes.

**Bioaccumulative potential** 

**Product:** 

Bioaccumulation : Remarks: Because of the product's consistency and low water

solubility, bioavailability is improbable.

**Components:** 

talc:

Partition coefficient: n-

octanol/water

Remarks: not applicable

2,3-epoxypropyl o-tolyl ether:

Partition coefficient: n-

octanol/water

log Pow: 2.16 (77 °F / 25 °C) Method: other (calculated)

Titanium dioxide:

Partition coefficient: n-

octanol/water

Remarks: not applicable





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

### Mobility in soil

#### Product:

Distribution among environmental compartments Remarks: The substance will not evaporate into the atmos-

phere from the water surface.

Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not ex-

pected.

Following exposure to soil, adsorption to solid soil particles is unlikely, therefore contamination of groundwater is expected.

#### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### **UNRTDG**

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(REACTION PRODUCT BISPHENOL-A)

Class : 9

Subsidiary risk : EHSM Packing group : III

Labels : 9 (EHSM)

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(REACTION PRODUCT BISPHENOL-A)



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

Class : 9
Subsidiary risk : EHSM
Packing group : III

Labels : Miscellaneous, Environmentally hazardous

Packing instruction (cargo :

aircraft)

Packing instruction (passen-

ger aircraft)

964

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(REACTION PRODUCT BISPHENOL-A)

Class : 9
Subsidiary risk : EHSM
Packing group : III
Labels : 9 (EHSM)

Labels : 9 (EHSM EmS Code : F-A, S-F Marine pollutant : yes

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **Domestic regulation**

### 49 CFR

Not regulated as a dangerous good

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## **SECTION 15. REGULATORY INFORMATION**

Clean Air Act

:

CA TAC :

HON HAP (US)

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Ambient air standard::

Threshold for emissions from stacks 40 to less than 75 ft::



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

Threshold for emissions from stacks greater than or equal to 75 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks less than 25 ft::

Ambient air standard::

Ambient air standard::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to

75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

HON SOC (US) : Group I

:

VOC (US)

VOC EQ (US)

CAA (US) :

:

## **US State Regulations**

Pennsylvania Right To Know

Titanium dioxide 13463-67-7 talc 14807-96-6

**New Jersey Right To Know** 

Titanium dioxide 13463-67-7 talc 14807-96-6

California Prop. 65

WARNING: This product can expose you to chemicals including 1-chloro-2,3-epoxypropane, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

TSCA Inventory exemption.

DSL All components of this product are on the Canadian DSL

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:

## Flammability Health Instability 2 0

Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV** 

threshold limit values (US)

NIOSH REL USA. NIOSH Recommended Exposure Limits

OSHA<sub>P0</sub> USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

Time Weighted Average (TWA):

eral Dusts

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA 8-hour, time-weighted average Time Weighted Average (TWA): ACGIHTLV / TWA value

Time-weighted average concentration for up to a 10-hour NIOSH REL / TWA

workday during a 40-hour workweek



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 07/27/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT



## SikaEmaco ADH 326 Part A Formerly MEmaco ADH 326 PTA

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000259976 Date of first issue: 07/27/2020

PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN