

Versior 1.0	Revision Date: 08/05/2021		DS Number: 60000009350	Date of last issue: - Date of first issue: 08/05/2021
SECTIO	ON 1. IDENTIFICATION			
Pre	oduct name	:	SikaEmaco ADH	612 Part A Formerly MEmaco 612 Part A
Pr	oduct code	:	0000000005840	08846
Ма	anufacturer or supplier's	deta	ails	
Co	mpany name of supplier	:	Sika MBCC US L	LC
Ad	dress	:	201 POLITO AVE Lyndhurst NJ 070	_
En	nergency telephone	:	ChemTel: +1-813	3-248-0585
Recommended use of the c		cher	nical and restriction	ons on use
Re	commended use	:	Product for const	ruction chemicals
Re	strictions on use	:	Reserved for indu	ustrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation	:	Category 2
Serious eye damage	:	Category 1
Skin sensitization	:	Category 1
Carcinogenicity (Inhalation)	:	Category 1A
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 1 (Lungs)
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 2 (Kidney, Immune system)

GHS label elements





Version 1.0	Revision Date: 08/05/2021	SDS Number: 96000009350	Date of last issue: - Date of first issue: 08/05/2021
Hazaı	rd pictograms		
Signa	l Word	: Danger	
Hazaı	rd Statements	H318 Causes H335 May cau H350 May cau H372 Causes repeated expo H373 May cau	skin irritation. se an allergic skin reaction. serious eye damage. se respiratory irritation. se cancer by inhalation. damage to organs (Lungs) through prolonged or sure if inhaled. se damage to organs (Kidney, Immune system) ged or repeated exposure if inhaled.
Preca	utionary Statements	Prevention:	
		P202 Do not h and understoo P260 Do not b P264 Wash sk P270 Do not e P271 Use only P272 Contami the workplace.	reathe dust/ fume/ gas/ mist/ vapors/ spray. in thoroughly after handling. at, drink or smoke when using this product. outdoors or in a well-ventilated area. nated work clothing must not be allowed out of ptective gloves/ protective clothing/ eye protection
		Response:	
		P304 + P340 + and keep com doctor if you fe P305 + P351 + water for sever and easy to do CENTER/ doc P308 + P313 I attention. P333 + P313 I attention.	P338 + P310 IF IN EYES: Rinse cautiously with ral minutes. Remove contact lenses, if present O. Continue rinsing. Immediately call a POISON
		tightly closed.	Store in a well-ventilated place. Keep container
		P405 Store loc	sked up.
		Disposal: P501 Dispose posal plant.	of contents/ container to an approved waste dis-



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2021	96000009350	Date of first issue: 08/05/2021

Other hazards

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: modified cement mortar

Components

Chemical name	CAS-No.	Concentration (% w/w)					
Cement, portland, chemicals	65997-15-1	>= 30 - < 50					
Quartz (SiO2)	14808-60-7	>= 20 - < 30					
hydroxypropyl methacrylate	27813-02-1	>= 5 - < 10					
Actual concentration is withheld as a trade secret							

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	First aid personnel should pay attention to their own safety. Remove contaminated clothing.
If inhaled	:	After inhalation of dust. Keep patient calm, remove to fresh air. If difficulties occur: Seek medical attention.
In case of skin contact	:	After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
In case of eye contact	:	Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control cen- ter or doctor.
Most important symptoms and effects, both acute and delayed	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure if inhaled. Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.
Notes to physician	:	Treat symptomatically.



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2021	96000009350	Date of first issue: 08/05/2021

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam Water spray Dry powder Carbon dioxide (CO2) Product itself is non-combustible. Only the packaging materi- als can catch fire. The extinguishing agents normally used are sufficient.
Unsuitable extinguishing media	:	water jet
Specific hazards during fire fighting	:	Exposure to decomposition products may be a hazard to health.
Hazardous combustion prod- ucts	:	harmful vapours
Further information	:	Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus and chemical- protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid dust formation. Avoid contact with skin and eyes. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.
Environmental precautions	:	Do not discharge into drains/surface waters/groundwater.
Methods and materials for containment and cleaning up	:	Sweep up and shovel into suitable containers for disposal. Avoid dust formation. Rinse with plenty of water. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	No special precautions necessary.
Advice on safe handling	:	Avoid dust formation. Avoid inhalation of dusts. Avoid contact with skin and eyes.



Versio 1.0	on Revision Date: 08/05/2021	SDS Number: 960000009350	Date of last issue: - Date of first issue: 08/05/2021	
		contact with tion of skin o mucous mer direct contac Pour downw emptying ba Breathing m	The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irrita- tion of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are de- canted without local exhaust ventilation.	
-	Further information on stor- ige conditions	: Containers s	hould be stored tightly sealed in a dry place.	
Ν	laterials to avoid	Segregate fr	om metals. om acids and bases.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace c			T	
Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible concentration	Basis
	05007.45.4	exposure)		4000
Cement, portland, chemicals	65997-15-1	TWA (Res-	1 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
		TWA (Res- pirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respir-	5 mg/m3	OSHA P0
		able dust	-	
		fraction)		
		TWA (Dust)	50 Million parti- cles per cubic foot	OSHA Z-3
Quartz (SiO2)	14808-60-7	TWA (Res-	0.05 mg/m3	OSHA Z-1
		pirable dust)		
		TWA (respir-	10 mg/m3 /	OSHA Z-3
		able)	%SiO2+2	
		TWA (respir-	250 mppcf /	OSHA Z-3
		able)	%SiO2+5	
		TWA (respir-	0.1 mg/m3	OSHA P0
		able dust		

Ingredients with workplace control parameters



sion	n Revision Date: SDS Number: 08/05/2021 96000009350			e of last issue: - e of first issue: 08/05/2021		
				fraction) TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
				PÉL (respir- able)	0.05 mg/m3	OSHA CA
				TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH RE
Engir	neering measures	:	Provide local P.E.L.	exhaust ventilati	on to maintain reco	mmended
Perso	onal protective equip	ment				
Respi	ratory protection	:	Wear appropriate certified respirator when exposure limits may be exceeded. Wear a NIOSH-certified (or equivalent) particulate respirator.			
Hand	protection					
Re	emarks	:			gloves. Manufacture ved because of grea	
Eye p	rotection	:	Tightly fitting safety goggles (chemical goggles).			
Skin a	and body protection	:	Body protection must be chosen based on level of activity and exposure.			
Protec	ctive measures	:	Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice.			
Hygie	ne measures	:	Hands and/or the end of the At the end of care agents a Gloves must Replace if ne Remove cont	shift. the shift the skin pplied. be inspected reg cessary (e.g. pin	washed before brea should be cleaned jularly and prior to e hole leaks). g immediately and o	and skin- ach use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Color

: greyish

: paste



Version 1.0	Revision Date: 08/05/2021		S Number: 0000009350	Date of last issue: - Date of first issue: 08/05/2021	
Odor		:	faint, earthy		
Odor	Threshold	:	Not determined	due to potential health hazard by inhalation.	
pН		:	No data availab	le	
Melti	ng point	:	No data availab	le	
Boilir	ng point/boiling range	:	No data availab	le	
Flash	n point	:	> 212 °F / > 100	℃ C	
Evap	oration rate	:	No data availab	le	
Flam	mability (solid, gas)	:	Not classified as	s a flammability hazard	
	er explosion limit / Upper nability limit	:	knowledge of its	ur experience with this product and our s composition we do not expect any hazard as duct is used appropriately and in accordance ed use.	
	er explosion limit / Lower nability limit	:	knowledge of its	ur experience with this product and our s composition we do not expect any hazard as duct is used appropriately and in accordance ed use.	
Vapo	or pressure	:	No data availab	le	
Relat	tive vapor density	:	No data available		
Relat	tive density	:	No data availab	le	
Dens	sity	:	1.7 - 1.8 g/cm3	(68 °F / 20 °C)	
	oility(ies) /ater solubility	:	No data availab	le	
S	olubility in other solvents	:	No data availab	le	
	tion coefficient: n- nol/water	:	No data available		
Autoi	ignition temperature	:	No data available		
Decc	omposition temperature	:	No decomposition if stored and handled as pre- scribed/indicated.		
Visco Vi	osity iscosity, dynamic	:	120 - 160 Pas (68 °F / 20 °C)	



Vers 1.0	sion	Revision Date: 08/05/2021	-	S Number: 0000009350	Date of last issue: - Date of first issue: 08/05/2021	
				Method: Brookfie	ld	
	Vis	cosity, kinematic	:	No data available	9	
	Explos	ive properties	:	Not explosive		
	Oxidizi	ng properties	:	No data available	9	
	Sublim	ation point	:	No data available	9	
	Molecu	ular weight	:	No data available	9	
SEC	SECTION 10. STABILITY AND REACTIVITY					
	Reacti	vity	:	No hazardous re scribed/indicatec	actions if stored and handled as pre-	
	Chemical stability		:	The product is stable if stored and handled as pre- scribed/indicated.		
	Possibility of hazardous reac- tions		:		e formed on the addition of water. able if stored and handled as pre-	
	Conditions to avoid		:	Avoid dust formation. Avoid humidity.		
	Incom	patible materials	:	Powdered metals Strong acids Strong bases Strong oxidizing		
	Hazaro produc	dous decomposition ts	:	No hazardous de as prescribed/inc	ecomposition products if stored and handled licated.	

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.





Vers 1.0	ion	Revision Date: 08/05/2021	SDS Number: 960000009350	Date of last issue: - Date of first issue: 08/05/2021			
	Respiratory sensitization Not classified based on available information.						
	Produc Remarl			product has been reduced. Sensitization due in stated shelf-live is unlikely.			
		cell mutagenicity ssified based on availa	able information.				
	Carcin	ogenicity					
	May ca IARC	use cancer by inhalati Group 1: Car Quartz (SiO2 (Silica dust, c	cinogenic to humans	14808-60-7			
	OSHA	OSHA specif Quartz (SiO2 (crystalline si		ogen 14808-60-7			
	NTP	Quartz (SiO2	human carcinogen :) alline (Respirable Size	14808-60-7			

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Product:

Skin contact		Remarks: In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.
Further information		
Product:		
Remarks	:	Health injuries are not known or expected under normal use.



ersion 0	Revision Date: 08/05/2021		DS Number: 0000009350	Date of last issue: - Date of first issue: 08/05/2021
	12. ECOLOGICAL INF	ORI	MATION	
Ecoto	oxicity			
<u>Produ</u>	<u>ict:</u>			
Ecoto	xicology Assessment			
Acute	aquatic toxicity	:	This product has	no known ecotoxicological effects.
Chron	ic aquatic toxicity	:	This product has	no known ecotoxicological effects.
Persis	stence and degradabil	ity		
<u>Produ</u>	<u>ict:</u>			
Biode	gradability	:	Remarks: Not ap	plicable for inorganic substances.
Bioac	cumulative potential			
<u>Produ</u>	<u>ict:</u>			
Bioac	cumulation	:		oduct will not be readily bioavailable due to nd insolubility in water.
Mobil	ity in soil			
<u>Produ</u>	<u>ict:</u>			
	oution among environ- al compartments	:	particles is proba is not expected.	ing exposure to soil, adsorption to solid soil ble, therefore contamination of groundwater rill not evaporate into the atmosphere from
			the water surface).
Other	adverse effects			
Produ	<u>uct:</u>			
Addition mation	onal ecological infor- n	:	The product has	e product into the environment without contro not been tested. The statements on ecotoxi n derived from the properties of the individua

Disposal methods		
Waste from residues	:	Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.
Contaminated packaging	:	Completely emptied packagings can be given for recycling. Packs that cannot be cleaned should be disposed of in the same manner as the contents.





: 08/05/2021

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2021	96000009350	Date of first issue: 08

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

US State Regulations


Pennsylvania Right To Know					
Cement, portland, chemicals	65997-15-1				
Quartz (SiO2)	14808-60-7				
New Jersey Right To Know					
Cement, portland, chemicals	65997-15-1				
Quartz (SiO2)	14808-60-7				
California Prop. 65					
WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.					
The ingredients of this product are reported in the following inventories:					

TSCA	:	All substances listed as active on the TSCA inventory
DSL	:	All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information





workday during a 40-hour workweek
Permissible exposure limit (PEL)
8-hour time weighted average
8-hour time weighted average
8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/05/2021	96000009350	Date of first issue: 08/05/2021

Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date

: 08/05/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN