



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

SECTION 1. IDENTIFICATION

Product name : Sikafloor CC 160 WB Formerly MKure CC 160WB

Product code : 00000000051679175

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Reproductive toxicity : Category 1B

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms

Signal Word : Danger

Hazard Statements : H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.





Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P201 Obtain special instructions before use.

P273 Avoid release to the environment.

P202 Do not handle until all safety precautions have been read and understood.

P284 In case of inadequate ventilation wear respiratory protec-

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
solvent naphtha	64742-95-6	>= 3 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 3
Diethylbenzene	25340-17-4	>= 0.2 - < 0.3
dibutyl phthalate	84-74-2	>= 0.2 - < 0.3
ethyleneglycol	107-21-1	>= 0.1 - < 1
methanol	67-56-1	>= 0.1 - < 1
Butyl diglycol	112-34-5	>= 0.1 - < 1





Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

cumene	98-82-8	>= 0.1 - < 1
diammonium peroxodisulphate	7727-54-0	>= 0 - < 0.2

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

Call a physician or poison control center immediately.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Immediately wash thoroughly with soap and water, seek med-

ical attention.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open.

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Suspected of causing cancer.

May damage fertility or the unborn child.

Sikafloor CC 160 WB Formerly MKure CC 160WB



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Product is not explosive.

Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-





Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Recommended storage tem: :

perature

41 °F / 5 °C

Further information on stor-

age stability

Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyl phthalate	84-74-2	TWA value	5 mg/m3	ACGIHTLV
		REL value	5 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
1,2,4-trimethylbenzene	95-63-6	TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 125 mg/m3	NIOSH
		TWA value	25 ppm	29 CFR





Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

			125 mg/m3	1910.1000 (Table Z-1-A)
		TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
diammonium peroxodisulphate	7727-54-0	TWA value	0.1 mg/m3 (persulfate)	ACGIHTLV
		TWA	0.1 mg/m3 (Persulphate)	ACGIH

Engineering measures No applicable information available.

Personal protective equipment

Respiratory protection Wear appropriate certified respirator when exposure limits

may be exceeded.

Hand protection

Remarks The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye wash bottle with pure water Eye protection

Tightly fitting safety goggles

Skin and body protection Impervious clothing

Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Color milky white

Odor characteristic, slight odour

Sikafloor CC 160 WB Formerly MKure CC 160WB



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

Odor Threshold : No data available

pH : slightly alkaline

Melting point : No applicable information available.

Boiling point : 307.99 - 401.00 °F / 153.33 - 205.00 °C

Flash point : $> 304 \, ^{\circ}\text{F} \, / > 151 \, ^{\circ}\text{C}$

Method: closed cup

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Flammable.

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

15.3 %(V)

(73 °F / 23 °C)

Lower explosion limit / Lower

flammability limit

: 0.9 %(V)

(73 °F / 23 °C)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 1 g/cm3 (68 °F / 20 °C)

Bulk density : not applicable

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

: No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive





Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation temperature : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability: No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Strong acids
Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

Incompatible materials

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapors may cause irritation to the eyes, respiratory system

Sikafloor CC 160 WB Formerly MKure CC 160WB



Version 1.0

Revision Date: 10/01/2020

SDS Number: 000000260262

Date of last issue: -

Date of first issue: 10/01/2020

and the skin.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

: Causes sensitization.

Product:

Remarks

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No data available.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

solvent naphtha:

Partition coefficient: n- : log Pow: 3.17





Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

octanol/water Method: other (calculated)

GLP: no

1,2,4-trimethylbenzene:

Partition coefficient: n-

octanol/water

log Pow: 3.63 (77 °F / 25 °C) Method: other (calculated)

dibutyl phthalate:

Partition coefficient: n-

octanol/water

log Pow: 4.57 (77 °F / 25 °C) Method: other (calculated)

Metriod. Other (calculated)

log Pow: 4.79 (77 °F / 25 °C) Method: other (measured)

GLP: yes

Remarks: The data refers to the undissociated form of the

substance.

ethyleneglycol:

Partition coefficient: n-

octanol/water

log Pow: approx. -1.36 (73 °F / 23 °C)

Method: Calculation Hansch/Leo

GLP: no data

Remarks: Information taken from reference works and the

literature.

methanol:

Partition coefficient: n-

octanol/water

log Pow: -0.77 (68 °F / 20 °C) Method: other (measured)

GLP: no data

Remarks: Information taken from reference works and the

literature.

Butyl diglycol:

Partition coefficient: n-

octanol/water

log Pow: 1 (68 °F / 20 °C)

pH: 7

Method: Partition coefficient (n-octanol/water), HPLC method.

GLP: yes

cumene:

Partition coefficient: n-

octanol/water

log Pow: 3.55 (73 °F / 23 °C)

Method: Partition coefficient (n-octanol/water), Shake-flask

method

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : An environmental hazard cannot be excluded in the event of

Sikafloor CC 160 WB Formerly MKure CC 160WB



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

mation unprofessional handling or disposal.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

1,2,4- 95-63-6

trimethylbenzene

US State Regulations

Pennsylvania Right To Know

1,2,4-trimethylbenzene 95-63-6

New Jersey Right To Know

Sikafloor CC 160 WB Formerly MKure CC 160WB



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

1,2,4-trimethylbenzene95-63-6methanol67-56-1dibutyl phthalate84-74-2

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and

dibutyl phthalate, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

1)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000



Sikafloor CC 160 WB Formerly MKure CC 160WB

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Time

: Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 10/01/2020



Sikafloor CC 160 WB Formerly MKure CC 160WB

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260262 Date of first issue: 10/01/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS. DESIGNS. DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN