

## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

### **SECTION 1. IDENTIFICATION**

Product name : SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL

750 FN Neu TB

Product code : 00000000055395217

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Carcinogenicity (Inhalation) : 1A

Short-term (acute) aquatic

hazard

3

Long-term (chronic) aquatic

hazard

. ,

**GHS** label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H350 May cause cancer.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P201 Obtain special instructions before use.



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

P202 Do not handle until all safety precautions have been read

and understood.

P273 Avoid release to the environment.

Response:

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

No data available.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Acrylic polymer

inorganic compounds

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 20 - < 50
Perlite, expanded	93763-70-3	>= 0 - < 5
ethyleneglycol	107-21-1	>= 1 - < 3
zinc oxide	1314-13-2	>= 0.3 - < 1
Poly(oxy-1,2-ethanediyl), .alpha	9036-19-5	>= 0.2 - < 1
[(1,1,3,3-tetramethylbutyl)phenyl]-		
.omegahydroxy-		
Quartz (SiO2)	14808-60-7	>= 0 - < 1
diuron	330-54-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate; 3-	55406-53-6	>= 0 - < 0.1
iodoprop-2-yn-1-yl butylcarbamate		

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause cancer.

Notes to physician : Treat symptomatically.

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version SDS Number: Date of last issue: -Revision Date:

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against : Product is not explosive.

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Keep container tightly closed in a dry and well-ventilated Conditions for safe storage

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Recommended storage tem-

perature

41 °F / 5 °C

Further information on stor-

age stability

Minimum storage temperature:

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyleneglycol	107-21-1	TWA value (Vapor frac- tion)	25 ppm	ACGIHTLV



# SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

		STEL value (Vapor frac- tion)	50 ppm	ACGIHTLV
		STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTLV
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		С	50 ppm 125 mg/m3	OSHA P0
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
zinc oxide	1314-13-2	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		STEL value (Respirable fraction)	10 mg/m3	ACGIHTLV
		REL value (fumes/smok e)	5 mg/m3	NIOSH
		REL value (dust)	5 mg/m3	NIOSH
		STEL value (fumes/smok e)	10 mg/m3	NIOSH
		Ceil_Time (dust)	15 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable	5 mg/m3	29 CFR 1910.1000



# SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

	,	,	1	
		fraction)		(Table Z-1-A)
		TWA value	10 mg/m3	29 CFR
		(Total dust)		1910.1000
				(Table Z-1-A)
		STEL value	10 mg/m3	29 CFR
		(fumes/smok		1910.1000
		e)		(Table Z-1-A)
		TWA (Res-	2 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
		STEL (Res-	10 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
		TWA (Dust)	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	NIOSH REL
		(Fumes)		
		ST (Fumes)	10 mg/m3	NIOSH REL
		C (Dust)	15 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		(Fumes)		
		TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA (respir-	5 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA	5 mg/m3	OSHA P0
		(Fumes)		
		STEL	10 mg/m3	OSHA P0
		(Fumes)		
Limestone	1317-65-3	REL value	5 mg/m3	NIOSH
		(Respirable)		
		REL value	10 mg/m3	NIOSH
		(Total)		
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)		1910.1000
		<b>'</b>		(Table Z-1)
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
				(Table Z-1)
		TWA value	5 mg/m3	29 CFR
		(Respirable		1910.1000
		fraction)		(Table Z-1-A)
		TWA value	15 mg/m3	29 CFR
		(Total dust)		1910.1000
		,		(Table Z-1-A)
		TWA (total	15 mg/m3	OSHA Z-1



# SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

I	ĺ	duot)	1	
		dust) TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)	5 mg/ms	03/1A Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Perlite, expanded	93763-70-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Res- pirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir- able dust	0.1 mg/m3	OSHA P0



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

fraction)		
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

**Engineering measures** : Wear appropriate respiratory protection.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : pigmented

Odor : sweetish, slight odour

Odor Threshold : No data available



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

pH : approx. 9.2 - 10.0

Melting point : No applicable information available.

Freezing point No applicable information available.

Boiling point : 379.00 - 401.00 °F / 192.78 - 205.00 °C

Flash point : 200.01 °F / 93.34 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not flammable

Upper explosion limit / Upper

flammability limit

15.3 %(V)

Lower explosion limit / Lower

flammability limit

3.2 %(V)

Vapor pressure : No applicable information available.

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : approx. 1.2 - 1.4 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : soluble (68 °F / 20 °C)

Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

Metal corrosion rate : Corrosive effects to metal are not anticipated.

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability: No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Not classified based on available information.

## **Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Not classified based on available information.

### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

Not classified based on available information.

### **Product:**

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

## Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.

## Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

May cause cancer.

## Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

## STOT-repeated exposure

Not classified based on available information.

## **Aspiration toxicity**

Not classified based on available information.

## **Product:**

No aspiration hazard expected.

### **Further information**

**Product:** 

Remarks : No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

#### Components:

#### zinc oxide:

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic

toxicity)

1



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

## Persistence and degradability

### **Components:**

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Biodegradability : aerobic

Inoculum: activated sludge, domestic, non-adapted

Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: Modified OECD-Screening-Test.

## **Bioaccumulative potential**

## **Components:**

Perlite, expanded:

Partition coefficient: n-

Remarks: The value has not been determined because the

substance is inorganic.

ethyleneglycol:

Partition coefficient: n-

octanol/water

octanol/water

log Pow: approx. -1.36 (73 °F / 23 °C)

Method: Calculation Hansch/Leo

GLP: no data

Remarks: Information taken from reference works and the

literature.

zinc oxide:

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Bioaccumulation : Remarks: Accumulation in organisms is not to be expected.

Quartz (SiO2):

octanol/water

Partition coefficient: n-

Remarks: The value has not been determined because the

substance is inorganic.

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:

Partition coefficient: n- : log Pow: 2.81 (77 °F / 25 °C)

octanol/water Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes

Mobility in soil

No data available

Other adverse effects

**Product:** 



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

## **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethyleneglycol 107-21-1

## **US State Regulations**

## Pennsylvania Right To Know

ethyleneglycol 107-21-1 Limestone 1317-65-3

### **New Jersey Right To Know**



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

ethyleneglycol 107-21-1
Limestone 1317-65-3
Perlite, expanded 93763-70-3
Quartz (SiO2) 14808-60-7
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5

### California Prop. 65

WARNING: This product can expose you to chemicals including lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


## The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

### **SECTION 16. OTHER INFORMATION**

## **Further information**

### NFPA 704:



Special hazard

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

1910.1000

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Short Term Exposure Limit (STEL):

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / : OSHA Action level:

**OSHA** Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL): ACGIHTLV / TWA value : Time Weighted Average (TWA):

NIOSH / Ceil\_Time : Ceiling Limit Value and Time Period (if specified):

NIOSH / REL value : Recommended exposure limit (REL): NIOSH / STEL value : Short Term Exposure Limit (STEL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International



## SikaThorolastic-750 fine neutral tintbse Formerly MProtect EL 750 FN Neu TB

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/07/2020 000000260763 Date of first issue: 08/07/2020

Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/07/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN