

## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

### **SECTION 1. IDENTIFICATION**

Product name : Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Product code : 00000000050513506

### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

### **SECTION 2. HAZARDS IDENTIFICATION**

### GHS classification in accordance with 29 CFR 1910.1200

No need for classification according to GHS criteria for this product.

### **GHS label elements**

The product does not require a hazard warning label in accordance with GHS criteria.

### Other hazards

No data available.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No applicable information available.

### Components

Chemical name	CAS-No.	Concentration (% w/w)
bis(2,2,6,6-tetramethyl-4-	52829-07-9	>= 0.3 - < 1
piperidyl)sebacate		
N-(3-	1760-24-3	>= 0.3 - < 1
(Trimethoxysi-		
lyl)propyl)ethylenediamine		
dibutyltin dilaurate	77-58-7	>= 0.1 - < 0.2
ethylenediamine	107-15-3	>= 0 - < 1
stearic acid	57-11-4	>= 0.3 - < 3
calcium carbonate	471-34-1	>= 15 - < 50
Limestone	1317-65-3	>= 7 - < 20
Titanium dioxide	13463-67-7	>= 0 - < 3



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

### **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

If inhaled : No applicable information available.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash thoroughly with soap and water

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

None known.

Notes to physician : Treat symptomatically.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

: harmful vapours nitrogen oxides

fumes/smoke carbon black carbon oxides

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES** 

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Avoid dust formation.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust.

Sweep up and shovel.

Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE** 

Advice on protection against

fire and explosion

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Conditions for safe storage : Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, well-ventilated

place.

Protect from direct sunlight.
Store protected against freezing.

Materials to avoid : No applicable information available.

No materials to be especially mentioned.

Further information on stor-

age stability

No data available

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
stearic acid	57-11-4	TWA value	10 mg/m3	ACGIHTLV
		(Inhalable		
		fraction)		
		TWA value	3 mg/m3	ACGIHTLV



# **Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base**

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

<u> </u>		(Respirable	1	1
		fraction)		
		TWA (Inhal-	10 mg/m3	ACGIH
		able particu-	3	
		late matter)		
		TWA (Res-	3 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
<del>                                  </del>		ter)		
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m3	ACGIHTLV
		STEL value	(tin (Sn)) 0.2 mg/m3	ACGIHTLV
		31 EL value	(tin (Sn))	ACGINILV
		REL value	0.1 mg/m3	NIOSH
		TEE VAIGE	(tin (Sn))	1410011
		PEL	0.1 mg/m3	29 CFR
			(tin (Sn))	1910.1000
				(Table Z-1)
		TWA value	0.1 mg/m3	29 CFR
			(tin (Sn))	1910.1000
				(Table Z-1-A)
		TWA	0.1 mg/m3	OSHA Z-1
		T10/0	(Tin)	400111
		TWA	0.1 mg/m3	ACGIH
		STEL	(Tin) 0.2 mg/m3	ACGIH
		SIEL	(Tin)	ACGIN
		TWA	0.1 mg/m3	OSHA P0
			(Tin)	
		TWA	0.1 mg/m3	NIOSH REL
			(Tin)	
ethylenediamine	107-15-3	TWA value	10 ppm	ACGIHTLV
		REL value	10 ppm	NIOSH
		551	25 mg/m3	22.050
		PEL	10 ppm	29 CFR
			25 mg/m3	1910.1000 (Table Z-1)
		TWA value	10 ppm	29 CFR
		TVVA value	25 mg/m3	1910.1000
			20 1119/1110	(Table Z-1-A)
		TWA	10 ppm	ACGIH
		TWA	10 ppm	NIOSH REL
			25 mg/m3	
		TWA	10 ppm	OSHA Z-1
			25 mg/m3	
		TWA	10 ppm	OSHA P0
			25 mg/m3	NIOC: :
	4-1 -1 -1			NIOSH
calcium carbonate	471-34-1	REL value	10 mg/m3	INIOOIT
calcium carbonate	471-34-1	(Total)		
calcium carbonate	471-34-1		10 mg/m3 5 mg/m3	NIOSH



# **Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base**

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

I				1
		able fraction)		1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total	10 mg/m3	OSHA P0





Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

dust)

TWA 10 mg/m3 ACGIH
(Titanium dioxide)

**Engineering measures** : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : impermeable gloves rubber Manufacturer's directions for use

should be observed because of great diversity of types.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Protective measures : Avoid contact with the skin, eyes and clothing.

No special measures necessary if stored and handled cor-

rectly.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : General industrial hygiene practice.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : white to off-white

Odor : faint odour

Odor Threshold : No data available

pH : not applicable

Melting point : No applicable information available.

Boiling range : not applicable

Flash point : 253.04 °F / 122.80 °C

Method: Standard Method of Test for Flash Point by Setaflash

Closed Tester, closed cup

Evaporation rate : No applicable information available.



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

Flammability (solid, gas) : No applicable information available.

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : 1.3700 g/cm3 (77.00 °F / 25.00 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : 4,000.000 mPa.s (77.00 °F / 25.00 °C)

Method: N-114; Brookfield Viscosity

10,000.000 mPa.s (77.00 °F / 25.00 °C) Method: N-114; Brookfield Viscosity

Viscosity, kinematic : No applicable information available.

Oxidizing properties : not determined

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

Possibility of hazardous reac- :

tions

: Stable under recommended storage conditions.

No hazards to be specially mentioned.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents
Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

### **Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

## **Aspiration toxicity**

Not classified based on available information.

#### **Product:**

No aspiration hazard expected.

### **Further information**

Product:

Remarks : No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

### **Components:**

### bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate:

Partition coefficient: n- : log Pow: 0.35 (77 °F / 25 °C)

octanol/water pH: 7

Method: Partition coefficient (n-octanol/water), Shake-flask

method

### N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Partition coefficient: n- : log Pow: -0.82

octanol/water Method: other (calculated)

dibutyltin dilaurate:

Partition coefficient: n- : log Pow: 3.17 (69.4 °F / 20.8 °C)

octanol/water pH: 6.1 - 6.3

Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes

ethylenediamine:

Partition coefficient: n- : log Pow: -2 - -1.3

octanol/water Method: other (measured)

GLP: no data

stearic acid:

Partition coefficient: n-

octanol/water

Remarks: No data available.



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

log Pow: 8.23

Method: other (measured)

calcium carbonate:

Partition coefficient: n-

octanol/water

: GLP: no

Remarks: The value has not been determined because the

substance is inorganic.

Titanium dioxide:

Partition coefficient: n-

octanol/water

Remarks: not applicable

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Disposal requirements are dependent on the hazard classifi-

cation and will vary by location and the type of disposal se-

lected.

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater. Residues should be disposed of in the same manner as the

substance/product.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous

waste.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

## **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

### **UNRTDG**

Not regulated as a dangerous good

IATA-DGR



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

**49 CFR** 

Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

### **US State Regulations**

### Pennsylvania Right To Know

calcium carbonate	471-34-1
Limestone	1317-65-3
Titanium dioxide	13463-67-7
Di-isononylphthalate	28553-12-0
bis(2-propylheptyl) phthalate	53306-54-0
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	68515-48-0
CO rich	

C9-rich

### **New Jersey Right To Know**

calcium carbonate	471-34-1
Limestone	1317-65-3
Titanium dioxide	13463-67-7
bis(2-propylheptyl) phthalate	53306-54-0
Quartz (SiO2)	14808-60-7

### California Prop. 65

WARNING: This product can expose you to chemicals including lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

### **SECTION 16. OTHER INFORMATION**

### **Further information**




## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -


1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

### NFPA 704:



Special hazard

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1) 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 08/12/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU



## Sikaflex HY 100 tint base Formerly MSeal NP 100 Tint Base

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/12/2020 000000828243 Date of first issue: 08/12/2020

EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN