Sikagard AWB 660 Formerly MSeal AWB 660



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/05/2021

 1.2
 11/02/2022
 000000260345
 Date of first issue: 05/20/2020

SECTION 1. IDENTIFICATION

Product name : Sikagard AWB 660 Formerly MSeal AWB 660

Product code : 00000000050161622

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

Sikagard AWB 660 Formerly MSeal AWB 660



Version Revision Date: SDS Number: Date of last issue: 01/05/2021 1.2 11/02/2022 000000260345 Date of first issue: 05/20/2020

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : polymers

inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
crystalline silica	14808-60-7	>= 20 - < 30
Limestone	1317-65-3	>= 10 - < 20
Titanium dioxide	13463-67-7	>= 1 - < 5
propane-1,2-diol	57-55-6	>= 1 - < 5
cristobalite	14464-46-1	>= 1 - < 5
Kieselguhr, soda ash flux-calcined	68855-54-9	>= 1 - < 5
1,3,5-Triazine-1,3,5(2H,4H,6H)-	4719-04-4	>= 0.1 - < 1
triethanol		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

Sikagard AWB 660 Formerly MSeal AWB 660



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/05/2021

 1.2
 11/02/2022
 000000260345
 Date of first issue: 05/20/2020

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air.

If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Contact lenses should be removed. Hold eyelids open and

flush with copious amounts of clean, fresh water or a special

eyewash solution and seek medical advice.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod-

ucts

fumes/smoke harmful vapours Carbon oxides nitrogen oxides

nitrogen oxides carbon black

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment : Wear a self-contained breathing apparatus.

Sikagard AWB 660 Formerly MSeal AWB 660



Version **Revision Date:** SDS Number: Date of last issue: 01/05/2021 11/02/2022 000000260345 Date of first issue: 05/20/2020 1.2

for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wear eye/face protection. Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Contain contaminated water/firefighting water. Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid inhalation of dusts/mists/vapours.

Avoid skin contact.

Ensure adequate ventilation.

No special measures necessary provided product is used

correctly.

Keep only in the original container in a cool, dry, well-Conditions for safe storage

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem-

perature

 $> 39 \,^{\circ}\text{F} / > 4 \,^{\circ}\text{C}$

Further information on stor-

age stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
crystalline silica	14808-60-7	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir-	0.1 mg/m3	OSHA P0





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/05/2021

 1.2
 11/02/2022
 000000260345
 Date of first issue: 05/20/2020

1	1	1	1	1
		able dust		
		fraction)	0.005 / 0	400:::
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	
		ticulate mat-		
		ter)		
		TWA (Res-	0.05 mg/m3	NIOSH REL
		pirable dust)	(Silica)	
Limestone	1317-65-3	TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)	4.5 / 0	00114 00
		TWA (Total	15 mg/m3	OSHA P0
		dust)		
		TWA (respir-	5 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	5 mg/m3	NIOSH REL
		pirable)	(Calcium car-	
			bonate)	
		TWA (total)	10 mg/m3	NIOSH REL
			(Calcium car-	
			bonate)	
Titanium dioxide	13463-67-7	TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA (Res-	0.2 mg/m3	ACGIH
		pirable par-	(Titanium dioxide)	
		ticulate mat-		
		ter)		
		TWA (Res-	2.5 mg/m3	ACGIH
		pirable par-	(Titanium dioxide)	
		ticulate mat-		
		ter)		
propane-1,2-diol	57-55-6	TWA	10 mg/m3	US WEEL
cristobalite	14464-46-1	TWA (Res-	0.05 mg/m3	OSHA Z-1
		pirable dust)		
		TWA (respir-	0.05 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	1
		ticulate mat-	(=7	
		ter)		
		TWA (Res-	0.05 mg/m3	NIOSH REL
		pirable dust)	(Silica)	
Kieselguhr, soda ash flux-	68855-54-9	REL value	6 mg/m3	NIOSH
calcined				
		TWA value	20 millions of	29 CFR
			particles per cubic	1910.1000
			foot of air	(Table Z-3)
		TWA value	0.8 mg/m3	29 CFR
		I VVA VAIUE	3.0 mg/mo	1910.1000
	1			1010.1000

Sikagard AWB 660 Formerly MSeal AWB 660



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/05/2021

 1.2
 11/02/2022
 000000260345
 Date of first issue: 05/20/2020

		(Table Z-3)
OSHA Action	0.025 mg/m3	29 CFR
level	(Respirable dust)	1910.1001-
		1050
TWA value	0.05 mg/m3	29 CFR
	(Respirable dust)	1910.1001-
		1050
TWA (Dust)	20 Million parti-	OSHA Z-3
, ,	cles per cubic foot	
	(Silica)	
TWA (Dust)	80 mg/m3 /	OSHA Z-3
, ,	%SiO2	
	(Silica)	
TWA	6 mg/m3	NIOSH REL
	(Silica)	

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Sikagard AWB 660 Formerly MSeal AWB 660



Version Revision Date: SDS Number: Date of last issue: 01/05/2021 1.2 11/02/2022 000000260345 Date of first issue: 05/20/2020

Color : gray

Odor : slight odour, acidulous

Odor Threshold : not determined

pH : 8 - 9.5 (73 °F / 23 °C)

Melting point : No data available

Boiling point : Not applicable

Flash point : A flash point determination is unnecessary due to the high

water content.

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : No data available

Density : 1.47 g/cm3 (73 °F / 23 °C)

12.27 lb/USg

Bulk density : Not applicable

Solubility(ies)

Water solubility : soluble, partly miscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : Based on the water content the product does not ignite.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Sikagard AWB 660 Formerly MSeal AWB 660



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/05/2021

 1.2
 11/02/2022
 000000260345
 Date of first issue: 05/20/2020

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Sikagard AWB 660 Formerly MSeal AWB 660



Version Revision Date: SDS Number: Date of last issue: 01/05/2021 1.2 11/02/2022 000000260345 Date of first issue: 05/20/2020

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

crystalline silica 14808-60-7

(Silica dust, crystalline)

Group 1: Carcinogenic to humans

cristobalite 14464-46-1

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

NTP Known to be human carcinogen

crystalline silica 14808-60-7

(Silica, Crystalline (Respirable Size)) Known to be human carcinogen

cristobalite 14464-46-1

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Sikagard AWB 660 Formerly MSeal AWB 660



Version Revision Date: SDS Number: Date of last issue: 01/05/2021 1.2 11/02/2022 000000260345 Date of first issue: 05/20/2020

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several

ingredients, the product is estimated not to be readily biode-

gradable according to OECD classification.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available.

Discharge into the environment must be avoided.

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Sikagard AWB 660 Formerly MSeal AWB 660



Version Revision Date: SDS Number: Date of last issue: 01/05/2021 1.2 11/02/2022 000000260345 Date of first issue: 05/20/2020

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

crystalline silica	14808-60-7
Limestone	1317-65-3
Titanium dioxide	13463-67-7
propane-1,2-diol	57-55-6
cristobalite	14464-46-1
Kieselguhr, soda ash flux-calcined	68855-54-9
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

New Jersey Right To Know

crystalline silica	14808-60-7
Limestone	1317-65-3
Titanium dioxide	13463-67-7
propane-1,2-diol	57-55-6
cristobalite	14464-46-1

California Prop. 65

WARNING: This product can expose you to chemicals including crystalline silica, which is/are known to the State of California to cause cancer, and

4-vinyl cyclohexene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains one or more components not listed on

the Canadian DSL or NDSL. All other components are on the

Canadian DSL.

SECTION 16. OTHER INFORMATION


Further information

Sikagard AWB 660 Formerly MSeal AWB 660




Version Revision Date: SDS Number: Date of last issue: 01/05/2021 1.2 11/02/2022 000000260345 Date of first issue: 05/20/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic

Sikagard AWB 660 Formerly MSeal AWB 660



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/05/2021

 1.2
 11/02/2022
 000000260345
 Date of first issue: 05/20/2020

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/02/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN