

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

Version 2.0      Revision Date: 06/11/2024      SDS Number: 000000267665      Date of last issue: 01/08/2021  
Date of first issue: 06/11/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikalastic-315 Formerly MSeal 615  
Product code : 000000000057152697

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1  
Carcinogenicity (Inhalation) : Category 1A  
Specific target organ toxicity : Category 1 (Lungs)  
- repeated exposure (Inhalation)  
Specific target organ toxicity : Category 2 (Kidney, Immune system)  
- repeated exposure (Inhalation)

#### GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black silhouette of a person's head and neck, with a starburst symbol on the neck, representing Health Hazard. The second is a red diamond with a black exclamation mark, representing a general hazard.

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H350 May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
H373 May cause damage to organs (Kidney, Immune system)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

Version 2.0      Revision Date: 06/11/2024      SDS Number: 000000267665      Date of last issue: 01/08/2021  
Date of first issue: 06/11/2020

through prolonged or repeated exposure if inhaled.

### Precautionary Statements

- Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.
- Storage:**  
P405 Store locked up.
- Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution

### Components

| Chemical name                             | CAS-No.    | Concentration (% w/w) |
|---|------------|-----------------------|
| Asphalt                                   | 8052-42-4  | >= 20 - < 30          |
| Quartz (SiO <sub>2</sub> )                | 14808-60-7 | >= 1 - < 5            |
| 1,3,5-Triazine-1,3,5(2H,4H,6H)-triethanol | 4719-04-4  | >= 0.1 - < 1          |

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/08/2021  |
| 2.0     | 06/11/2024     | 000000267665 | Date of first issue: 06/11/2020 |

---

- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.  
Remove contact lenses, if present.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water.  
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

Version 2.0      Revision Date: 06/11/2024      SDS Number: 000000267665      Date of last issue: 01/08/2021  
Date of first issue: 06/11/2020

Special protective equipment : Wear a self-contained breathing apparatus.  
for fire-fighters

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.  
Pick up with inert absorbent material (e.g. sand, earth etc.).  
Spilled product should be disposed in accordance with all applicable government regulations.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid aerosol formation.  
Avoid inhalation of mists/vapours.  
Avoid skin contact.  
Avoid contact with eyes.

Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.

Recommended storage temperature : 50 - 109 °F / 10 - 43 °C

Further information on storage stability : PROTECT FROM FREEZING.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|---------|-------------------------------|--|-------|
|            |         |                               |  |       |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

Version 2.0      Revision Date: 06/11/2024      SDS Number: 000000267665      Date of last issue: 01/08/2021  
Date of first issue: 06/11/2020

|               |            |                                     |                                     |           |
|---------------|------------|-------------------------------------|-------------------------------------|-----------|
| Asphalt       | 8052-42-4  | TWA (Fume, inhalable fraction)      | 0.5 mg/m3 (benzene soluble aerosol) | ACGIH     |
|               |            | C (Fumes)                           | 5 mg/m3                             | NIOSH REL |
| Quartz (SiO2) | 14808-60-7 | TWA (Respirable dust)               | 0.05 mg/m3                          | OSHA Z-1  |
|               |            | TWA (respirable)                    | 10 mg/m3 / %SiO2+2                  | OSHA Z-3  |
|               |            | TWA (respirable)                    | 250 mppcf / %SiO2+5                 | OSHA Z-3  |
|               |            | TWA (respirable dust fraction)      | 0.1 mg/m3                           | OSHA P0   |
|               |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica)                | ACGIH     |
|               |            | TWA (Respirable dust)               | 0.05 mg/m3 (Silica)                 | NIOSH REL |
|               |            | PEL (respirable)                    | 0.05 mg/m3                          | OSHA CARC |

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

**Respiratory protection** : Wear appropriate certified respirator when exposure limits may be exceeded.  
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Safety glasses with side-shields.

**Skin and body protection** : light protective clothing

**Protective measures** : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

**Hygiene measures** : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Remove contaminated clothing immediately and clean before

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/08/2021  |
| 2.0     | 06/11/2024     | 000000267665 | Date of first issue: 06/11/2020 |

re-use or dispose it if necessary.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |   |   |
|--|---|---|
| Appearance                                       | : | viscous liquid                          |
| Color  | : | brown                                   |
| Odor   | : | mild, of petroleum                      |
| Odor Threshold                                   | : | not determined                          |
| pH   | : | 5 - 7                                   |
| Melting point/freezing point                     | : | 32 °F / 0 °C                            |
| Boiling point/boiling range                      | : | 212 °F / 100 °C                         |
| Flash point                                      | : | > 212 °F / > 100 °C                     |
| Evaporation rate                                 | : | No data available                       |
| Flammability (liquids)                           | : | Not classified as a flammability hazard |
| Upper explosion limit / Upper flammability limit | : | No data available                       |
| Lower explosion limit / Lower flammability limit | : | No data available                       |
| Vapor pressure                                   | : | approx. 60 mmHg (212 °F / 100 °C)       |
| Relative vapor density                           | : | No data available                       |
| Relative density                                 | : | 1.03                                    |
| Density  | : | 8.6 lb/gal                              |
| Solubility(ies)                                  | : |   |
| Water solubility                                 | : | slightly soluble                        |
| Solubility in other solvents                     | : | No data available                       |
| Partition coefficient: n-octanol/water           | : | No data available                       |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/08/2021  |
| 2.0     | 06/11/2024     | 000000267665 | Date of first issue: 06/11/2020 |

---

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : Avoid extreme heat.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Sulfur oxides  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Hydrocarbons

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Skin corrosion/irritation

Not classified due to lack of data.

#### Serious eye damage/eye irritation

Not classified due to lack of data.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

Version 2.0      Revision Date: 06/11/2024      SDS Number: 000000267665      Date of last issue: 01/08/2021  
Date of first issue: 06/11/2020

---

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

May cause cancer by inhalation.

|             |  |            |
|-------------|--|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans  |            |
|             | Quartz (SiO <sub>2</sub> )<br>(Silica dust, crystalline)   | 14808-60-7 |
|             | Group 2B: Possibly carcinogenic to humans  |            |
|             | Asphalt<br>(Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving) | 8052-42-4  |
| <b>OSHA</b> | OSHA specifically regulated carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(crystalline silica)                 | 14808-60-7 |
| <b>NTP</b>  | Known to be human carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(Silica, Crystalline (Respirable Size))        | 14808-60-7 |

#### Reproductive toxicity

Not classified due to lack of data.

#### STOT-single exposure

Not classified due to lack of data.

#### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

#### Aspiration toxicity

Not classified due to lack of data.

#### Further information

#### Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/08/2021  |
| 2.0     | 06/11/2024     | 000000267665 | Date of first issue: 06/11/2020 |

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615


Version  
2.0

Revision Date:  
06/11/2024


SDS Number:  
000000267665

Date of last issue: 01/08/2021  
Date of first issue: 06/11/2020

### NFPA 704:



### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

|                 |   |   |
|-----------------|---|---|
| ACGIH           | : | USA. ACGIH Threshold Limit Values (TLV)   |
| NIOSH REL       | : | USA. NIOSH Recommended Exposure Limits  |
| OSHA CARC       | : | OSHA Specifically Regulated Chemicals/Carcinogens   |
| OSHA P0         | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)                        |
| OSHA Z-1        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants          |
| OSHA Z-3        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts                        |
| ACGIH / TWA     | : | 8-hour, time-weighted average   |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / C   | : | Ceiling value not be exceeded at any time.  |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL)  |
| OSHA P0 / TWA   | : | 8-hour time weighted average  |
| OSHA Z-1 / TWA  | : | 8-hour time weighted average  |
| OSHA Z-3 / TWA  | : | 8-hour time weighted average  |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Indus-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Sikalastic-315 Formerly MSeal 615

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/08/2021  |
| 2.0     | 06/11/2024     | 000000267665 | Date of first issue: 06/11/2020 |

---

trial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/11/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN