



**Gold Bond® High Strength Fire-Shield
60® Gypsum Board**
Gold Bond Building Products, LLC
provided by National Gypsum Company

Final Assembly: Multiple US Locations
Life Expectancy: 60+ Year(s)
End of Life Options: Recyclable (100%), Landfill

Ingredients:

Gypsum Core: Gypsum; Vermiculite; STARCH; Continuous Filament Glass Fiber, Non-Respirable; Dextrose; **Sodium polynaphthalenesulfonate**¹; Boric acid; Polignate Sodium; Metaphosphoric acid (H3P3O9), trisodium salt; Undisclosed (< 0.06%)²; Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C9-11-alkyl ethers, sodium salts; POTASSIUM SULFATE; Glycerine; Sodium bisulfate; **Paper Facing:** Mixed Recycled Paper; Starch; Alkenyl succinic anhydride

¹LBC Temp Exception RL-009 - Formaldehyde

²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 99.94% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

NGC-0002
EXP. 01 MAR 2024
Original Issue Date: 2023