PermaBASE[™] Cement Board Screws

Technical Information 800.NATIONAL • 800.628.4662

DESCRIPTION

 $\label{eq:permabase} \mbox{PermaBASE}^{\text{\tiny{TM}}}\mbox{ Cement Board Screws are corrosion-resistant screws specifically designed to be used with PermaBASE}^{\mbox{\tiny{SC}}}\mbox{ Cement Boards.}$

BASIC USES

Applications

Used to attach PermaBASE Cement Board and other approved tile backers to wood or steel studs, plywood subfloors, ceilings and countertops.

Advantages

- Self-drilling and self-tapping versions available.
- · Used for interior and exterior applications.
- Large diameter, low profile wafer-type head for more secure attachment.
- · Durable, corrosion-resistant coating.
- · No ribs under head, preventing reinforcing mesh damage.
- · Packaged in convenient jars and pails for jobsite durability.
- Available in 1-1/4", 2" and 2-1/2" lengths for optimal framing penetration.

INSTALLATION

- Drive screws to where screw-heads are flush with the panel surface. Do not countersink or overdrive screws.
- Screw must be driven straight for proper performance.
- Install screws 3/8" to 5/8" from edges of panels.
- Recommended screw spacing is 8" o.c. for walls, floors and countertops, and 6" o.c. for ceilings.
- Metal screws are designed to attach cement board to steel studs of 20 to 12 gauge.

TECHNICAL DATA

Property	Standard	Result
Coating type	N/A	Zinc plated with chemical coating
Recess	N/A	Philips #2
Thread/point (wood)	N/A	#10-16 / Hi-Lo
Thread/point (metal)	N/A	#8-18 / #10-18 / Type S-12
Head Diameter	N/A	0.45" (11.4 mm)
Salt Spray Resistance	ASTM B117 (0% rust)	1,000 hrs

Available Sizes			
Size	Length	Thread/Point	Quantities
Wood Screws			
#10-16	1-1/4"	Hi-Lo	1,000/Jar
#10-16	2"	Hi-Lo	2,000/Pail
#10-16	2-1/2"	Hi-Lo	2,000/Pail
Metal Screws			
#8-18	1-1/4"	Drill Point	1,000/Jar
#8-18	2"	Drill Point	2,000/Pail
#10-16	2-1/2"	Drill Point	1,500/Pail

Estimated Screw Requirements				
Application	Screws per Board	Screws per Sq. Ft.		
Wall	52	1.625		
Ceiling	63	2		
Wall	36	2.4		
Floor	60	4		
	Application Wall Ceiling Wall	Application Screws per Board Wall 52 Ceiling 63 Wall 36		

Job Name	
Contractor	Date Submittal Approvals: (Stamps or Signatures)

PermaBASECement Board Screws

FOR MORE INFORMATION

Architectural Specifications

PermaBASE Building Products CSI MasterFormat® 3-part guide specifications are downloadable as editable Microsoft® Word documents at: permabase.com.

Latest Technical Information and Update

Visit **permabase.com** or call National Gypsum Company Construction Services: 1-800-NATIONAL (628-4662).



National Gypsum Company is the exclusive service provider for products offered or manufactured by PermaBASE Building Products, LLC.

PermaBASE Cement Board Screws are offered by PermaBASE Building Products, LLC to be used with PermaBASE® Cement Boards.



National Gypsum Company is the exclusive service provider for products offered or manufactured by PermaBASE Building Products, LLC.



PermaBASE Building Products, LLC 2001 Rexford Road Charlotte, NC 28211 704.365.7300 permabase.com