







# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



Conforms to ANSI Z400.1-2010 Standard - HCS 2012

Protective Clothing	General Hazard	DOT
Consult your supervisor or S.O.P. for special handling	   	 

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : NEOGARD ALIPHATIC URETHANE TOPCOAT GRAY  
Product identity : 47LJB16650, 7470-002  
Product type : polyurethane paint

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings and metal industry.  
Identified uses : Industrial/Professional use  
TSCA : **Unless otherwise stated. All components are listed or exempted.**

### 1.3 Details of the supplier of the safety data sheet

Company details : NEOGARD, a Division of Hempel (USA), Inc.  
2728 Empire Central  
Dallas, TX 75235  
Phone number: 1-214-353-1600  
E-mail: [hempel@hempel.com](mailto:hempel@hempel.com)

### 1.4 Emergency telephone number (with hours of operation)

For Transportation Emergencies : CHEMTREC: **1-800-424-9300** (Toll-free in the U.S., Canada and the U.S. Virgin Islands) **703-527-3887** (24 hours)  
For calls originating elsewhere (Collect calls are accepted). Contract number: CCN10384  
To preserve the effectiveness of arrangements for providing accurate and timely emergency response information, the basic identifying information (shipper name or contract number) must be included on shipping papers.  
If the purchaser of this product is going to be shipping this product to other locations, the purchaser must arrange for its own Emergency Information Provider to respond to transport incidents. Hempel's 24 hour response contract does not cover non-Hempel shipments.  
For all other information : In USA toll free calling available: 1-800- 678-6641 or (936)-523-6000  
(8 AM - 5 PM CST) See Section 4 of the safety data sheet (first aid measures).

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
GHS Classification : FLAMMABLE LIQUIDS - Category 3  
ACUTE TOXICITY (inhalation) - Category 4  
SKIN IRRITATION - Category 2  
SERIOUS EYE DAMAGE - Category 1  
RESPIRATORY SENSITIZATION - Category 1  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1A  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

### 2.2 Label elements

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY

## SECTION 2: Hazards identification

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H226 - Flammable liquid and vapor.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H332 - Harmful if inhaled.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H350 - May cause cancer.  
H361 - Suspected of damaging fertility or the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure. (lungs)

Precautionary statements :

Prevention :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wear respiratory protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor, mist or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response :

IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage :

Store locked up. Store in a well-ventilated place. Keep cool.

Disposal :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements :

None known.

### 2.3 Other hazards

Hazards not otherwise classified : None known.

## SECTION 3: Composition/information on ingredients

Product definition :

Mixture

Physical state :

Liquid.

Product/ingredient name	Identifiers	%	GHS Classification
Solvent naphtha (petroleum), light arom.	64742-95-6	≥5 - ≤10	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	140921-24-0	≥5 - ≤10	SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1
titanium dioxide	13463-67-7	≥5 - ≤10	Not classified.
quartz (chrystalline, non respirable)	14808-60-7	≥5 - ≤10	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
1,2,4-trimethylbenzene	95-63-6	≥3 - ≤5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

**SECTION 3: Composition/information on ingredients**

respirable quartz	14808-60-7	≥3 - ≤5	(Respiratory tract irritation) - Category 3 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
3-isocyanatomethyl- 3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	≥1 - ≤3	ACUTE TOXICITY (inhalation) - Category 1 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
bis(2-ethylhexyl) terephthalate	6422-86-2	≥1 - ≤3	EYE IRRITATION - Category 2B
1,2,3-trimethylbenzene	526-73-8	≥1 - ≤3	FLAMMABLE LIQUIDS - Category 3
xylene	1330-20-7	≥1 - ≤3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4
Isocyanurate of isophorone diisocyanate	53880-05-0	<1	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	≤1	SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
1,2,3,6-tetrahydromethyl- 3,6-methanophthalic anhydride	25134-21-8	<1	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 3 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1
cumene	98-82-8	≤0.3	FLAMMABLE LIQUIDS - Category 3 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
ethylbenzene	100-41-4	≤0.3	ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
methyl-1,2,2,6,6-pentamethyl- 4-piperidylsebacate	82919-37-7	≤0.3	ASPIRATION HAZARD - Category 1 SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
fatty acids, C14-18 and C16-18-unsatd., maleated		≤0.3	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
maleic anhydride	108-31-6	<0.1	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1


Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).
Eye contact :	 Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

#### SECTION 4: First aid measures

Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact :	Causes serious eye damage.
Inhalation :	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact :	May cause an allergic skin reaction.
Ingestion :	No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

Eye contact :	Adverse symptoms may include the following: pain watering redness
Inhalation :	Adverse symptoms may include the following: wheezing and breathing difficulties asthma
Skin contact :	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion :	Adverse symptoms may include the following: stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed.
Specific treatments :	No specific treatment.

#### SECTION 5: Firefighting measures

##### 5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray. Not to be used: waterjet.
-----------------------	---

##### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

##### 5.3 Advice for firefighters

## SECTION 5: Firefighting measures

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.2 Environmental precautions

**A**void dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Contains isocyanates. Exposure to isocyanate may result in acute irritation and/or sensitisation when breathing.

**Care should be taken when re-opening partly-used containers.**

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

### 7.2 Conditions for safe storage, including any incompatibilities

**S**ore in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids as well as of amines, alcohols and water. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.  
This product may be applied using several application techniques and methods of handling may be different for each. Application techniques include [but are not limited to] brushing, rolling, and spray application [conventional, HPLV, airless, pleural component or aerosol can]. Avoid the breathing of vapors and, if spraying, do not breath spray mist or aerosols.

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY

#### SECTION 8: Exposure controls/personal protection

##### 8.1 Control parameters

Product/ingredient name	Exposure limit values
<p>Solvent naphtha (petroleum), light arom.</p> <p>titanium dioxide</p> <p>quartz (chrySTALLINE, non respirable)</p> <p>1,2,4-trimethylbenzene</p> <p>respirable quartz</p> <p>3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate</p> <p>1,2,3-trimethylbenzene</p> <p>xylene</p> <p>cumene</p> <p>ethylbenzene</p>	<p><b>ACGIH TLV (United States).</b> TWA Tentative: 25 ppm 8 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b> TWA: 15 mg/m<sup>3</sup> 8 hours. Form: Total dust</p> <p><b>ACGIH TLV (United States, 1/2023).</b> TWA: 2.5 mg/m<sup>3</sup> 8 hours. Form: respirable fraction, finescale particles</p> <p><b>OSHA PEL Z3 (United States, 6/2016).</b> TWA: 250 mppcf / (%SiO<sub>2</sub>+5) 8 hours. Form: Respirable TWA: 10 mg/m<sup>3</sup> / (%SiO<sub>2</sub>+2) 8 hours. Form: Respirable</p> <p><b>OSHA PEL (United States, 5/2018). [Silica, crystalline]</b> TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust</p> <p><b>ACGIH TLV (United States, 1/2023). [Silica, crystalline]</b> TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p> <p><b>NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE]</b> TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</p> <p><b>NIOSH REL (United States, 10/2020).</b> TWA: 125 mg/m<sup>3</sup> 10 hours. TWA: 25 ppm 10 hours.</p> <p><b>ACGIH TLV (United States, 1/2022).</b> TWA: 10 ppm 8 hours.</p> <p><b>OSHA PEL Z3 (United States, 6/2016).</b> TWA: 250 mppcf / (%SiO<sub>2</sub>+5) 8 hours. Form: Respirable TWA: 10 mg/m<sup>3</sup> / (%SiO<sub>2</sub>+2) 8 hours. Form: Respirable</p> <p><b>OSHA PEL (United States, 5/2018). [Silica, crystalline]</b> TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust</p> <p><b>ACGIH TLV (United States, 1/2023). [Silica, crystalline]</b> TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p> <p><b>NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE]</b> TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</p> <p><b>ACGIH TLV (United States, 1/2023).</b> TWA: 0.005 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020). Absorbed through skin.</b> STEL: 0.18 mg/m<sup>3</sup> 15 minutes. STEL: 0.02 ppm 15 minutes. TWA: 0.045 mg/m<sup>3</sup> 10 hours. TWA: 0.005 ppm 10 hours.</p> <p><b>ACGIH TLV (United States, 1/2022). [trimethyl benzene, isomers]</b> TWA: 123 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b> TWA: 125 mg/m<sup>3</sup> 10 hours. TWA: 25 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018). [Xylenes]</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2023). [p-xylene and mixtures containing p-xylene] Ototoxicant.</b> TWA: 20 ppm 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2023).</b> TWA: 5 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020). Absorbed through skin.</b> TWA: 245 mg/m<sup>3</sup> 10 hours. TWA: 50 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018). Absorbed through skin.</b> TWA: 245 mg/m<sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2023). Ototoxicant.</b> TWA: 20 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b> STEL: 545 mg/m<sup>3</sup> 15 minutes. STEL: 125 ppm 15 minutes. TWA: 435 mg/m<sup>3</sup> 10 hours. TWA: 100 ppm 10 hours.</p>



**SECTION 8: Exposure controls/personal protection**

maleic anhydride	<p><b>OSHA PEL (United States, 5/2018).</b>  TWA: 435 mg/m<sup>3</sup> 8 hours.  TWA: 100 ppm 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2023). Skin sensitizer. Inhalation sensitizer.</b>  TWA: 0.01 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction and vapor</p> <p><b>NIOSH REL (United States, 10/2020).</b>  TWA: 1 mg/m<sup>3</sup> 10 hours.  TWA: 0.25 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b>  TWA: 1 mg/m<sup>3</sup> 8 hours.  TWA: 0.25 ppm 8 hours.</p>
------------------	---

**Recommended monitoring procedures**

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**8.2 Exposure controls**

**Appropriate engineering controls**

Provide local exhaust and general ventilation systems to maintain airborne concentrations below OSHA, ACGIH, and manufacturer recommended exposure limits. Local exhaust ventilation is preferred because it prevents contaminant dispersion into work areas by controlling it at its source. Use local and general exhaust ventilation to effectively remove and prevent buildup of mists/vapors/fumes generated from the handling of this product.

Note: Local exhaust ventilation is designed to capture an emitted contaminant at or near its source, before the contaminant has a chance to disperse into the workplace air. General exhaust ventilation, also called dilution ventilation, is different from local exhaust ventilation because instead of capturing emissions at their source and removing them from the air, general exhaust ventilation allows the contaminant to be emitted into the workplace air and then dilutes the concentration of the contaminant to an acceptable level (e.g., to the PEL or below).

**Individual protection measures**

- General : Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.
- Hygiene measures : Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Hand protection : Wear chemical-resistant gloves in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.  
Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:  
May be used: nitrile rubber  
Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®  
Short term exposure: neoprene rubber, butyl rubber, natural rubber (latex), polyvinyl chloride (PVC)
- Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.  
Wear suitable protective clothing. Always wear protective clothing when spraying.
- Respiratory protection : If working areas have insufficient ventilation, wear half or totally covering mask equipped with gas filter of type Organic Vapor, when grinding use particle filter of type P95, P99 or P100. When spraying use a combined filter (organic vapor / HEPA or organic vapor / P100 type). Be sure to use approved/certified respirator or equivalent. Always wear an air-fed respirator when spraying in a continuous and prolonged work situation (e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter).

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



#### SECTION 8: Exposure controls/personal protection

Protective clothing (pictograms) :

**Consult your supervisor or S.O.P. for special handling**

Note: Application of paint products by spraying requires additional safety precautions: Full body suit, Full face respirator with air supplied.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### SECTION 9: Physical and chemical properties

##### 9.1 Information on basic physical and chemical properties

Physical state :	Liquid.
Color :	Gray
Odor :	Solvent-like
pH :	Testing not relevant or not possible due to nature of the product.
Melting point/freezing point :	Testing not relevant or not possible due to nature of the product.
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.
Flash point :	Closed cup: 54°C (129.2°F)
Evaporation rate :	Testing not relevant or not possible due to nature of the product.
Flammability :	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. Flammable in the presence of the following materials or conditions: oxidizing materials. Slightly flammable in the presence of the following materials or conditions: reducing materials.
Upper/lower flammability or explosive limits :	0.6 - 10.7 vol %
Vapor pressure :	Testing not relevant or not possible due to nature of the product.
Vapor density :	Testing not relevant or not possible due to nature of the product.
Relative density :	1.13 g/cm <sup>3</sup>
Partition coefficient (LogKow) :	Testing not relevant or not possible due to nature of the product.
Auto-ignition temperature :	Testing not relevant or not possible due to nature of the product.
Decomposition temperature :	Testing not relevant or not possible due to nature of the product.
Viscosity :	Testing not relevant or not possible due to nature of the product.
Explosive properties :	Not available.
Oxidizing properties :	Testing not relevant or not possible due to nature of the product.

##### 9.2 Other information

Solvent(s) % by weight (Included exempt solvent(s)):	17.8 % (w/w)
Water % by weight :	Weighted average: 0 %
VOC content (Coatings) :	1.68 lbs/gal (200.7 g/l)
VOC content (Regulatory) :	1.68 lbs/gal (200.8 g/l)
TOC Content (Volatile) :	Weighted average: 142 g/l
Solvent Gas :	Weighted average: 0.041 m <sup>3</sup> /l



# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

The product is stable.

### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

### 10.5 Incompatible materials

Highly reactive or incompatible with the following materials: oxidizing materials.  
Slightly reactive or incompatible with the following materials: reducing materials.

### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Isocyanate containing products have characteristics that include producing acute irritation and/or sensitisation when breathing, subsequent asthmatic problems and lung contractions. Sensitised people can, as a result from this, show asthmatic symptoms with exposure to atmospheric concentrations far below the TLV. Repeated exposures will lead to permanent damage to the respiratory system.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), light arom.	LC50 Inhalation Vapor	Rat	6193 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	3160 mg/kg	-
titanium dioxide	LD50 Oral	Rat	3492 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>6.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
1,2,4-trimethylbenzene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	18000 mg/m <sup>3</sup>	4 hours
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	LD50 Oral	Rat	5 g/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0.03 mg/l	4 hours
	LD50 Oral	Rat	4825 mg/kg	-
xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	6350 ppm	4 hours
	LD50 Dermal	Rabbit	>4200 mg/kg	-
	LD50 Oral	Rat	3523 mg/kg	-
Isocyanurate of isophorone diisocyanate	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Oral	Rat	>20000 mg/kg	-
bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
1,2,3,6-tetrahydromethyl-	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rat	4920 mg/kg	-

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY

#### SECTION 11: Toxicological information

3,6-methanophthalic anhydride	LD50 Oral	Rat	914 mg/kg	-
cumene	LC50 Inhalation Vapor	Rat	39000 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
ethylbenzene	LD50 Oral	Rat	1400 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
maleic anhydride	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Dermal	Rabbit	2620 mg/kg	-
	LD50 Oral	Rat	1090 mg/kg	-

#### Acute toxicity estimates

Route	ATE value
Dermal	106017.74 mg/kg
Inhalation (gases)	79146.83 ppm
Inhalation (vapors)	279.08 mg/l
Inhalation (dusts and mists)	1.35 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure
Solvent naphtha (petroleum), light arom.	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters
	Respiratory - Mild irritant	Rabbit	-	-
titanium dioxide	Skin - Moderate irritant	Rabbit	-	-
	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent
bis(2-ethylhexyl) terephthalate	Skin - Mild irritant	Human	-	504 hours 0.5 Percent Intermittent
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams
xylene	Skin - Irritant	Rabbit	-	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams
Isocyanurate of isophorone diisocyanate	Eyes - Mild irritant	Rabbit	-	-
	Skin - Irritant	Rat	-	-
1,2,3,6-tetrahydromethyl-3,6-methanophthalic anhydride	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams
cumene	Eyes - Mild irritant	Rabbit	-	-
	Respiratory - Mild irritant	Rabbit	-	-
ethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams
	Eyes - Severe irritant	Rabbit	-	1 Percent
maleic anhydride	Skin - Severe irritant	Rabbit	-	-
		Rabbit	-	-

#### Sensitizer

Product/ingredient name	Route of exposure	Species	Result
Isocyanurate of isophorone diisocyanate	skin	Guinea pig	Sensitizing
bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	skin	Guinea pig	Sensitizing

#### Carcinogen Classification

Product/ingredient name	IARC	NTP	OSHA
titanium dioxide	2B	-	-
	1	Known to be a human carcinogen.	+
quartz (chrystalline, non respirable)	1	Known to be a human carcinogen.	+
respirable quartz	1	Known to be a human carcinogen.	+
xylene	3	-	-
cumene	2B	Reasonably anticipated to be a human carcinogen.	-
ethylbenzene	2B	-	-

#### Specific target organ toxicity (single exposure)

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



#### SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3		Respiratory tract irritation
1,2,4-trimethylbenzene	Category 3 Category 3		Narcotic effects Respiratory tract irritation
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Category 3		Respiratory tract irritation
Isocyanurate of isophorone diisocyanate	Category 3		Respiratory tract irritation
cumene	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
quartz (chrySTALLINE, non respirable)	Category 1	inhalation	lungs
respirable quartz	Category 1	inhalation	lungs
ethylbenzene	Category 2	-	hearing organs
maleic anhydride	Category 1	inhalation	respiratory system

#### Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), light arom. cumene ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

#### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

Sensitization : Contains 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, Isocyanurate of isophorone diisocyanate, 1,2,3,6-tetrahydromethyl-3,6-methanophthalic anhydride, (R)-p-mentha-1,8-diene. May produce an allergic reaction.

Other information : No additional known significant effects or critical hazards.

#### SECTION 12: Ecological information

##### 12.1 Toxicity

Do not allow to enter drains or watercourses. Toxic to aquatic life with long lasting effects.

When spilled, this product may act as an oil, causing a film, sheen, emulsion, or sludge at or beneath the surface of a body of water. Oils of any kind can cause: (a) drowning of waterfowl due to lack of buoyancy, loss of insulating capacity of feathers, starvation and vulnerability to predators due to lack of mobility; (b) lethal effect on fish by coating gill surfaces, preventing respiration; (c) potential fish kills resulting from alteration in biochemical oxygen demand; (d) asphyxiation of benthic life forms when floating masses become engaged with surface debris and settle on the bottom; and (e) adverse aesthetic effects of fouled shoreline and beaches.

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Acute EC50 2.6 mg/l	Algae - Pseudokirchneriella subcapitata (green algae)	96 hours
	Acute EC50 3.2 mg/l	Daphnia	48 hours
	Acute LC50 9.22 mg/l	Fish - Oncorhynchus mykiss (rainbow trout)	96 hours
titanium dioxide	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
1,2,4-trimethylbenzene	Acute LC50 4910 µg/l Marine water	Crustaceans - Elasmopus pectinicus - Adult	48 hours
		Fish - Pimephales promelas	96 hours
bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Acute LC50 7720 µg/l Fresh water Acute EC50 1.68 mg/l	Aquatic plants	72 hours
		Fish - Lepomis macrochirus	96 hours
cumene	Acute EC50 2.6 mg/l Acute EC50 7400 - 11290 µg/l Fresh water Acute EC50 1 - 10 mg/l Acute LC50 2700 µg/l Fresh water Acute NOEC 0.35 mg/l	Algae	72 hours
		Crustaceans - Artemia sp. - Nauplii	48 hours
		Daphnia	48 hours
		Fish - Oncorhynchus mykiss	96 hours
		Algae	21 days

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY

#### SECTION 12: Ecological information

ethylbenzene	Chronic NOEC <1000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
--------------	-------------------------------------	---	----------

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Solvent naphtha (petroleum), light arom.	OECD 301F Ready Biodegradability - Manometric Respirometry Test	78 % - Readily - 28 days	-	-
	-	>70 % - Readily - 28 days	-	-
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate bis(2-ethylhexyl) terephthalate	OECD	>60 % - Readily - 28 days	-	-
	-	0 % - Not readily - 28 days	-	-
xylene	301B Ready Biodegradability - CO <sub>2</sub> Evolution Test	73.05 % - Readily - 28 days	-	-
	OECD 301F Ready Biodegradability - Manometric Respirometry Test	90 - 98 % - Readily - 28 days	-	-
Isocyanurate of isophorone diisocyanate	-	>60 % - Readily - 28 days	-	-
	OECD 301F Ready Biodegradability - Manometric Respirometry Test	0 % - Not readily - 28 days	-	-
ethylbenzene	-	>70 % - Readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Solvent naphtha (petroleum), light arom.	-	-	Readily
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate bis(2-ethylhexyl) terephthalate	-	-	Not readily
xylene	-	-	Readily
Isocyanurate of isophorone diisocyanate	-	-	Readily
ethylbenzene	-	-	Not readily
			Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Solvent naphtha (petroleum), light arom.	-	10 - 2500	high
1,2,4-trimethylbenzene	3.63	243	low
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate bis(2-ethylhexyl) terephthalate	0.99	-	low
1,2,3-trimethylbenzene	8.39	393	low
xylene	3.66	194.98	low
1,2,3,6-tetrahydromethyl-3,6-methanophthalic anhydride	3.12	8.1 - 25.9	low
cumene	-	3.9 - 5.5	low
ethylbenzene	3.55	35.48	low
maleic anhydride	3.6	-	low
	-2.78	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>): No known data available in our database.

Mobility:

No known data available in our database.

#### 12.5 Other adverse effects

No known significant effects or critical hazards.

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7 and Section 8 for additional handling information and protection of employees.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

Transport may take place according to national regulation or DOT for transport by road and by train, IMDG for transport by sea, IATA for Air shipment. Refer to specific Dangerous Goods Transport requirements under 49CFR, ICAO and IATA.

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	14.5 Additional information
<b>DOT Code</b>	UN1263	PAINT. (Solvent naphtha (petroleum), light arom.)	3 -		III	Yes.  The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes.  <b>Reportable quantity</b> (xylene) 36.23 lbs / 4373.1 kg [1023.2 gal / 3873.4 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
<b>TDG Code</b>	UN1263	PAINT. (Solvent naphtha (petroleum), light arom.)	3 -		III	Yes. Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.
<b>SCT Code</b>	UN1263	PAINT	3 -		III	Yes. -
<b>IMDG Code</b>	UN1263	PAINT. (Solvent naphtha (petroleum), light arom.)	3 -		III	Yes. The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-E, S-E
<b>IATA Code</b>	UN1263	PAINT	3 -		III	Yes. The environmentally hazardous substance mark may appear if required by other transportation regulations.

Code : Classification  
PG\* : Packing group  
Env.\* : Environmental hazards

### 14.6 Special precautions for user

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



#### SECTION 14: Transport information

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

Not applicable.

#### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : Not determined.

**TSCA 8(a) PAIR:** 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; silica/polydimethylsiloxane reaction product; methyl formate; octamethylcyclotetrasiloxane (D4); naphthalene

**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined

**United States inventory (TSCA 8b):** Not determined.

**TSCA 8(c) calls for record of SAR:** 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

**Clean Water Act (CWA) 307:** ethylbenzene; toluene; benzene; bis(2-ethylhexyl) phthalate; naphthalene; hexachlorobenzene

**Clean Water Act (CWA) 311:** xylene; n-butyl acetate; ethylbenzene; phosphoric acid; toluene; benzene; maleic anhydride; naphthalene

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) :** Listed

Product/ingredient name	CAS number	Concentration
2-(2-butoxyethoxy)ethyl acetate	124-17-4	1.0766
xylene	1330-20-7	1.0382
cumene	98-82-8	0.22458
ethylbenzene	100-41-4	0.1858
toluene	108-88-3	0.029706
benzene	71-43-2	0.0075681
2-(2-butoxyethoxy)ethanol	112-34-5	0.0030825
bis(2-ethylhexyl) phthalate	117-81-7	0.0018068
methanol	67-56-1	0.001542
maleic anhydride	108-31-6	0.0010679
hexachlorobenzene	118-74-1	<0.001

**Clean Air Act Section 602 Class I Substances :** Not listed

**Clean Air Act Section 602 Class II Substances :** Not listed

**DEA List I Chemicals (Precursor Chemicals) :** Not listed

**DEA List II Chemicals (Essential Chemicals) :** Not listed

**SARA 302/304 :**

Product/ingredient name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	≥1 - ≤3	Yes.	500	56.7	500	56.7

**SARA 304 RQ :**

22450.5 lbs / 10192.5 kg [2384.9 gal / 9027.9 L]

**SARA 311/312 Classification :**

FLAMMABLE LIQUIDS - Category 3  
 ACUTE TOXICITY (inhalation) - Category 4  
 SKIN IRRITATION - Category 2  
 SERIOUS EYE DAMAGE - Category 1  
 RESPIRATORY SENSITIZATION - Category 1  
 SKIN SENSITIZATION - Category 1  
 CARCINOGENICITY - Category 1A  
 TOXIC TO REPRODUCTION - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Product/ingredient name	%	Classification
Solvent naphtha (petroleum), light arom.	≥5 - ≤10	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	≥5 - ≤10	SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1
quartz (chrystalline, non respirable)	≥5 - ≤10	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
1,2,4-trimethylbenzene	≥3 - ≤5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2



# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



#### SECTION 15: Regulatory information

respirable quartz	≥3 - ≤5	EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	≥1 - ≤3	ACUTE TOXICITY (inhalation) - Category 1 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
bis(2-ethylhexyl) terephthalate	≥1 - ≤3	EYE IRRITATION - Category 2B
1,2,3-trimethylbenzene	≥1 - ≤3	FLAMMABLE LIQUIDS - Category 3
xylene	≥1 - ≤3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2
Isocyanurate of isophorone diisocyanate	<1	SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤1	SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
1,2,3,6-tetrahydromethyl-3,6-methanophthalic anhydride	<1	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 3 SKIN IRRITATION - Category 2
cumene	≤0.3	SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 FLAMMABLE LIQUIDS - Category 3 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
ethylbenzene	≤0.3	ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate	≤0.3	ASPIRATION HAZARD - Category 1 SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
fatty acids, C14-18 and C16-18-unsatd., maleated	≤0.3	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
maleic anhydride	<0.1	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

#### SARA 313 :

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### Form R - Reporting requirements :

Product/ingredient name	CAS number	Concentration
1,2,4-trimethylbenzene	95-63-6	3 - 5
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	1 - 3
2-(2-butoxyethoxy)ethyl acetate	124-17-4	1 - 3
xylene	1330-20-7	1 - 3
ethylbenzene	100-41-4	0 - 1
hexachlorobenzene	118-74-1	0 - 1

#### Supplier notification :

Product/ingredient name	CAS number	Concentration
1,2,4-trimethylbenzene	95-63-6	3 - 5
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	1 - 3
2-(2-butoxyethoxy)ethyl acetate	124-17-4	1 - 3
xylene	1330-20-7	1 - 3
ethylbenzene	100-41-4	0 - 1
hexachlorobenzene	118-74-1	0 - 1

#### State regulations :

**Connecticut Carcinogen Reporting:** None of the components are listed.

**Connecticut Hazardous Material Survey:** None of the components are listed.

**Florida substances:** None of the components are listed.

**Illinois Chemical Safety Act:** None of the components are listed.

**Illinois Toxic Substances Disclosure to Employee Act:** None of the components are listed.

**Louisiana Reporting:** None of the components are listed.

**Louisiana Spill:** None of the components are listed.

**Massachusetts Substances:** The following components are listed: TITANIUM DIOXIDE; SILICA, CRYSTALLINE, QUARTZ; PSEUDOCUMENE; SILICA, CRYSTALLINE, QUARTZ; ISOPHORONE DIISOCYANATE; TRIMETHYL BENZENE; XYLENE

**Massachusetts Spill:** None of the components are listed.

**Michigan Critical Material:** None of the components are listed.

**SECTION 15: Regulatory information**

**Minnesota Hazardous Substances:** None of the components are listed.  
**New Jersey Spill:** None of the components are listed.  
**New Jersey Toxic Catastrophe Prevention Act:** None of the components are listed.  
**New Jersey Hazardous Substances:** The following components are listed: TITANIUM DIOXIDE; SILICA, QUARTZ; PSEUDOCUMENE; SILICA, QUARTZ; ISOPHORONE DIISOCYANATE; TRIMETHYL BENZENE (mixed isomers); GLYCOL ETHERS; XYLENES; ETHYL BENZENE  
**New York Hazardous Substances:** The following components are listed: Isophorone diisocyanate; Xylene mixed  
**New York Toxic Chemical Release Reporting:** None of the components are listed.  
**Pennsylvania RTK Hazardous Substances:** The following components are listed: TITANIUM OXIDE; QUARTZ DUST; PSEUDOCUMENE; QUARTZ DUST; CYCLOHEXANE, 5-ISOCYANATO-1-(ISOCYANATOMETHYL)-1,3,3-TRIMETHYL-; BENZENE, DIMETHYL-  
**Rhode Island Hazardous Substances:** None of the components are listed.

**California Prop. 65 PFF :**

**WARNING:** This product can expose you to chemicals including Benzene, Di(2-ethylhexyl)phthalate and Hexachlorobenzene, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, Silica, crystalline, Silica, crystalline, cumene, Ethylbenzene and Naphthalene, which are known to the State of California to cause cancer, and 1-ethyl-2-methylbenzene, Toluene and Methanol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Product/ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
titanium dioxide	Yes.	No.		
quartz (chrySTALLINE, non respirable)	Yes.	No.		
respirable quartz	Yes.	No.		
1-ethyl-2-methylbenzene	No.	Yes.		
cumene	Yes.	No.		
ethylbenzene	Yes.	No.	Yes.	
toluene	No.	Yes.		Yes.
benzene	Yes.	Yes.	Yes.	Yes.
bis(2-ethylhexyl) phthalate	Yes.	Yes.	Yes.	Yes.
methanol	No.	Yes.		Yes.
naphthalene	Yes.	No.	Yes.	
hexachlorobenzene	Yes.	Yes.	Yes.	

**SECTION 16: Other information**

**Remarks :** Note: In USA, consult Code of Federal Regulations, Title 29, Labor, Parts 1910 and 1915 concerning occupational safety and health standards and regulations, as well as any other applicable Federal, State or local regulations that apply to safe practices in coating operations.  
 Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD is TOXIC.

**Validation :** Validated by US - HSE Products Coordinator on 19 December 2023

**GHS Classification**


Procedure used to derive the classification.

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SKIN IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
RESPIRATORY SENSITIZATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)



Personal Protective Equipment (PPE) shown in this section is a suggestion. Since conditions vary from one work location to another consult the facility safety & health program. Customer or end user is responsible to evaluate worker exposure conditions at the site of application and determine the appropriate PPE suitable for workers at that particular facility or location.

Abbreviations and acronyms :

# Safety Data Sheet

## NEOGARD ALIPHATIC URETHANE TOPCOAT

### 7470-002 GRAY



#### SECTION 16: Other information

ANSI = American National Standards Institute  
HCS = Hazardous Communication System  
TSCA = Toxic Substances Control Act  
CFR = Code of federal Regulations  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
OSHA = United States Occupational Health and Safety Administration  
NIOSH = National Institute for Occupational Safety and Health  
ACGIH = American Conference of Industrial Hygienists  
IARC = International Agency for Research on Cancer.  
NTP = National Toxicology Program  
ATE = Acute Toxicity Estimate

OECD = Organisation for Economic Co-operation and Development  
BCF = Bioconcentration Factor  
DOT = United States Department of Transportation  
ERG = Emergency Response Guide  
TDG = Transport of Dangerous Goods, Canada  
SCT = Transportation & Communications Ministry, Mexico  
IMDG = International Maritime Dangerous Goods  
IATA = International Air Transport Association  
SARA = Superfund Amendments Reauthorization Act  
EPCRA = Emergency Planning and Community Right to Know Act

#### Notice to reader

▣ Indicates information that has changed from previously issued version.

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*