

#### Conforms to ANSI Z400.1-2010 Standard - HCS 2012

Protective Clothing General Hazard		DOT

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : NEOGARD BIODEGRADABLE CLEANER

Product identity: 089JB00000, 8500

Product type: cleaner

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings and metal industry.

Identified uses : Industrial/Professional use

TSCA: Unless otherwise stated. All components are listed or exempted.

#### 1.3 Details of the supplier of the safety data sheet

Company details : NEOGARD, a Division of Hempel (USA), Inc.

2728 Empire Central Dallas, TX 75235

Phone number: 1-214-353-1600 E-mail: hempel@hempel.com

#### 1.4 Emergency telephone number (with hours of operation)

For Transportation Emergencies :

(24 hours)

CHEMTREC: 1-800-424-9300 (Toll-free in the U.S., Canada and the U.S. Virgin Islands) 703-527-3887

For calls originating elsewhere (Collect calls are accepted). Contract number: CCN10384

To preserve the effectiveness of arrangements for providing accurate and timely emergency response information, the basic identifying information (shipper name or contract number) must be included on

shipping papers.

If the purchaser of this product is going to be shipping this product to other locations, the purchaser must arrange for its own Emergency Information Provider to respond to transport incidents. Hempel's

24 hour response contract does not cover non-Hempel shipments.

For all other information: In USA toll free calling available: 1-800- 678-6641 or (936)-523-6000

(8 AM - 5 PM CST) See Section 4 of the safety data sheet (first aid measures).

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

GHS Classification : FLAMMABLE LIQUIDS - Category 4

SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1

#### 2.2 Label elements

Hazard pictograms:



Signal word : Danger

Hazard statements : H227 - Combustible liquid.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

Version: 0.08 Page: 1/10



#### **SECTION 2: Hazards identification**

Precautionary statements:

Prevention: Wear protective gloves, protective clothing and eye or face protection. Keep away from flames and hot

surfaces. No smoking. Wash thoroughly after handling.

Response: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If

skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call

a POISON CENTER or doctor.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international

regulations.

Supplemental label elements: None known.

2.3 Other hazards

Hazards not otherwise classified: None known.

#### **SECTION 3: Composition/information on ingredients**

Product definition : Mixture
Physical state : Liquid.

Product/ingredient name	Identifiers	%	GHS Classification
Octan-1-ol, ethoxylated	27252-75-1	≥10 - ≤25	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
ethoxylated C12-18 alcohols	68213-23-0	≥1 - ≤3	SERIOUS EYE DAMAGE - Category 1
disodium N-(2-carboxyethyl)-N-dodecyl-β-alaninate	3655-00-3	≥1 - ≤3	SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1
(C8-C10)alkyl ether of corn sugar	68515-73-1	≥1 - ≤3	SERIOUS EYE DAMAGE - Category 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

to an unconscious person.

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate

treatment (first aid).

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15

minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention

immediately.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use

recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this container or label. Keep person warm

and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so

that vomit will not re-enter the mouth and throat.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that

fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed Potential acute health effects

Version: 0.08 Page: 2/10

Occupational exposure limits, if available, are listed in Section 8.



#### **SECTION 4: First aid measures**

Eye contact : Causes serious eye damage.

Inhalation: No known significant effects or critical hazards.

Skin contact: Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

watering redness

Inhalation: No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed.

Specific treatments: No specific treatment.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Extinguishing media: Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

Not to be used: waterjet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or

mixture :

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/

oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and materials for containment and cleaning up

Version: 0.08 Page: 3/10



#### **SECTION 6: Accidental release measures**

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Product/ingredient name	Exposure limit values
No exposure limit value known.	

#### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Provide local exhaust and general ventilation systems to maintain airborne concentrations below OSHA, ACGIH, and manufacturer recommended exposure limits. Local exhaust ventilation is preferred because it prevents contaminant dispersion into work areas by controlling it at its source. Use local and general exhaust ventilation to effectively remove and prevent buildup of mists/vapors/fumes generated from the handling of this product.

Note: Local exhaust ventilation is designed to capture an emitted contaminant at or near its source, before the contaminant has a chance to disperse into the workplace air. General exhaust ventilation, also called dilution ventilation, is different from local exhaust ventilation because instead of capturing emissions at their source and removing them from the air, general exhaust ventilation allows the contaminant to be emitted into the workplace air and then dilutes the concentration of the contaminant to an acceptable level (e.g., to the PEL or below).

#### Individual protection measures

General:

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

Version: 0.08 Page: 4/10



#### **SECTION 8: Exposure controls/personal protection**

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, Hygiene measures:

using lavatory, and at the end of day.

Safety eyewear complying with an approved standard should be used when a risk assessment Eye/face protection:

> indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face

respirator may be required instead.

Hand protection: Wear chemical-resistant gloves in combination with 'basic' employee training. The quality of the

chemical-resistant protective gloves must be chosen as a function of the specific workplace

concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the

appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber, neoprene rubber, butyl rubber, natural

rubber (latex), polyvinyl alcohol (PVA), polyvinyl chloride (PVC), Viton®

Body protection: Personal protective equipment for the body should be selected based on the task being performed and

the risks involved handling this product.

Use appropriate respiratory protection if there is a risk of exceeding any exposure limits. Respiratory protection:

Protective clothing (pictograms):



Note: Application of paint products by spraying requires additional safety precautions: Full body suit, Full face respirator with air supplied.

#### **Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Liquid. Color: Clear

Odor: Non-characteristic.

pH: 7 - 9

Melting point/freezing point: 0°C This is based on data for the following ingredient: water Testing not relevant or not possible due to nature of the product. Boiling point/boiling range:

Flash point: Closed cup: 86°C (186.8°F)

Evaporation rate: Testing not relevant or not possible due to nature of the product.

Flammability: Not available. Upper/lower flammability or No specific data.

explosive limits:

Vapor pressure: 2.333 kPa This is based on data for the following ingredient: water Vapor density: Testing not relevant or not possible due to nature of the product.

1.03 g/cm<sup>3</sup> Relative density:

Partition coefficient (LogKow): Testing not relevant or not possible due to nature of the product. Auto-ignition temperature : Testing not relevant or not possible due to nature of the product. Decomposition temperature: Testing not relevant or not possible due to nature of the product. Viscosity: Testing not relevant or not possible due to nature of the product.

Not available. Explosive properties:

Oxidizing properties: Testing not relevant or not possible due to nature of the product.

Version: 0.08 Page: 5/10



#### **SECTION 9: Physical and chemical properties**

#### 9.2 Other information

Solvent(s) % by weight 0.15 % (w/w)

(Included excempt solvent(s)):

Water % by weight: Weighted average: 73 % VOC content (Coatings): 0.0129 lbs/gal (1.5 g/l) VOC content (Regulatory): 0.0526 lbs/gal (6.3 g/l) TOC Content (Volatile): Weighted average: 1 g/l Solvent Gas: Weighted average: 0 m³/l

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

No specific data.

#### 10.5 Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Direct contact with the eyes can cause irreversible damage, including blindness.

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

#### Acute toxicity estimates

Route	ATE value
No known significant effects or critical hazards.	

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure
Octan-1-ol, ethoxylated	Eyes - Severe irritant	Rat	-	-
·	Skin - Moderate irritant	Rat	-	-
ethoxylated C12-18 alcohols	Eyes - Severe irritant	Rabbit	-	100 milligrams

#### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

Version: 0.08 Page: 6/10



#### **SECTION 11: Toxicological information**

Sensitization: Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

Other information: No additional known significant effects or critical hazards.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Do not allow to enter drains or watercourses.

When spilled, this product may act as an oil, causing a film, sheen, emulsion, or sludge at or beneath the surface of a body of water. Oils of any kind can cause: (a) drowning of waterfowl due to lack of buoyancy, loss of insulating capacity of feathers, starvation and vulnerability to predators due to lack of mobility; (b) lethal effect on fish by coating gill surfaces, preventing respiration; (c) potential fish kills resulting from alteration in biochemical oxygen demand; (d) asphyxiation of benthic life forms when floating masses become engaged with surface debris and settle on the bottom; and (e) adverse aesthetic effects of fouled shoreline and beaches.

Product/ingredient name	Result	Species	Exposure
Octan-1-ol, ethoxylated	Acute EC50 >100 mg/l	Daphnia	48 hours

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
	OECD 301B Ready Biodegradability - CO <sub>2</sub> Evolution Test	91 % - Readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Octan-1-ol, ethoxylated	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
ethoxylated C12-18 alcohols (C8-C10)alkyl ether of corn sugar	4.2 -0.07	-	high low

#### 12.4 Mobility in soil

Soil/water partition coefficient No known data avaliable in our database.

(K<sub>oc</sub>):

Mobility: No known data avaliable in our database.

#### 12.5 Other adverse effects

No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7 and Section 8 for additional handling information and protection of employees.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Version: 0.08 Page: 7/10



#### **SECTION 14: Transport information**

Transport may take place according to national regulation or DOT for transport by road and by train, IMDG for transport by sea, IATA for Air shipment. Refer to specific Dangerous Goods Transport requirements under 49CFR, ICAO and IATA.

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
DOT Code	Not regula	ated.				
TDG Code	Not regula	ated.				
SCT Code	Not regula	ated.				
IMDG Code	Not regula	ated.				
IATA Code	Not regula	ated.				

Code : Classification PG\* : Packing group

Env.\*: Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

Not applicable.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : All components are active or exempted.

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304:

			SARA 302 TPQ		SARA 3	SARA 304 RQ	
Product/ingredient name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)	
ethylene oxide	<0.1	Yes.	1000	-	10	-	

**SARA 304 RQ**: 71428571.4 lbs / 32428571.4 kg [8333387.4 gal / 31545302.9 L]

SARA 311/312 Classification: FLAMMABLE LIQUIDS - Category 4
SKIN IRRITATION - Category 2
SERIOUS EVE DAMAGE - Category

SERIOUS EYE DAMAGE - Category 1

Product/ingredient name	%	Classification
Octan-1-ol, ethoxylated	≥10 - ≤25	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
ethoxylated C12-18 alcohols disodium N-(2-carboxyethyl)-N-dodecyl-β- alaninate	≥1 - ≤3 ≥1 - ≤3	SERIOUS EYE DAMAGE - Category 1 SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1
(C8-C10)alkyl ether of corn sugar	≥1 - ≤3	SERIOUS EYE DAMAGE - Category 1

Version: 0.08 Page: 8/10



#### **SECTION 15: Regulatory information**

State regulations: Connecticut Carcinogen Reporting: None of the components are listed.

Connecticut Hazardous Material Survey: None of the components are listed.

Florida substances: None of the components are listed.

Illinois Chemical Safety Act: None of the components are listed.

Illinois Toxic Substances Disclosure to Employee Act: None of the components are listed.

Louisiana Reporting: None of the components are listed. Louisiana Spill: None of the components are listed.

Massachusetts Substances: None of the components are listed. Massachusetts Spill: None of the components are listed.

Michigan Critical Material: None of the components are listed. Minnesota Hazardous Substances: None of the components are listed.

New Jersey Spill: None of the components are listed.

New Jersey Toxic Catastrophe Prevention Act: None of the components are listed.

New Jersey Hazardous Substances: None of the components are listed. New York Hazardous Substances: None of the components are listed.

New York Toxic Chemical Release Reporting: None of the components are listed. Pennsylvania RTK Hazardous Substances: None of the components are listed. Rhode Island Hazardous Substances: None of the components are listed.

California Prop. 65 PFF:

WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including 1,4-Dioxane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Product/ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
1,4-dioxane ethylene oxide	Yes. Yes.	No. Yes.	Yes. Yes.	Yes.

#### **SECTION 16: Other information**

Remarks: Note: In USA, consult Code of Federal Regulations, Title 29, Labor, Parts 1910 and 1915 concerning

occupational safety and health standards and regulations, as well as any other applicable Federal,

State or local regulations that apply to safe practices in coating operations.

Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD is TOXIC.

Validation: Validated by US - HSE Products Coordinator on 19 December 2023

#### **GHS Classification**

Procedure used to derive the classification.

Classification	Justification	
FLAMMABLE LIQUIDS - Category 4 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1	On basis of test data Calculation method Calculation method	

Hazardous Material Information System (U.S.A.)





Personal Protective Equipment (PPE) shown in this section is a suggestion. Since conditions vary from one work location to another consult the facility safety & health program. Customer or end user is responsible to evaluate worker exposure conditions at the site of application and determine the appropriate PPE suitable for workers at that particular facility or location.

#### Abbreviations and acronyms:

ANSI = American National Standards Institute HCS = Hazardous Communication System TSCA = Toxic Substances Control Act

CFR = Code of federal Regulations GHS = Globally Harmonized System of Classification and Labelling of Chemicals

OSHA = United States Occupational Health and Safety Administration

NIOSH = National Institute for Occupational Safety and Health ACGIH = American Conference of Industrial Hygienists

IARC = International Agency for Research on Cancer.

NTP = National Toxicology Program ATE = Acute Toxicity Estimate

OECD = Organisation for Economic Co-operation and Development

BCF = Bioconcentration Factor

DOT = United States Department of Transportation

ERG = Emergency Response Guide TDG = Transport of Dangerous Goods, Canada

SCT = Transportation & Communications Ministry, Mexico

IMDG = International Maritime Dangerous Goods IATA = International Air Transport Association

SARA = Superfund Amendments Reauthorization Act

EPCRA = Emergency Planning and Community Right to Know Act

Indicates information that has changed from previously issued version.

Version: 0.08 Page: 9/10



#### **SECTION 16: Other information**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Version: 0.08 Page: 10/10