84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



Conforms to ANSI Z400.1-2010 Standard - HCS 2012

Protective Clothing	General Hazard	DOT
	&	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: 84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980

Product identity: 66GJB99980, 84013

Product type : Paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application: buildings

Identified uses: Industrial/Professional use

TSCA: Unless otherwise stated. All components are listed or exempted.

1.3 Details of the supplier of the safety data sheet

Company details: NEOGARD, a Division of Hempel (USA), Inc.

2728 Empire Central Dallas, TX 75235

Phone number: 1-214-353-1600 E-mail: hempel@hempel.com

1.4 Emergency telephone number (with hours of operation)

For Transportation Emergencies :

(24 hours)

CHEMTREC: 1-800-424-9300 (Toll-free in the U.S., Canada and the U.S. Virgin Islands) 703-527-3887

For calls originating elsewhere (Collect calls are accepted). Contract number: CCN10384

To preserve the effectiveness of arrangements for providing accurate and timely emergency response information, the basic identifying information (shipper name or contract number) must be included on

shipping papers.

If the purchaser of this product is going to be shipping this product to other locations, the purchaser must arrange for its own Emergency Information Provider to respond to transport incidents. Hempel's

24 hour response contract does not cover non-Hempel shipments.

For all other information: In USA toll free calling available: 1-800- 678-6641 or (936)-523-6000

(8 AM - 5 PM CST) See Section 4 of the safety data sheet (first aid measures).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

GHS Classification : CARCINOGENICITY - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements: H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure. (lungs)

Precautionary statements :

Version: 0.04 Page: 1/9

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 2: Hazards identification

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe

dust. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response: IF exposed or concerned: Get medical advice or attention.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international

regulations.

Supplemental label elements: None known.

2.3 Other hazards

Hazards not otherwise classified: None known.

SECTION 3: Composition/information on ingredients

Product definition : Mixture
Physical state : Solid. [Sand.]

Product/ingredient name	Identifiers	%	GHS Classification
respirable quartz	14808-60-7	≥50 - ≤75	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
aluminium oxide Iron oxide (Fe2O3)	1344-28-1 1309-37-1	≥10 - ≤25 ≥1 - ≤3	Not classified. Not classified.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4: First aid measures

4.1 Description of first aid measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

to an unconscious person.

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate

treatment (first aid).

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15

minutes, occasionally lifting the upper and lower eyelids. In all cases of doubt, or when symptoms

persist, seek medical attention.

Inhalation : Remove to fresh air.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use

recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this container or label. Keep person warm

and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so

that vomit will not re-enter the mouth and throat.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Version: 0.04 Page: 2/9

Occupational exposure limits, if available, are listed in Section 8.

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 4: First aid measures

Inhalation :No specific data.Skin contact :No specific data.Ingestion :No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Not applicable.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media: Recommended: alcohol resistant foam, CO₂, powders, water spray.

Not to be used: waterjet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or No specific fire or explosion hazard.

mixture:

Hazardous combustion products: Decomposition products may include the following materials: metal oxide/oxides

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training.

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

Version: 0.04 Page: 3/9

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Product/ingredient name	Exposure limit values
respirable quartz	OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form: Respirable OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2022). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust
aluminium oxide	ACGIH TLV (United States, 1/2022). [Aluminum, metal and insoluble compounds] TWA: 1 mg/m³ 8 hours. Form: Respirable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust
Iron oxide (Fe2O3)	NIOSH REL (United States, 10/2020). TWA: 5 mg/m³, (as Fe) 10 hours. Form: Dust and fumes ACGIH TLV (United States, 1/2022). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls

Provide local exhaust and general ventilation systems to maintain airborne concentrations below OSHA, ACGIH, and manufacturer recommended exposure limits. Local exhaust ventilation is preferred because it prevents contaminant dispersion into work areas by controlling it at its source. Use local and general exhaust ventilation to effectively remove and prevent buildup of mists/vapors/fumes generated from the handling of this product.

Note: Local exhaust ventilation is designed to capture an emitted contaminant at or near its source, before the contaminant has a chance to disperse into the workplace air. General exhaust ventilation, also called dilution ventilation, is different from local exhaust ventilation because instead of capturing emissions at their source and removing them from the air, general exhaust ventilation allows the contaminant to be emitted into the workplace air and then dilutes the concentration of the contaminant to an acceptable level (e.g., to the PEL or below).

Individual protection measures

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be

worn when soiling is so great that regular work clothes do not adequately protect skin against contact

with the product. Safety eyewear should be used when there is a likelihood of exposure.

Hygiene measures: Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking,

using lavatory, and at the end of day.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment

indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of

protection: safety glasses with side-shields.

Hand protection: Wear chemical-resistant gloves in combination with 'basic' employee training. The quality of the

chemical-resistant protective gloves must be chosen as a function of the specific workplace

concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the

appropriate type.

Body protection: Personal protective equipment for the body should be selected based on the task being performed and

the risks involved handling this product.

Respiratory protection: Use appropriate respiratory protection if there is a risk of exceeding any exposure limits. Use dust

protection mask, when there is a risk for dust.

Version: 0.04 Page: 4/9

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 8: Exposure controls/personal protection

Protective clothing (pictograms):



Note: Application of paint products by spraying requires additional safety precautions: Full body suit, Full face respirator with air supplied.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Sand.

Odor: Non-characteristic.

pH: Testing not relevant or not possible due to nature of the product.

Melting point/freezing point: 1610°C This is based on data for the following ingredient: respirable quartz

Boiling point/boiling range: Testing not relevant or not possible due to nature of the product.

Flash point : May be combustible at high temperature.

Evaporation rate: Testing not relevant or not possible due to nature of the product.

Flammability: May be combustible at high temperature.

Upper/lower flammability or

explosive limits:

No specific data.

Vapor pressure : Testing not relevant or not possible due to nature of the product.

Vapor density : Testing not relevant or not possible due to nature of the product.

Relative density: 2.65 g/cm³

Partition coefficient (LogKow): Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature: Testing not relevant or not possible due to nature of the product.

Decomposition temperature: Testing not relevant or not possible due to nature of the product.

Viscosity: Testing not relevant or not possible due to nature of the product.

Explosive properties: Not available.

Oxidizing properties: Testing not relevant or not possible due to nature of the product.

9.2 Other information

Solvent(s) % by weight 0 % (w/w)

(Included excempt solvent(s)):

Water % by weight : Weighted average: 0 %

VOC content (Coatings): 0 lbs/gal (0 g/l)
VOC content (Regulatory): 0 lbs/gal (0 g/l)

TOC Content (Volatile): Weighted average: 0 g/l Solvent Gas: Weighted average: 0 m³/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Version: 0.04 Page: 5/9

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 10: Stability and reactivity

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

No specific data.

10.5 Incompatible materials

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

No known significant effects or critical hazards.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Acute toxicity estimates

Route	ATE value		
No known significant effects or critical hazards.			

Carcinogen Classification

Product/ingredient name	IARC	NTP	OSHA	
respirable quartz	1	Known to be a	-	
Iron oxide (Fe2O3)	3	human carcinogen. -	-	

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category Route of exposu		Target organs
respirable quartz	Category 1	inhalation	lungs

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

Other information: No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses.

When spilled in water or drains, this product can cause: (a) contribute to suspended solid loading of the water body; (b) turbidity and reduce penetration of light into the water column; (c) alter water pH and/or alkalinity; (d) contribute to sediments at bottom of water column; (e) add colour to the sediment. When spilled to land surface with no runoff due to precipitation, this product can cause: (a) fines present may become air-borne and be transported by wind; (b) contribute to accumulation of surface "dirt"; (c) colour changes to surfaces on which it is spilled.

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

Version: 0.04 Page: 6/9

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 12: Ecological information

Soil/water partition coefficient No known data avaliable in our database.

(K_{oc}) : Mobility :

No known data avaliable in our database.

12.5 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7 and Section 8 for additional handling information and protection of employees.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Transport may take place according to national regulation or DOT for transport by road and by train, IMDG for transport by sea, IATA for Air shipment. Refer to specific Dangerous Goods Transport requirements under 49CFR, ICAO and IATA.

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
DOT Code	Not regula	ated.				
TDG Code	Not regula	ated.				
SCT Code	Not regula	ated.				
IMDG Code	Not regula	ated.				
IATA Code	Not regula	ated.				

Code : Classification PG* : Packing group

Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

Not applicable.

Version: 0.04 Page: 7/9

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : All components are active or exempted.

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 311/312 Classification: CARCINOGENICITY - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Product/ingredient name	%	Classification
respirable quartz	≥50 - ≤75	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

State regulations: Connecticut Carcinogen Reporting: None of the components are listed.

Connecticut Hazardous Material Survey: None of the components are listed.

Florida substances: None of the components are listed.

Illinois Chemical Safety Act: None of the components are listed.

Illinois Toxic Substances Disclosure to Employee Act: None of the components are listed.

Louisiana Reporting: None of the components are listed. **Louisiana Spill**: None of the components are listed.

Massachusetts Substances: The following components are listed: SILICA, CRYSTALLINE, QUARTZ;

ALUMINUM OXIDE; ROUGE DUST

Massachusetts Spill: None of the components are listed.

Michigan Critical Material: None of the components are listed.

Minnesota Hazardous Substances: None of the components are listed.

New Jersey Spill: None of the components are listed.

New Jersey Toxic Catastrophe Prevention Act: None of the components are listed.

New Jersey Hazardous Substances: The following components are listed: SILICA, QUARTZ;

ALUMINUM OXIDE; POTASSIUM OXIDE; IRON OXIDE

New York Hazardous Substances: None of the components are listed.

New York Toxic Chemical Release Reporting: None of the components are listed.

Pennsylvania RTK Hazardous Substances: The following components are listed: QUARTZ DUST;

ALUMINUM OXIDE; IRON OXIDE

Rhode Island Hazardous Substances: None of the components are listed.

California Prop. 65 PFF:WARNING: This product can expose you to chemicals including Silica, crystalline and Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.

P65Warnings.ca.gov.

Product/ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
respirable quartz titanium dioxide	Yes. Yes.	No. No.		

SECTION 16: Other information

Remarks: Note: In USA, consult Code of Federal Regulations, Title 29, Labor, Parts 1910 and 1915 concerning

occupational safety and health standards and regulations, as well as any other applicable Federal,

State or local regulations that apply to safe practices in coating operations.

Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD is TOXIC.

Validation: Validated by US - HSE Products Coordinator on 19 December 2023

GHS Classification

Procedure used to derive the classification.

Classification	Justification
CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method Calculation method

0.04 Page: 8/9

Hazardous Material Information System (U.S.A.)

84013 CUSTOM BLEND NEOQUARTZ 66GJB 99980 84013



SECTION 16: Other information





Personal Protective Equipment (PPE) shown in this section is a suggestion. Since conditions vary from one work location to another consult the facility safety & health program. Customer or end user is responsible to evaluate worker exposure conditions at the site of application and determine the appropriate PPE suitable for workers at that particular facility or location

Abbreviations and acronyms:

ANSI = American National Standards Institute HCS = Hazardous Communication System TSCA = Toxic Substances Control Act CFR = Code of federal Regulations

GHS = Globally Harmonized System of Classification and Labelling of Chemicals OSHA = United States Occupational Health and Safety Administration

NIOSH = National Institute for Occupational Safety and Health

ACGIH = American Conference of Industrial Hygienists IARC = International Agency for Research on Cancer.

NTP = National Toxicology Program

ATE = Acute Toxicity Estimate

OECD = Organisation for Economic Co-operation and Development

BCF = Bioconcentration Factor

DOT = United States Department of Transportation

ERG = Emergency Response Guide

TDG = Transport of Dangerous Goods, Canada SCT = Transportation & Communications Ministry, Mexico

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association SARA = Superfund Amendments Reauthorization Act

EPCRA = Emergency Planning and Community Right to Know Act

Notice to reader



Indicates information that has changed from previously issued version.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Version: 0.04 Page: 9/9