



Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Form	Mixture
Trade Name	ACRYL-PEN 600
Product Code	AP600

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet

Manufacturer

NOX-CRETE, INC.
1444 SOUTH 20TH STREET
OMAHA, NE 68108
Tel: 402-341-2080
Fax: 402-341-9752
E-Mail: corporate@nox-crete.com
Web Site: www.nox-crete.com

1.4 Emergency telephone number

Emergency Number	Chemtrec (800) 424-9300 Chemtrec Outside of U.S. 703-527-3887
------------------	--

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Flam Liq. 3	H226
Asp. Tox. 1	H304
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Acute Tox. 4 (inhalation)	H332
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT SE	H371
STOT RE 2	H373

Full text of H phrases see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2 Label elements

Hazard pictograms



Signal word

Danger



Hazard statements

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H371 - May cause damage to organs
H373 - May cause damage to ears and CNS through prolonged or repeated exposure

Flam Liq. 3

Precautionary statements

Prevention:

P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/light/equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P264 - Wash exposed area's thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response:

P301+P316 - IF SWALLOWED: Get emergency medical help immediately.
P317, P319, P318: Get emergency medical help, if you feel unwell.
P303+P361+P353, P321 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P332+P317 - If skin irritation occurs: Get medical help.

P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction

Storage:

P403+P405+P235+P233 - Store locked up in a cool well ventilated place. Keep container tightly closed.

Disposal:

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Full text of H and P phrases: see section 16

Section 3. Composition / information on ingredients

**3.1 Substances**

Not applicable

3.2 Mixture

Name	Product identifier	%
Xylene	1330-20-7	< 60.0
Aromatic Solvent	Trade Secret	Trade Secret
Ethylbenzene	100-41-4	< 20.0
Propylene Glycol Monomethyl Ether	108-65-6	Trade Secret
Alkyl Alkoxy Silane	Trade Secret	Trade Secret

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS. Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

Section 4. First aid measures**4.1 Description of first aid measures****First-aid measures general**

Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation

If the individual experiences nausea, dizziness, has difficulty in breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact

If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.

First-aid measure after eye contact

When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.

4.2 Most important symptoms and effects, acute and delayed**Symptoms/injuries after inhalation**

May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.

Symptoms/injuries after skin contact

May cause skin irritation or burning sensation

Symptoms/injuries after eye contact

May cause eye irritation or injury

Symptoms/injuries after ingestion

May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

Section 5. Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Dry chemical, foam, carbon dioxide

Unsuitable extinguishing media

Do not use heavy water stream

5.2 Special hazards arising from the substance or mixture



Reactivity

Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Firefighting instructions

Flammable Liquid! This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.

Protective equipment for firefighters

Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.

Other information

On heating or burning harmful gasses/vapors may be released. This product may cause the floor to become slippery.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General measures

Extremely Flammable. Eliminate any ignition sources. Dike or impound spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and safety before attempting spill control or cleanup.

6.11 Protective Equipment

Equip cleanup crew with proper protective equipment.

6.2 Environmental precautions

Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

Soak up spills with inert solids, such as clay or diatomaceous earth. Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures

Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist.

Hygiene measures

Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store in accordance with local regulations. Store in original container in a cool well-ventilated place away from heat, sparks and open flame. Keep containers tightly closed until ready for use.

Incompatible materials

Strong oxidizing agents

Storage temperature

Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Xylene	TWA: 100 ppm 8 hours
Aromatic Solvent	TWA: 100 ppm 8 hours
Ethylbenzene	TWA: 20 ppm 8 hours
Toluene	TWA: 20 ppm 8 hours
Cumene	TWA: 50 ppm 8 hours
Propylene Glycol Monomethyl Ether	TWA: 100 ppm 8 hours
Alkyl Alkoxy Silane	Not established



8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations below specified TLV

Eye and face protection potential

Chemical goggles and/or face shields are recommended to prevent eye contact, irritation or injury.

Skin protection

Wear chemical resistant gloves and appropriate protective clothing and boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

Respiratory protection

General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Clear liquid
Odor	Strong Aromatic Odor
Odor Threshold	No data available
PH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	> 136 C (> 275 F)
Flash point	> 27 C (> 80 F) PMCC
Relative evaporation rate (butyl acetate=1)	No data available
Flammability (solid, gas)	Flammable liquid and vapor
Upper/lower explosive limits	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density (Specific gravity)	0.97 Kg per Liter 8.1 Lbs per Gallon
Solubility	Water: Negligible
Partition coefficient n-octanol/water	No data available
Auto-ignition temperature	Not applicable
Viscosity	No data available
VOC content	Less than 600 g/l

Section 10. Stability and reactivity

<u>10.1 Reactivity</u>	No additional information available
<u>10.2 Chemical stability</u>	Stable under normal conditions
<u>10.3 Possibility of hazardous reactions</u>	Hazardous polymerization will not occur.
<u>10.4 Conditions to avoid</u>	Extreme high or low temperatures.
<u>10.5 Incompatible materials</u>	Strong acids and oxidizers
<u>10.6 Hazardous decomposition products</u>	carbon monoxide, carbon dioxide, various hydrocarbon derivatives

Section 11. Toxicology information

11.1 Information on toxicological effects

Acute toxicity	No adverse effects expected under intended use.
Irritation/Corrosion	May cause skin irritation
Skin	May causes serious eye irritation and damage.
Eyes	May cause respiratory irritation
Respiration or skin sensitization	No data available
Germ cell mutagenicity	
Carcinogenicity	IARC



Xylene	3
Ethylbenzene	2B
Cumene	2B
Toluene	3

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

Reproductive toxicity	No data available
Specific target organ toxicity	
Single exposure	No data available
Repeated exposure	No data available
Aspiration hazard	May be fatal if swallowed and enters airways

Section 12. Ecological information

12.1 Ecotoxicity	Not established
12.2 Persistence and degradability	Not established
12.3 Bioaccumulative potential	Not established
12.4 Mobility in soil	No additional information available
12.5 Other adverse effects	Avoid release to the environment

SECTION 13. Disposal Considerations

13.1 Waste treatment methods	The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
-------------------------------------	--

SECTION 14. Transport information

In accordance with DOT Not dangerous goods in sense of transport regulations.

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN number	UN1263
14.2 UN proper shipping name	Paint Related Material
14.3 Transport hazard class(es)	3
14.4 Packing group	III
14.5 Environmental hazards	No additional information available
14.6 Special precautions for user	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No additional information available
14.8 Transport in bulk according to CFR 49 173.15	Not applicable

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
15.1.2 USA Regulations



Section 313

Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material.

CHEMICAL	CAS #	MAX WEIGHT %
Xylene	1330-20-7	60.0
Ethylbenzene	100-41-4	20.0
1,2,4,-Trimethylbenzene	95-63-6	2.0
Cumene	98-82-8	1.0
Toluene	108-88-3	1.0

TSCA

All ingredients are listed or exempted

PROPOSITION 65

NOT FOR SALE IN THE STATE OF CALIFORNIA

15.1.3 Canada Regulations

This SDS has been prepared according to the hazard criteria of the *Hazardous Products Regulation* (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR.

DSL

All ingredients are listed or exempted

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

Section 16. Other information

Date of issue / revision	5-13-2024
Version	5.0
Number	102
Date of previous issue / revision	1-31-2024
Preparer	Nox-Crete, Inc.

Reference Documentation

The information and recommendations contained herein are, to the best of Nox-Crete, Inc.'s knowledge and belief, accurate and reliable as of the date issued. You can contact Nox-Crete, Inc. to ensure that this document is the most current available from Nox-Crete, Inc. The information and recommendations are offered for the buyer's/user's consideration and examination. It is the buyer's/user's responsibility to satisfy themselves that the product is suitable for the intended use. Appropriate warnings and safe-handling procedures should be provided to all handlers and users. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Since the information provided herein may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and buyer/user may rely thereon only at their risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further, since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each buyer/user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. If buyer/user repackages this product, it is the buyer's/user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Nox-Crete, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted.

**Full text of H and P phrases**

Flam Liq. 3	H226
Asp. Tox. 1	H304
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Acute Tox. 4 (inhalation)	H332
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT SE	H371
STOT RE 2	H373

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H371 - May cause damage to organs
H373 - May cause damage to ears and CNS through prolonged or repeated exposure

Flam Liq. 3

P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/light/equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P264 - Wash exposed area's thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P316 - IF SWALLOWED: Get emergency medical help immediately.
P317, P319, P318: Get emergency medical help, if you feel unwell.
P303+P361+P353, P321 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P332+P317 - If skin irritation occurs: Get medical help.
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction
P403+P405+P235+P233 - Store locked up in a cool well ventilated place. Keep container tightly closed.
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.