



# EcoTouch® Flame Spread 25 Fiberglas™ Insulation



Owens Corning® EcoTouch® Flame Spread 25 Fiberglas™ Insulation is a preformed, flexible blanket insulation. It is produced in R-values from 11 to 49, at thickness from 3½ to 11 inches. It is available with either a FSK (foil-scrim-kraft) or PSK (poly-scrim-kraft) facing; both of which act as vapor retarders and provide a neat, finished appearance.

- Excellent thermal control
- Effective acoustical performance
- Provides long term performance and will not settle nor slump within wall cavities
- Less dust than other fiberglass insulation products
- Excellent recovery characteristics<sup>1</sup>
- Compression packaging speeds job site handling and installation

1. According to 2010 clinical trial conducted in Toronto, Canada by Ducker Worldwide on behalf of Owens Corning Insulation Systems, LLC.

- Wall, floor and roof/ceiling assemblies where the insulation will be left exposed, or where a low flame spread vapor retarder facing is required
- Concealed applications of assemblies for non-combustible construction
- Wood and metal framed assembly cavities, or attached to surfaces with impaling pins

Property (unit)	Test	Value
Thermal Resistance	ASTM C518	See "Availability" table for R-values
Surface Burning Characteristics (flame spread/smoke developed)	ASTM E84 <sup>1</sup>	
FSK		<25/<50
PSK		<25/<50
Critical Radiant Flux (W/cm <sup>2</sup> )	ASTM E970	>0.12
Water Vapor Permeance (perms)		
FSK	ASTM E96 <sup>2</sup>	.5
PSK	ASTM E96 <sup>2</sup>	.5
Water Vapor Sorption (by weight)	ASTM C1104/ C1104M	<5%
Odor Emission	ASTM C1304	pass
Corrosion Resistance	ASTM C665, part 13.8	pass
Fungi Resistance (fiberglass only)	ASTM C1338	pass

1. ASTM E84 is used solely to measure and describe properties of products in response to heat and flame under controlled laboratory conditions, and should not be used to describe or approve the fire hazard of materials under actual fire conditions. However, the results of these tests may be used as elements of a fire risk assessment that takes into account all of the factors of the fire hazard of a particular end use. Values are reported to the nearest five rating.
2. Dessicant method

	IBC Bldg. Construction	ASTM C665
FSK	All Types	Type III, Class A, Cat. 1
PSK	All Types	Type II, Class A, Cat. 1

- Manufactured in compliance with ASTM C 665
- Federal Specification HH-I-521F has been canceled and replaced by ASTM C 665
- Classified noncombustible when tested in accordance with ASTM E 136
- EcoTouch® Flame Spread 25 insulation is accepted for use in all ICC building construction types (1 through V)
- Certified to meet California Code of Regulations, Title 24, Chapter 12-13, Article 3, "Standards for Insulating Material"
- The building thermal barrier (insulation) should be in continual alignment with the building air barrier
- In framed cavities product thickness should match the depth of the framing members
- Follow the local, applicable building code(s) to determine the need for and placement of a vapor retarder
- Do not install insulation on top, or within 3 inches of a recessed light fixture unless the fixture is labeled as "insulation contact" (IC) rated

Application	Width	Length	Thickness	R-value <sup>3</sup>
Wood Frame Walls				
FSK-E <sup>4</sup>	23"	93"	6.25"	19 <sup>5</sup>
PSK-E <sup>4</sup>	23"	93"	6.25"	19 <sup>5</sup>
PSK-E <sup>4</sup>	23"	96"	6.25"	19 <sup>5</sup>
FSK-E <sup>4</sup>	23"	96"	6.25"	19 <sup>5</sup>
FSK	15"	93"	5.5"	21
Metal Frame Walls				
FSK	16"	96"	3.5"	13
FSK	24"	96"	3.5"	13
FSK	16"	96"	6.25"	19
FSK	24"	96"	6.25"	19
FSK	16"	96"	5.5"	21
Floor/Ceiling				
FSK	16"	48"	9.5"	30
PSK-E <sup>4</sup>	24"	48"	9.5"	30
FSK-E <sup>4</sup>	24"	48"	9.5"	30
FSK	24"	48"	9.5"	30
FSK	16"	48"	12"	38
FSK	24"	48"	12"	38

3. Tested per ASTM C518
4. FSK-E / PSK-E = Extended flange
5. Delivers R18 when installed in a 5.5" deep cavity

See Owens Corning publication "Installation Guide for Light Density Building Insulation" (Pub. No. 10017858) for more information. Both FSK and PSK EcoTouch® Flame Spread 25 insulation facing options are more abuse-resistant than most other building insulation facings. However, when it is installed in areas where the material may be subject to abuse, suitable protection should be provided.

Owens Corning is a worldwide leader in building material systems, insulation and composite solutions, delivering a broad range of high-quality products and services. Owens Corning is committed to driving sustainability by delivering solutions, transforming markets and enhancing lives. More information can be found at [www.owenscorning.com](http://www.owenscorning.com).

Fiberglass products may cause temporary skin and mucous membranes itching due to the mechanical abrasion effects of fibers, a condition which is completely reversible. Owens Corning does not recommend the use of unfaced EcoTouch® PINK® Fiberglas™ Insulation in exposed applications where it will be subject to routine human contact due to this potential temporary irritation.

For additional information, refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

- Certified by SCS Global Services to contain a minimum of 55% recycled glass content, 18% pre-consumer and 37% post-consumer
- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg)
- Environmental Product Declaration (EPD) has been certified by UL Environment
- Bronze Material Health Certificate from Cradle to Cradle Products Innovation Institute



Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.SCSglobalservices.com](http://www.SCSglobalservices.com).

LEED® is a registered trademark of the U.S. Green Building Council.

**OWENS CORNING INSULATING SYSTEMS, LLC**  
 ONE OWENS CORNING PARKWAY  
 TOLEDO, OHIO, USA 43659

**1-800-GET-PINK®**  
[www.owenscorning.com](http://www.owenscorning.com)

Pub. No. 18142-R. Printed in U.S.A. July 2018.  
 THE PINK PANTHER™ & © 1964–2018 Metro-Goldwyn-Mayer Studios Inc.  
 All Rights Reserved. The color PINK is a registered trademark of Owens Corning.  
 © 2018 Owens Corning. All Rights Reserved.

