

HPD UNIQUE IDENTIFIER: 22590

CLASSIFICATION: 09 29 00 Gypsum Board

PRODUCT DESCRIPTION: PABCO® 1/2" gypsum wallboard products are manufactured with a dimensionally stable, noncombustible fire-resistant gypsum core encased in 100% recycled paper. The panels are tapered providing a recessed area that allows joints to be reinforced and concealed with joint treatment creating a monolithic decorating surface. PABCO® 1/2" gypsum wallboard products are suitable for use on both walls and ceilings in non-fire-resistance rated applications. 1/2" PABCO® Regular gypsum wallboard is formulated to provide a suitable surface for decoration. 1/2" PABCO® Interior Ceiling Board is specifically formulated with a sag-resistant gypsum core allowing for the application of a water-based texture material on ceiling applications. 1/2" LITECORE® is specifically formulated to be lighter than original 1/2" PABCO® Regular wallboard.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- Basic Method

Threshold level

- 100 ppm
- 1,000 ppm
- Per GHS SDS
- Other

Residuals/Impurities

- Considered
- Partially Considered
- Not Considered

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No
% weight and role provided for all substances.

Threshold Disclosed Per

- Material
- Product

Explanation(s) provided for Residuals/Impurities?

- Yes No

Screened Yes Ex/SC Yes No

All substances screened using Priority Hazard Lists with results disclosed.

Identified Yes Ex/SC Yes No

All substances disclosed by Name (Specific or Generic) and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

1/2" PABCO® GYPSUM WALLBOARD [CALCIUM SULFATE DIHYDRATE LT-UNK PULP, CELLULOSE NoGS STARCH LT-UNK DEXTRIN LT-UNK SODIUM 1-NAPHTHALENESULFONATE NoGS QUARTZ LT-1 | CAN]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Undisclosed substances are proprietary trade secrets.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed

Third Party Verified?

- Yes
- No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2020-10-16

PUBLISHED DATE: 2020-10-20

EXPIRY DATE: 2023-10-16

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

1/2" PABCO® GYPSUM WALLBOARD

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw material obtained from naturally occurring gypsum mineral may contain crystalline silica. The amount of silica that can be reduced to respirable is dependent on many factors and testing has shown that the cut and score method does not produce respirable silica above OSHA Permissible Exposure Limit (PEL).

OTHER PRODUCT NOTES: N/A

CALCIUM SULFATE DIHYDRATE

ID: 10101-41-4

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2020-10-16

#: 85.0000 - 95.0000 GS: LT-UNK RC: Both NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found		No warnings found on HPD Priority Hazard Lists
------------	--	--

SUBSTANCE NOTES: Main core substrate comprised of gypsum

PULP, CELLULOSE

ID: 65996-61-4

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2020-10-16

#: 5.0000 - 10.0000 GS: NoGS RC: Both NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found		No warnings found on HPD Priority Hazard Lists
------------	--	--

SUBSTANCE NOTES: Paper encasing for the front and back

STARCH

ID: 9005-25-8

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2020-10-16

#: 0.0000 - 1.0000 GS: LT-UNK RC: UNK NANO: No SUBSTANCE ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
-------------	------------------------	----------

None found		No warnings found on HPD Priority Hazard Lists
------------	--	--

SUBSTANCE NOTES: Core adhesive added to the core.

DEXTRIN

ID: 9004-53-9

%: **0.0000 - 0.5000**GS: **LT-UNK**RC: **UNK** NANO: **No** SUBSTANCE ROLE: **Structure component**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Drying additive added to to the core.

SODIUM 1-NAPHTHALENESULFONATEID: **130-14-3**%: **0.0000 - 0.5000**GS: **NoGS**RC: **UNK** NANO: **No** SUBSTANCE ROLE: **Structure component**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Drying additive added to the core.

QUARTZID: **14808-60-7**%: **Impurity/Residual**GS: **LT-1**RC: **None** NANO: **No** SUBSTANCE ROLE: **Impurity/Residual**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CANCER	IARC	Group 1 - Agent is Carcinogenic to humans
CANCER	US CDC - Occupational Carcinogens	Occupational Carcinogen
CANCER	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CANCER	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CANCER	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CANCER	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CANCER	GHS - New Zealand	6.7A - Known or presumed human carcinogens
CANCER	GHS - Japan	Carcinogenicity - Category 1A [H350]
CANCER	GHS - Australia	H350i - May cause cancer by inhalation

SUBSTANCE NOTES: Impurity of naturally occurring gypsum.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario

CERTIFYING PARTY: Third Party

ISSUE DATE: 2018-10-

EXPIRY DATE:

CERTIFIER OR LAB: Berkeley

APPLICABLE FACILITIES: Berkeley Analytical, 815

19

Analytical

Harbour Way South, Suite 6 Richmond, CA 94804 510-

236-2325

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

FRAMING

HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Framing material, i.e. wood or steel, shall be selected per building codes, fire design, or acoustical design as specified in the Basis of Design (BOD).

FASTENERS

HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Fasteners, i.e. nail or screw, shall be selected per building codes, fire design, or acoustical design as specified in the Basis of Design (BOD).

JOINT TAPING

HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Joint taping shall be used in gypsum board finishing per Level of Finish as specified in the Basis of Design (BOD).

JOINT COMPOUND

HPD URL: No HPD Available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Joint compound shall be used in gypsum board finishing per Level of Finish as specified in the Basis of Design (BOD).

Section 5: General Notes

This HPD is for three products: 1/2" PABCO® Regular gypsum wallboard 1/2" PABCO® Interior Ceiling Board 1/2" LITECORE®

MANUFACTURER INFORMATION

MANUFACTURER: PABCO Gypsum
ADDRESS: PO Box 364329
 North Las Vegas NV 89036, United States
WEBSITE: www.pabco gypsum.com

CONTACT NAME: Deborah Callaway
TITLE: Technical Services Manager--Gypsum
PHONE: 17029562413
EMAIL: deborah.callaway@pabco gypsum.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	NoGS No GreenScreen.
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.