



SAFETY DATA SHEET PU COLORFAST AX

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name PU COLORFAST AX
Product number 8510
Internal identification YELLOW

Recommended use of the chemical and restrictions on use

Application Pigment
Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Manufacturer ParexUSA, Inc.
4125 E. La Palma Ave, Suite 250
Anaheim, CA 92807, USA
T: 1-800-226-2424
F: 1-714-774-2079

Contact Information Technical Department
technicalservice@parexusa.com
www.parexusa.com

Emergency telephone number

Emergency telephone CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified
Health hazards Skin Sens. 1 - H317
Environmental hazards Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412

Label elements

Pictogram



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

PU COLORFAST AX

Precautionary statements	<p>P261 Avoid breathing vapor/ spray.</p> <p>P272 Contaminated work clothing must not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--

Contains 3-iodo-2-propynyl-butylcarbamate

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

<p>trizinc bis(orthophosphate) 1-5%</p> <p>CAS number: 7779-90-0</p> <p>M factor (Acute) = 1 M factor (Chronic) = 1</p>
<p>Classification</p> <p>Aquatic Acute 1 - H400</p> <p>Aquatic Chronic 1 - H410</p>
<p>Titanium Dioxide 1-5%</p> <p>CAS number: 13463-67-7</p>
<p>Classification</p> <p>Not Classified</p>
<p>Kaolin Clay 1-5%</p> <p>CAS number: 1332-58-7</p>
<p>Classification</p> <p>Skin Irrit. 2 - H315</p> <p>Eye Irrit. 2A - H319</p>

PU COLORFAST AX

3-iodo-2-propynyl-butylcarbamate	<1%
CAS number: 55406-53-6	
M factor (Acute) = 1	M factor (Chronic) = 1
Classification Acute Tox. 4 - H302 Acute Tox. 3 - H331 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT RE 1 - H372 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	Rinse with water.
Eye contact	Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known. May be slightly irritating to eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

PU COLORFAST AX

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances:
Harmful gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

PU COLORFAST AX

Storage class Miscellaneous hazardous material storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Titanium Dioxide

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

A4

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Kaolin Clay

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction

A4

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

OSHA = Occupational Safety and Health Administration.

Titanium Dioxide (CAS: 13463-67-7)

Immediate danger to life and health 5000 mg/m³

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended. Avoid contact with skin.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PU COLORFAST AX

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Odor threshold	No information available.
pH	Not applicable.
Melting point	Not available.
Initial boiling point and range	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Vapor pressure	No information available.
Vapor density	No information available.
Relative density	No information available.
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Other information	None.

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

PU COLORFAST AX

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 545.45

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation No specific symptoms known.

Ingestion No specific symptoms known.

Skin Contact No specific symptoms known.

Eye contact No specific symptoms known.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target Organs No specific target organs known.

12. Ecological Information

PU COLORFAST AX

Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
Toxicity	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
<u>Persistence and degradability</u>	
Persistence and degradability	The degradability of the product is not known.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
Partition coefficient	No information available.
<u>Mobility in soil</u>	
Mobility	No data available.
<u>Other adverse effects</u>	
Other adverse effects	None known.

13. Disposal considerations

Waste treatment methods

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Dispose of waste via a licensed waste disposal contractor.

14. Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).
<u>UN Number</u>	Not applicable.
UN No. (DOT)	Not applicable.
<u>UN proper shipping name</u>	Not applicable.
Proper shipping name (DOT)	Not applicable.
<u>Transport hazard class(es)</u>	No transport warning sign required.
DOT transport labels	No transport warning sign required.
<u>Packing group</u>	Not applicable.
DOT packing group	Not applicable.
<u>Environmental hazards</u>	

PU COLORFAST AX

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

trizinc bis(orthophosphate)

1.0 %

3-iodo-2-propynyl-butylcarbamate

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Titanium Dioxide

Known to the State of California to cause cancer.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

PU COLORFAST AX

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Titanium Dioxide

Present.

Kaolin Clay

Present.

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Titanium Dioxide

Present.

Kaolin Clay

Present.

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Titanium Dioxide

Present.

Kaolin Clay

Present.

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

3-iodo-2-propynyl-butylcarbamate

Present.

Titanium Dioxide

Present.

Kaolin Clay

Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Titanium Dioxide

Present.

Kaolin Clay

Present.

Inventories

US - TSCA

The following ingredients are listed or exempt:

trizinc bis(orthophosphate)

Present.

3-iodo-2-propynyl-butylcarbamate

Present.

PU COLORFAST AX

Titanium Dioxide

Present.

Kaolin Clay

Present.

5-Chloro-2-methyl-2H-isothiazol-3-one

Present.

2-methylisothiazol-3(2H)-one

Present.

US - TSCA 12(b) Export Notification

The following ingredients are listed or exempt:

5-Chloro-2-methyl-2H-isothiazol-3-one

Present.

2-methylisothiazol-3(2H)-one

Present.

16. Other information

Training advice	Only trained personnel should use this material.
Revision date	8/15/2018
Revision	1
SDS No.	4765
Hazard statements in full	<p>H302 Harmful if swallowed.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H331 Toxic if inhaled.</p> <p>H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H402 Harmful to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.