



Revision Number: 007.2

Issue date: 09/09/2020

1. PRODUCT AND COMPANY IDENTIFICATION


Product name: Loctite® PL® Polyurethane Self-Leveling Concrete Crack Sealant
IDH number: 1618150
Product type/use: Sealant
Restriction of Use: None identified
Region: United States
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067
Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkeln.com

This product contains a chemical which is subject to a proposed Environmental Protection Agency (EPA) Significant New Use Restriction (SNUR).

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
DANGER:	COMBUSTIBLE LIQUID. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE DAMAGE. MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. SUSPECTED OF CAUSING CANCER. HARMFUL IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
ACUTE TOXICITY INHALATION	3
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
CARCINOGENICITY	2



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	>= 40 - < 50
Stoddard solvent, <0.1% Benzene	8052-41-3	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Toluene-2,6-diisocyanate	91-08-7	0.1 - 1
Gamma-glycidoxypropyl trimethoxysilane	2530-83-8	0.1 - 1
Calcium oxide	1305-78-8	1 - 5
4-isocyanatosulphonyltoluene	4083-64-1	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If inhaled, immediately remove the affected person to fresh air. Immediate medical treatment necessary.
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothes.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Do not induce vomiting, seek medical advice immediately.
Symptoms:	See Section 11.
Notes to physician:	An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate. Treatment based on judgement of the physician in response to reactions of the patient.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	None known.
Hazardous combustion products:	Nitrous gases Irritating fumes. Isocyanate vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilated area. Wear appropriate protective equipment and clothing during clean-up. Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid extreme temperatures. Wash thoroughly after handling. Protect from moisture. Use only with adequate ventilation.

Storage: For safe storage, store between 18.3 °C (64.9 °F) and 40 °C (104°F) Avoid moisture. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m3) PEL	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Toluene-2,6-diisocyanate	0.005 ppm STEL Inhalable fraction and vapor. 0.001 ppm TWA Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor. (Dermal sensitization) (Respiratory sensitization)	None	None	None
Gamma-glycidoxypropyl trimethoxysilane	None	None	None	None
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
4-isocyanatosulphonyltoluene	None	None	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: Observe OSHA regulations for respirator use (29 CFR 1910.134). Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Respirator with combination filter for vapor/particulate.

Eye/face protection: Safety glasses with side-shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Gray
Odor: Slight
Odor threshold: Not available.
pH: Not available.
Vapor pressure: Not available.

IDH number: 1618150

Product name: Loctite® PL® Polyurethane Self-Leveling Concrete Crack Sealant
 Page 3 of 6

Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.15
Vapor density:	Not available.
Flash point:	85 °C (185°F) Certificate of Supplier
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	1.5 %; 36 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Contact with moisture, other materials that react with isocyanates, or temperatures above 350° F (177° C), may cause polymerization.
Hazardous decomposition products:	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. nitrogen oxides Aromatic isocyanates. carbon oxides. carbon monoxide Hydrogen cyanide.
Incompatible materials:	Oxidizing agents. Alcohols. Water. Strong bases.
Reactivity:	Not available.
Conditions to avoid:	Avoid moisture. Keep away from open flames, hot surfaces and sources of ignition. Prolonged exposure to heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
-------------------------------------	------------------------

Potential Health Effects/Symptoms

Inhalation:	As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been reported to cause lung damage. Dryness of nasal passages, sore throat, cough, tightness of chest, shortness of breath. Persons suffering from allergic reactions to isocyanates should avoid contact with the product. This product may cause sensitization by inhalation and skin contact. May cause respiratory tract irritation.
Skin contact:	Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals. This product may discolor the skin.
Eye contact:	Contact with eyes will cause irritation.
Ingestion:	Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Stoddard solvent, <0.1% Benzene	None	Central nervous system, Irritant
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity
Toluene-2,6-diisocyanate	None	Allergen, Bone Marrow, Corrosive, Eyes, Irritant, Mutagen, Respiratory, Some evidence of carcinogenicity
Gamma-glycidoxypropyl trimethoxysilane	None	Allergen, Irritant
Calcium oxide	None	Irritant, Corrosive, Eyes
4-isocyanatosulphonyltoluene	None	No Target Organs

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Stoddard solvent, <0.1% Benzene	No	No	No
Titanium dioxide	No	Group 2B	No
Toluene-2,6-diisocyanate	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Gamma-glycidoxypropyl trimethoxysilane	No	No	No
Calcium oxide	No	No	No
4-isocyanatosulphonyltoluene	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: U223: Toluene Diisocyanate. It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: Toluene-2,6-diisocyanate (CAS# 91-08-7).

CERCLA/SARA Section 302 EHS: Toluene-2,6-diisocyanate (CAS# 91-08-7).
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene-2,6-diisocyanate (CAS# 91-08-7).

CERCLA Reportable quantity: Toluene-2,6-diisocyanate (CAS# 91-08-7) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 09/09/2020

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.