## SAFETY DATA SHEET



Issuing Date 21-Nov-2014 Revision date 29-Feb-2024

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal Natural Stone Treatment

Other means of identification

Product Code(s) 40057 UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday 785-865-4200 NON-BUSINESS HOURS (INFOTRAC) 800-535-5053

## 2. HAZARDS IDENTIFICATION

#### Classification

Aspiration hazard	Category 1
Flammable liquids	Category 3

## Label elements

#### **Emergency Overview**

## Warning

#### Hazard statements

May be fatal if swallowed and enters airways

Flammable liquid and vapor





Appearance clear Physical state Liquid Odor Mild Petroleum

#### **Precautionary Statements - Prevention**

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/ and /lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

## Other information

- · May be harmful in contact with skin
- Causes mild skin irritation

10% of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Heavy Alkylate Naphtha (petroleum)	64741-65-7	60 - 100	*
Isobutyl triethoxysilane	17980-47-1	1 - 5	*
Ethyl Silicate	78-10-4	1 - 5	*

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

## **Description of first aid measures**

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice (show directions for use or safety data sheet if possible).

**Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

**Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a

physician.

**Ingestion** Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth

to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

## Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways. Mild skin irritant. May be harmful in contact

with skin.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Should not be released into the environment. Prevent product from entering drains. See

Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Use clean non-sparking tools to collect

absorbed material. Pick up and transfer to properly labeled containers. Take precautionary

measures against static discharges.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use personal protective equipment

as required. Avoid contact with skin, eyes or clothing.

## Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat. Keep

in properly labeled containers. Keep out of the reach of children.

**Incompatible materials** Incompatible with oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Silicate	TWA: 10 ppm	TWA: 100 ppm	IDLH: 700 ppm
78-10-4		TWA: 850 mg/m <sup>3</sup>	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 85 mg/m <sup>3</sup>
		(vacated) TWA: 85 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

**Engineering Controls** Showers

Eyewash stations

Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

> > **ASTM D 3278**

provided in accordance with current local regulations.

**General Hygiene Considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Liquid **Appearance** Odor Mild Petroleum clear

Color Slight yellow Odor threshold No information available

**Property** Values Remarks • Method Not Applicable

Not Applicable

-30 °C / -22 °F Melting point / freezing point °F Boiling point / boiling range

No information available Flash point 43 °C / 110 °F

**Evaporation rate** No information available Flammability (solid, gas) No information available

Flammability Limit in Air

**Upper flammability limit:** No information available Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available

Specific gravity 0.784 Water solubility negligible

Solubility in other solvents No information available **Partition coefficient** No information available

Autoignition temperature

Decomposition temperature

Kinematic viscosity

Dynamic viscosity

No information available

**Explosive properties**Not Applicable **Oxidizing properties**Not Applicable

## 10. STABILITY AND REACTIVITY

## Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

## Possibility of hazardous reactions

None under normal processing.

## **Conditions to avoid**

Heat, flames and sparks.

#### Incompatible materials

Incompatible with oxidizing agents.

## **Hazardous decomposition products**

Carbon monoxide. Carbon dioxide (CO2). Unidentified organic compounds. silicon dioxide. Formaldehyde.

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

**Product Information** May be fatal if swallowed and enters airways Mild skin irritant

**Inhalation** Avoid breathing vapors or mists.

**Eye contact** Avoid contact with eyes. May cause irritation.

**Skin Contact** Avoid contact with skin. May be harmful in contact with skin. Causes mild skin irritation.

**Ingestion** Do not taste or swallow. Harmful if swallowed. Potential for aspiration if swallowed.

**Component Information** 

Component information				
Chemical name	LD50/Oral	LD50/Dermal	Inhalation LC50	
Heavy Alkylate Naphtha (petroleum) 64741-65-7	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat)4 h	
Isobutyl triethoxysilane 17980-47-1	> 5000 mg/kg (Rat)		> 13750 mg/m³ (Rat) 4 h	
Ethyl Silicate 78-10-4	= 6270 mg/kg (Rat)	= 5878 mg/kg ( Rabbit )	< 1837 ppm (Rat) 4 h	

## Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May be fatal if swallowed and enters airways. May be harmful in contact with skin. Causes

mild skin irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

**Aspiration hazard** May be fatal if swallowed and enters airways.

## Numerical measures of toxicity - Product Information

Unknown acute toxicity 10% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6737 mg/kg
ATEmix (dermal) 2101 mg/kg mg/l
ATEmix (inhalation-dust/mist) 107.5 mg/l
ATEmix (inhalation-vapor) 1120.3 mg/l

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Heavy Alkylate Naphtha (petroleum) 64741-65-7	30000: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-	2: 48 h Mysidopsis bahia mg/L LC50
Isobutyl triethoxysilane 17980-47-1	-	85: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	-	-
Ethyl Silicate 78-10-4	-	245: 96 h Danio rerio mg/L LC50 semi-static	-	-

## Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

## 14. TRANSPORT INFORMATION

**DOT** Non-Hazardous/Non-Regulated (Under 119 Gallons per container)

UN number UN1866

UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

**IATA** 

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group |||

**IMDG** 

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

## 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

## SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

## **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

## **US State Regulations**

## **California Proposition 65**

This product contains the following Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethyl Silicate	X	X	X
78-10-4			

## **16. OTHER INFORMATION**

NFPA Health hazards 3 Flammability 2 Instability 0 Physical and chemical

properties -

HMIS Health hazards 3 Flammability 2 Physical hazards 0 Personal protection X

Prepared By Regulatory Department

**Issuing Date** 21-Nov-2014 **Revision date** 29-Feb-2024

Revision Note

SDS sections updated 9

Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

**End of Safety Data Sheet**