



CONCRETE OIL STAIN REMOVER

PRODUCT NO. 8670-06

PRODUCT USE:

- Removes oil stains and grease from concrete, paver and masonry surfaces.
- Low Odor
- Easy to rinse
- Heavy-duty commercial product

PRODUCT DESCRIPTION

QUIKRETE® Oil Stain Remover is a solvent-free specialty cleaner formulated for the removal of moderate to heavy motor oil stains and spills from concrete, paver and masonry surfaces.

SIZES:

- Gallon (3.8 L)

Coverage:

- 100-200 sq. ft. (9.3 – 18.6 sq. M) per gallon (3.8 L)

Application:

1. WEAR IMPERVIOUS GLOVES, such as nitrile. Protect eyes, skin & clothes. Wear rubber boots.
 2. Sweep and remove all soil and debris from the surface.
 3. Pour material directly from bottle onto oil stain. Surround the oil stain with liquid by about ½" (12 mm) on all sides.
 4. Allow the material to work for one minute.
 5. Scrub oil stain with a medium to stiff bristled nylon brush.
 6. Rinse thoroughly with water.
 7. A second application may be necessary to remove deep or old stains; rinse again.
- Exercise caution, as Oil Stain Remover may cause etching, particularly when left in contact for longer times. Oil Stain Remover should be test applied in an inconspicuous spot in order to optimize the application technique and to evaluate the effect, before treating the entire area.

PRECAUTIONS

- WEAR IMPERVIOUS GLOVES, such as nitrile, which are acid resistant. Wear safety glasses when handling product. Avoid prolonged contact with skin or inhalation of vapors. Use with adequate ventilation. Contains salt of organic acid. Wear rubber boots to protect feet. Slippery when wet.

DIVISION 3

Concrete Restoration &
Cleaning
03 90 00
Concrete Cleaner
03 91 00



- Contact with product may damage clothing.
- Do NOT mix with bleach, cleaners or other chemicals; chemical reactions may occur and produce poisonous gas.
- PREVENT RUN-OFF. This heavy duty product is not compatible with lawns and plants. Rinsing with large quantities of water dilutes the effect. Take appropriate precautions for vertical applications.
- Prevent contact with aluminum and other metals. Protect all non-concrete & masonry surfaces.
- Protect from freezing.
- For more information, refer to Safety Data Sheet (SDS) online at www.quikrete.com
- VOC = 14 g/L per EPA Method 24; Vapor Pressure of VOC <18 mm of Hg @ 20° C; Meets VOC requirements in all locations.

WARRANTY

The QUIKRETE® Companies, Inc. warrant this product to be of merchantable quality when used or applied in accordance with the instructions hereon. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at One Securities Centre, 3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.

** Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifications*