



R-SEAL 3000

Tape for Insulation Joints

ACCESSORIES
TAPE
FLASHING
LIQUID TAPE

PRODUCT DESCRIPTION

R-SEAL 3000 is a nominal 2mil high strength dead soft aluminum foil coated with cold weather acrylic pressure sensitive adhesive. The malleable foil conforms to irregular surfaces and applies easily to both fibrous and sheet metal ducts. R-SEAL 3000 excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.

COMPLIANCES

- UL723 (10/10 Flame Spread/Smoke Rating)
- DrJ TER 1212-03
- Specifically designed for cold weather conditions
- Approved component of the High Velocity Hurricane Zone system, R-Trac (HVHZ)
 - Florida Building Code Approval #FL16406
- Approved component for use within the ECOMAXci Wall Solution
 - Water-Resistive Barrier Component
AC71: ASTM E331, AATCC Test Method 127
 - Air Barrier System Component
ASTM E2357, CAN/ULC-S742 (A1)

PRODUCT CONSTRUCTION



PRODUCT DATA

Item	Roll Width	Roll Length	Rolls/Case
R-SEAL 3000-4	4 inches	150 feet	12

TYPICAL PHYSICAL PROPERTIES

Typical values shown in the chart below are not intended to be used for specification development. Technical data is believed to be true and accurate. Except when used within the ECOMAXci Wall

Test	Typical Value	Typical Value (metric)	Test Method
Product Thickness Ω	3.4 mils	0.08 mm	PSTC- 133
Backing Thickness (mils)	1.75 mils	0.04 mm	PSTC- 133
Peel Adhesion Δ	45 oz/in	12.5 N/25 mm	PSTC- 101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @15.2 kPa	PSTC-107
Tensile Strength	21 lb/in	94.9 N/25 mm	PSTC- 131
Elongation	4%	4%	PSTC- 131
Water Vapor Transmission	0.00 perm	0.0 ng/(Pa.s.m2)	ASTM D3833
Installation Temperature	0°F (min)	-17°C (min)	
Operating Temperature	-40 to 250°F	-40 to 121°C	

Ω - excluding liner Δ - 20 minute dwell



APPLICATION/INSTALLATION

- All surfaces to which the tape is to be applied should be free of moisture, oils, dust, dirt and other debris that could inhibit adhesion. Clean surfaces with a dry cloth as necessary.
 - Center tape over surface to be sealed, e.g., board joint, fastener plate, etc.
 - Do not allow the tape to form voids or buckle as it is applied.
 - Wipe tape firmly from center out with feathering tool or hand roller to smooth out wrinkles. Applying more pressure yields more surface contact, and therefore, creates a greater bond.
 - Do not tear tape, cut with scissors or knife.
 - NOTE: For optimal performance, maintain a minimum of 3/4" coverage beyond the area to be sealed.
-

Rmax Sales Offices and Plant Locations

Central:

13524 Welch Road
Dallas, Texas 75244

Phone: 972-387-4500
Fax: 972-387-4673
Toll Free: 1-800-527-0890

E-mail us at rmax@rmax.com or visit our website www.rmax.com

East:

1649 South Batesville Road
Greer, South Carolina 29650

Phone: 864-297-1382
Fax: 864-234-7548
Toll Free: 1-800-845-4455

West:

210 Lyon Drive
Fernley, Nevada 89408

Phone: 775-575-4849
Fax: 775-575-5035
Toll Free: 1-800-762-9462

2021-08



Proudly Made and
Engineered in the U.S.A.

